



CMP Plenum Shld

Application: Low voltage plenum (CMP) cables are used in drop ceilings for sound, security and PA systems. The overall shield provides additional protection from electrostatic noise and crosstalk.

Conductor: Stranded bare copper

Insulation: Low smoke PVC with CMP rating

Shield: Overall foil shield

Jacket: Low smoke PVC with CMP rating

Flame Test: Steiner Tunner Flame Test (UL 910)

Note: 22 AWG -16 AWG rated CMP | 14 AWG - 12 AWG rated CL3P

Color Code: [Click here](#)

DWC Part #	AWG Size	# of Conductors	# of Strands	Insulation Thickness In Mils	Jacket Thickness In Mils	O.D. Inch	Weight Lbs/M
2202SCMP	22	2	7	8	15	0.13	15
2203SCMP	22	3	7	8	15	0.14	17
2204SCMP	22	4	7	8	15	0.15	19
2206SCMP	22	6	7	8	15	0.17	28
2208SCMP	22	8	7	8	15	0.19	36
2210SCMP	22	10	7	8	15	0.21	39
2212SCMP	22	12	7	8	15	0.22	47
2002SCMP	20	2	7	8	15	0.14	18
2003SCMP	20	3	7	8	15	0.15	22
2004SCMP	20	4	7	8	15	0.17	28
2008SCMP	20	8	7	8	15	0.21	45
2012SCMP	20	12	7	10	15	0.27	61
1802SCMP	18	2	7	8	15	0.16	21
1803SCMP	18	3	7	8	15	0.17	29
1804SCMP	18	4	7	8	15	0.19	35
1806SCMP	18	6	7	8	15	0.22	51
1808SCMP	18	8	7	10	15	0.25	65
1810SCMP	18	10	7	8	15	0.29	79
1812SCMP	18	12	7	8	15	0.3	94
1602SCMP	16	2	19	8	15	0.18	29
1603SCMP	16	3	19	8	15	0.19	38
1604SCMP	16	4	19	10	15	0.22	48
1606SCMP	16	6	19	10	15	0.25	68
1608SCMP	16	8	19	10	15	0.29	93

1402SCMP	14	2	19	8	15	0.22	44
1403SCMP	14	3	19	8	15	0.23	60
1404SCMP	14	4	19	8	15	0.26	78
1202SCMP	12	2	19	8	15	0.24	62

*Product details and specifications are subject to manufacturing variations and accepted industry tolerances.
Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.*

fastQuote™

☎ 888.439.2947

🌐 distributorwire.com

📞 720.317.2278