



XLPTC – 12 AWG

Application: XLP/PVC tray cables are used in power and control applications in the industrial and commercial markets where additional flame retardance is required. It can be direct buried or installed in cable trays. This product has a XHHW-2 rating, TC-ER rated.

Conductor: Stranded bare copper

Insulation: XLP (Cross-Linked Polyethylene)

Jacket: PVC

Color Code: [Click here](#)

DWC Part #	AWG Size	# of Conductors	# of Strands	Ground Wire AWG	Insulation Thickness In Mils	Jacket Thickness In Mils	O.D. Inch	Weight Lbs/M
1202XLPTC	12	2	7	N/A	30	45	.25 X .41	95
1203XLPTC	12	3	7	N/A	30	45	0.43	135
1203XLPGTC	12	3	7	12	30	45	0.43	145
1204XLPTC	12	4	7	N/A	30	45	0.47	168
1205XLPTC	12	5	7	N/A	30	60	0.55	214
1207XLPTC	12	7	7	N/A	30	60	0.6	290
1209XLPTC	12	9	7	N/A	30	60	0.69	360
1212XLPTC	12	12	7	N/A	30	60	0.76	460
1219XLPTC	12	19	7	N/A	30	80	0.95	663
1225XLPTC	12	25	7	N/A	30	80	1.08	850
1230XLPTC	12	30	7	N/A	30	80	1.17	1003
1237XLPTC	12	37	7	N/A	30	80	1.27	1211

Product details and specifications are subject to manufacturing variations and accepted industry tolerances. Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.

fastQuote™

📞 888.439.2947

🌐 distributorwire.com

📠 720.317.2278