



## 22 AWG-12 AWG Non-Shielded CMR-Riser

DWC Part #	# of Conductors	# of Strands	Insulation Thickness In Mils	Jacket Thickness In Mils	O.D. Inch	Weight Lbs/M
2202CMR	2	7	8	15	0.12	9
2203CMR	3	7	8	15	0.14	13
2204CMR	4	7	8	15	0.16	17
2206CMR	6	7	8	15	0.17	22
2208CMR	8	7	8	15	0.18	27
2212CMR	12	7	8	15	0.22	42
2002CMR	2	7	8	15	0.13	11
2003CMR	3	7	8	15	0.14	18
2004CMR	4	7	8	17	0.14	22
1802CMR	2	7	10	15	0.15	19
1803CMR	3	7	10	15	0.17	26
1804CMR	4	7	9	15	0.19	31
1806CMR	6	7	9	15	0.23	46
1808CMR	8	7	9	15	0.25	59
1812CMR	12	7	9	15	0.29	86
1602CMR	2	19	9	15	0.18	26
1603CMR	3	19	9	15	0.19	35
1604CMR	4	19	9	15	0.21	47
1402CMR	2	19	13	15	0.22	41
1403CMR	3	19	13	15	0.24	55
1404CMR	4	19	13	15	0.26	72
1202CMR	2	19	13	15	0.26	57

Low voltage riser PVC (CMR) cables are used in various applications such as sound, security and PA systems.

**Conductor:** Stranded bare copper

**Insulation:** PVC with CMR rating

**Jacket:** PVC with CMR rating

**Flame Test:** UL Flame Test (1666)

**Note:** 22 AWG -16 AWG rated CMR | 14 AWG - 12 AWG rated CL3R

**Color Code:** [Click here](#)