



## AWG (Bare Cu) EPR/USE

AWG (Bare Cu), EPR/USE, Direct Burial, 600V are recommended for use in harsh environments in a broad range of commercial, industrial and utility applications where reliability and maximum performance is required. Approved for installation in conduits, ducts, cable tray when CT rated, direct burial or other approved raceways with maximum conductor temperature of 90°C in wet or dry locations.

DWC Part #	O.D. Inch	Weight Lbs/M
1201EPRUSE	0.19	34
1401EPRUSE	0.17	25
1001EPRUSE	0.21	48
0801EPRUSE	0.27	78
0601EPRUSE	0.31	114
0201EPRUSE	0.42	254
0101EPRUSE	0.49	327
1/001EPRUSE	0.53	402
2/001EPRUSE	0.58	495
3/001EPRUSE	0.63	613
4/001EPRUSE	0.69	759
25001EPRUSE	0.77	905
35001EPRUSE	0.87	1235
50001EPRUSE	1	1663
75001EPRUSE	1.22	2573
100001EPRUSE	1.37	3381
0401EPRUSE	0.36	169

*Product details and specifications are subject to manufacturing variations and accepted industry tolerances.  
Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.*

**fastQuote™**

📞 888.439.2947

🌐 distributorwire.com

📞 720.317.2278