



Type W Multi Conductor 1/0 – 500 MCM

Application: Type W is a 2KV (2000 volts) portable/mining cord frequently used in industrial mining applications and heavy duty service for power supply where high flexibility is needed.

Conductor: Extra flexible bare or tinned copper conductors

Insulation: Ethylene propylene diene monomer (EPDM)

Jacket: CPE

Notes: Round Construction / MSHA Approved

DWC Part #	AWG Size	# of Conductors	# of Strands	Insulation Thickness In Mils	Jacket Thickness In Mils	O.D. Inch	Weight Lbs/M
1/002W	1/0	2	259	80	165	1.52	1500
1/003W	1/0	3	259	80	203	1.61	2165
1/004W	1/0	4	259	80	193	1.76	2693
1/005W	1/0	5	259	80	188	2.03	3065
2/002W	2/0	2	259	80	177	1.62	1805
2/003W	2/0	3	259	80	198	1.72	2520
2/004W	2/0	4	259	80	182	1.89	3326
2/005W	2/0	5	259	80	192	2.18	3775
3/002W	3/0	2	259	80	182	1.74	2075
3/003W	3/0	3	259	80	185	1.85	3180
3/004W	3/0	4	259	80	184	2.03	4068
3/005W	3/0	5	259	80	182	2.34	4645
4/002W	4/0	2	259	80	199	1.9	2585
4/003W	4/0	3	259	80	207	2.02	3360
4/004W	4/0	4	259	80	221	2.19	4260
4/005W	4/0	5	259	80	203	2.54	5515
25003W	250	3	427	95	267	2.36	4645
35003W	350	3	427	95	283	2.5	5225
50003W	500	3	427	95	295	3	7985
50004W	500	4	1921	95	310	3.34	14726

Product details and specifications are subject to manufacturing variations and accepted industry tolerances. Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.

