



## SEOOW

**Application:** SEOOW portable cord is used in extreme environments where a flexible cord is required and extreme temperatures are found. Standard jacket color is high grade yellow. Reliable against acids/oils and in low temps. This product is rated for 600V and 105C.

**Conductor:** Extra flexible bare copper

**Insulation:** Thermoplastic elastomer

**Jacket:** Thermoplastic elastomer – Available in multiple colors

**Notes:** MSHA Approved – Power sizes (8 AWG and larger) are Non UL

DWC Part #	AWG Size	# of Conductors	# of Strands	Insulation Thickness In Mils	Jacket Thickness In Mils	O.D. Inch	Weight Lbs/M
1802SEOOW	18	2	16	31	62	0.34	57
1803SEOOW	18	3	16	31	62	0.36	69
1804SEOOW	18	4	16	31	62	0.39	78
1602SEOOW	16	2	26	31	62	0.37	69
1603SEOOW	16	3	26	31	62	0.39	80
1604SEOOW	16	4	26	31	62	0.42	96
1402SEOOW	14	2	41	47	82	0.5	124
1403SEOOW	14	3	41	47	82	0.53	149
1404SEOOW	14	4	41	47	82	0.57	180
1202SEOOW	12	2	65	46	97	0.57	152
1203SEOOW	12	3	65	46	97	0.6	197
1204SEOOW	12	4	65	46	97	0.64	240
1002SEOOW	10	2	104	46	97	0.62	193
1003SEOOW	10	3	104	46	97	0.66	257
1004SEOOW	10	4	104	46	97	0.7	313
0802SEOOW	8	2	96	48	90	0.66	233
0803SEOOW	8	3	96	48	90	0.7	327
0804SEOOW	8	4	96	48	100	0.78	420
0602SEOOW	6	2	96	48	90	0.74	302
0603SEOOW	6	3	96	48	100	0.81	458
0604SEOOW	6	4	96	48	100	0.88	599
0402SEOOW	4	2	96	48	125	0.9	464
0403SEOOW	4	3	96	48	125	0.98	667
0404SEOOW	4	4	96	48	125	1.09	865
0202SEOOW	2	2	96	50	128	1.09	715
0203SEOOW	2	3	119	50	128	1.15	971
0204SEOOW	2	4	119	50	128	1.26	1225

*Product details and specifications are subject to manufacturing variations and accepted industry tolerances.  
Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.*

**fastQuote™**

☎ 888.439.2947

🌐 distributorwire.com

📠 720.317.2278