



SOOW – 14 AWG

SOOW portable cord is used on industrial and processing equipment, cranes and hoist, motors and other equipment when flexibility and resistance to solvents, oils, flame and moisture are required. Suitable for shallow/medium water immersion. This product is rated for 600V and 90C.

Conductor: Stranded bare copper

Insulation: Thermoplastic elastomer

Jacket: CPE

Notes: MSHA approved for hard usage

Color Code: [Click Here](#)

DWC Part #	AWG Size	# of Conductors	# of Strands	Insulation Thickness In Mils	Jacket Thickness In Mils	O.D. Inch	Weight Lbs/M
1402SOOW	14	2	41	45	80	0.5	135
1403SOOW	14	3	41	45	80	0.53	170
1404SOOW	14	4	41	45	80	0.57	205
1405SOOW	14	5	41	45	95	0.65	275
1406SOOW	14	6	41	45	95	0.71	315
1407SOOW	14	7	41	45	95	0.71	345
1408SOOW	14	8	41	45	95	0.76	385
1409SOOW	14	9	41	45	95	0.83	410
1410SOOW	14	10	41	45	95	0.83	430
1412SOOW	14	12	41	45	95	0.87	485
1414SOOW	14	14	41	45	110	1	590
1416SOOW	14	16	41	45	110	1.03	665
1418SOOW	14	18	41	45	110	1.1	710
1420SOOW	14	20	41	45	110	1.15	780
1424SOOW	14	24	41	45	125	1.26	985
1430SOOW	14	30	41	45	125	1.34	1130
1437SOOW	14	37	41	45	125	1.48	1330

Product details and specifications are subject to manufacturing variations and accepted industry tolerances. Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.

fastQuote™