## Comparison

o o mpanio o m				
Earphones	VERSE	APOLLO 7s	MUSE 5	
	•0	•••	••••	••••
Features	A New Revolution In Sound Quality - Graphene Driver	(O) Advanced 3D EratoSurround™	(O) Advanced 3D EratoSurround™	14.2mm Diaphragm Driver with Dominate Bass
	Pantented SpinFit Eartips	Comply Eartips	Patented FitSeal™ Sleeves	Adjustable Earhooks with Metal Core
	Up To 15 Hours of Battery Playback	Up To 9 Hours of Battery Playback	Up To 12 Hours of Battery Playback	Up To 8 Hours of Battery Playback
	Magnetic Charging Case (Auto-PowerOn supported)	Aluminum 360° Charging Case	Charging Case	Carrying Case
	Single-Touch Multifunction	Single-Touch Multifunction	Single-Touch Multifunction	Multifunction Buttons
	O Built In Mic	Puilt In Mic	Duilt In Mic	O Built In Mic
	O IPX5 Waterproof	IPX5 Waterproof	IPX5 Waterproof	IPX5 Waterproof
	<b>8</b> ° <b>4.2</b> SBC AAC	3° 4.1 SBC AAC CSF	3° 4.1 SBC AAC GS	\$ 4.2 SBC AAC GIT
SPECIFICATIONS / Eraphone				
			PHOHE	
Bluetooth version	4.2	4.1	4.1	4.2
Bluetooth version  Dimensions				4.2 51mm x 34mm x 46mm
	4.2	4.1	4.1	
Dimensions	4.2 16.5mm x 15.5mm x 25.5mm	4.1 16.2mm x 15.4mm x 22.2mm	4.1 25.2mm x 20mm x 30mm	51mm x 34mm x 46mm
Dimensions  Weight	4.2 16.5mm x 15.5mm x 25.5mm 4.5g	4.1 16.2mm x 15.4mm x 22.2mm 4g	4.1 25.2mm x 20mm x 30mm 8.5g	51mm x 34mm x 46mm 14g
Dimensions  Weight  Audio Codec	4.2 16.5mm x 15.5mm x 25.5mm 4.5g SBC \ AAC	4.1  16.2mm x 15.4mm x 22.2mm  4g  SBC \ AAC \ aptX	4.1  25.2mm x 20mm x 30mm  8.5g  SBC \ AAC \ aptX	51mm x 34mm x 46mm  14g  SBC \ AAC \ aptX  14.2mm Comply
Dimensions  Weight  Audio Codec  Driver	4.2  16.5mm x 15.5mm x 25.5mm  4.5g  SBC \ AAC  5.8mm Graphene Driver	4.1  16.2mm x 15.4mm x 22.2mm  4g  SBC \ AAC \ aptX  5.8mm Micro Driver	4.1  25.2mm x 20mm x 30mm  8.5g  SBC \ AAC \ aptX  5.8mm Micro Driver	51mm x 34mm x 46mm  14g  SBC \ AAC \ aptX  14.2mm Comply Diaphragm Driver
Dimensions  Weight  Audio Codec  Driver  Battery capacity	4.2  16.5mm x 15.5mm x 25.5mm  4.5g  SBC \ AAC  5.8mm Graphene Driver  60mAh	4.1  16.2mm x 15.4mm x 22.2mm  4g  SBC \ AAC \ aptX  5.8mm Micro Driver  50mAh	4.1  25.2mm x 20mm x 30mm  8.5g  SBC \ AAC \ aptX  5.8mm Micro Driver  100mAh	51mm x 34mm x 46mm  14g  SBC \ AAC \ aptX  14.2mm Comply Diaphragm Driver  130mAh
Dimensions  Weight  Audio Codec  Driver  Battery capacity  Water proof	4.2  16.5mm x 15.5mm x 25.5mm  4.5g  SBC \ AAC  5.8mm Graphene Driver  60mAh  IPX5	4.1  16.2mm x 15.4mm x 22.2mm  4g  SBC \ AAC \ aptX  5.8mm Micro Driver  50mAh  IPX5	4.1  25.2mm x 20mm x 30mm  8.5g  SBC \ AAC \ aptX  5.8mm Micro Driver  100mAh	51mm x 34mm x 46mm  14g  SBC \ AAC \ aptX  14.2mm Comply Diaphragm Driver  130mAh  IPX5
Dimensions  Weight  Audio Codec  Driver  Battery capacity  Water proof  Stabilizers	4.2  16.5mm x 15.5mm x 25.5mm  4.5g  SBC \ AAC  5.8mm Graphene Driver  60mAh  IPX5	4.1  16.2mm x 15.4mm x 22.2mm  4g  SBC \ AAC \ aptX  5.8mm Micro Driver  50mAh  IPX5  YES	4.1  25.2mm x 20mm x 30mm  8.5g  SBC \ AAC \ aptX  5.8mm Micro Driver  100mAh  IPX5  FitSeal	51mm x 34mm x 46mm  14g  SBC \ AAC \ aptX  14.2mm Comply Diaphragm Driver  130mAh  IPX5  Flexible clasp
Dimensions  Weight  Audio Codec  Driver  Battery capacity  Water proof  Stabilizers  3D Surround	4.2  16.5mm x 15.5mm x 25.5mm  4.5g  SBC \ AAC  5.8mm Graphene Driver  60mAh  IPX5  x	4.1  16.2mm x 15.4mm x 22.2mm  4g  SBC \ AAC \ aptX  5.8mm Micro Driver  50mAh  IPX5  YES  ERATOSURROUND  Left / Right  x	4.1  25.2mm x 20mm x 30mm  8.5g  SBC \ AAC \ aptX  5.8mm Micro Driver  100mAh  IPX5  FitSeal  ERATOSURROUND	51mm x 34mm x 46mm  14g  SBC \ AAC \ aptX  14.2mm Comply Diaphragm Driver  130mAh  IPX5  Flexible clasp
Dimensions  Weight  Audio Codec  Driver  Battery capacity  Water proof  Stabilizers  3D Surround  Master	4.2  16.5mm x 15.5mm x 25.5mm  4.5g  SBC \ AAC  5.8mm Graphene Driver  60mAh  IPX5  x  Left	4.1  16.2mm x 15.4mm x 22.2mm  4g  SBC \ AAC \ aptX  5.8mm Micro Driver  50mAh  IPX5  YES  ERATOSURROUND  Left / Right	4.1  25.2mm x 20mm x 30mm  8.5g  SBC \ AAC \ aptX  5.8mm Micro Driver  100mAh  IPX5  FitSeal  ERATOSURROUND  Left	51mm x 34mm x 46mm  14g  SBC \ AAC \ aptX  14.2mm Comply Diaphragm Driver  130mAh  IPX5  Flexible clasp  x  Left
Dimensions  Weight  Audio Codec  Driver  Battery capacity  Water proof  Stabilizers  3D Surround  Master  Auto Power-On	4.2  16.5mm x 15.5mm x 25.5mm  4.5g  SBC \ AAC  5.8mm Graphene Driver  60mAh  IPX5  x  x  Left  Yes  SpinFit eartips (S/M/L)	4.1  16.2mm x 15.4mm x 22.2mm  4g  SBC ` AAC ` aptX  5.8mm Micro Driver  50mAh  IPX5  YES  ERATOSURROUND  Left / Right  x  Silicon tips (S/M/L)	4.1  25.2mm x 20mm x 30mm  8.5g  SBC ` AAC ` aptX  5.8mm Micro Driver  100mAh  IPX5  FitSeal  ERATOSURROUND  Left  x  Silicon tips (XS/S/M/L)	51mm x 34mm x 46mm  14g  SBC \ AAC \ aptX  14.2mm Comply Diaphragm Driver  130mAh  IPX5  Flexible clasp  x  Left
Dimensions  Weight  Audio Codec  Driver  Battery capacity  Water proof  Stabilizers  3D Surround  Master  Auto Power-On	4.2  16.5mm x 15.5mm x 25.5mm  4.5g  SBC \ AAC  5.8mm Graphene Driver  60mAh  IPX5  x  x  Left  Yes  SpinFit eartips (S/M/L)	4.1  16.2mm x 15.4mm x 22.2mm  4g  SBC ` AAC ` aptX  5.8mm Micro Driver  50mAh  IPX5  YES  ERATOSURROUND  Left / Right  x  Silicon tips (S/M/L) Comply T-600 (S/M/L)	4.1  25.2mm x 20mm x 30mm  8.5g  SBC ` AAC ` aptX  5.8mm Micro Driver  100mAh  IPX5  FitSeal  ERATOSURROUND  Left  x  Silicon tips (XS/S/M/L)	51mm x 34mm x 46mm  14g  SBC \ AAC \ aptX  14.2mm Comply Diaphragm Driver  130mAh  IPX5  Flexible clasp  x  Left
Dimensions  Weight  Audio Codec  Driver  Battery capacity  Water proof  Stabilizers  3D Surround  Master  Auto Power-On  Eartip	4.2  16.5mm x 15.5mm x 25.5mm  4.5g  SBC \ AAC  5.8mm Graphene Driver  60mAh  IPX5  x  Left  Yes  SpinFit eartips (S/M/L)	4.1  16.2mm x 15.4mm x 22.2mm  4g  SBC \ AAC \ aptX  5.8mm Micro Driver  50mAh  IPX5  YES  ERATOSURROUND  Left / Right  x  Silicon tips (S/M/L) Comply T-600 (S/M/L)	4.1  25.2mm x 20mm x 30mm  8.5g  SBC \ AAC \ aptX  5.8mm Micro Driver  100mAh  IPX5  FitSeal  ERATOSURROUND  Left  x  Silicon tips (XS/S/M/L)	51mm x 34mm x 46mm  14g  SBC \ AAC \ aptX  14.2mm Comply Diaphragm Driver  130mAh  IPX5  Flexible clasp  x  Left  x  Silicon tips (S/M/L)
Dimensions  Weight  Audio Codec  Driver  Battery capacity  Water proof  Stabilizers  3D Surround  Master  Auto Power-On  Eartip  Charging case	4.2  16.5mm x 15.5mm x 25.5mm  4.5g  SBC \ AAC  5.8mm Graphene Driver  60mAh  IPX5  x  x  Left  Yes  SpinFit eartips (S/M/L)  SF	4.1  16.2mm x 15.4mm x 22.2mm  4g  SBC \ AAC \ aptX  5.8mm Micro Driver  50mAh  IPX5  YES  ERATOSURROUND  Left / Right  x  Silicon tips (S/M/L) Comply T-600 (S/M/L)  PECIFICATIONS / Charge	4.1  25.2mm x 20mm x 30mm  8.5g  SBC \ AAC \ aptX  5.8mm Micro Driver  100mAh  IPX5  FitSeal  ERATOSURROUND  Left  x  Silicon tips (XS/S/M/L)  ging case  Elastic fastening	51mm x 34mm x 46mm  14g  SBC \ AAC \ aptX  14.2mm Comply Diaphragm Driver  130mAh  IPX5  Flexible clasp  x  Left  x  Silicon tips (S/M/L)
Dimensions  Weight  Audio Codec  Driver  Battery capacity  Water proof  Stabilizers  3D Surround  Master  Auto Power-On  Eartip  Charging case  Dimensions	4.2  16.5mm x 15.5mm x 25.5mm  4.5g  SBC \ AAC  5.8mm Graphene Driver  60mAh  IPX5  x  x  Left  Yes  SpinFit eartips (S/M/L)  SF  Magnetic Charger  55mm x 55mm x 25.5mm	4.1  16.2mm x 15.4mm x 22.2mm  4g  SBC \ AAC \ aptX  5.8mm Micro Driver  50mAh  IPX5  YES  ERATOSURROUND  Left / Right  x  Silicon tips (S/M/L) Comply T-600 (S/M/L)  PECIFICATIONS / Charge  Patent 360° placement  62.5mm x 40mm x 25.5mm	4.1  25.2mm x 20mm x 30mm  8.5g  SBC \ AAC \ aptX  5.8mm Micro Driver  100mAh  IPX5  FitSeal  ERATOSURROUND  Left  x  Silicon tips (XS/S/M/L)  ging case  Elastic fastening  78.1mm x 39.2mm x 39.77mm	51mm x 34mm x 46mm  14g  SBC \ AAC \ aptX  14.2mm Comply Diaphragm Driver  130mAh  IPX5  Flexible clasp  x  Left  x  Silicon tips (S/M/L)  Micro USB