

Genelec 1022A

System Specifications

Lower cut-off frequency, -3 dB:	38 Hz
Upper cut-off frequency, -3 dB:	20 kHz
Passband response tolerance, free field	± 2 dB
Maximum continuous sine wave acoustic output @ 1m on axis in free field	> 108 dB
Maximum peak acoustic output per pair behind a console, 1.7 m from the engineer	> 121 dB
-9 dBu will produce 102 dB SPL in free field @ 1 m on axis with the controls at 'CAL' position	
Self generated noise level in free field @ 1m on axis	< 15 dB (A)
Harmonic distortion at 98 dB SPL @ 1m on axis	
f < 200 Hz	< 3 %
f > 200 Hz	< 1 %
Horizontal treble radiation loss at 30 deg off axis	
f = 10 kHz	< 3 dB
f = 15 kHz	< 3 dB
Drivers	
Bass	300 mm cone
Mid	80 mm cone
Treble	9 x 65 mm ribbon
Weight	25 kg
Dimensions:	
Height	735 mm
Width	405 mm
Depth	365 mm

Amplifier

Input connector	XLR female
Bass amplifier output power:	
continuous	150 W
transients	190 W
Middle amplifier output power:	
continuous	32 W
transients	150 W
Treble amplifier output power:	
continuous	7 W
transients	150 W
Amplifier system distortion at nominal output	< 0,05 %
THD	< 0,05 %

SMPTE-IM CCIF-IM DIM100	< 0,05 %
Mains voltage, specifications applicable operation	220 VAC 198...242 VAC
Other mains voltage specifications available on request	
Power consumption, idle full output	30 VA 400 VA
Crossover	
Input impedance	10 kOhm balanced
Input level for maximum output, continuously variable	-3...+16 dBu 12 dB @ 15
Subsonic attenuation	Hz
Ultrasonic attenuation	3 dB @ 30 kHz
Crossover frequency bass / midrange midrange / treble	400 Hz 3.8 kHz
Tone control operation range in 1 dB steps bass middle treble	0...-6 dB 0...-6 dB 0...-6 dB
Bass roll-off filter, 2 dB steps	-6...0 dB @ 40 Hz

All data subject to change without prior notice