


GENELEC®

Genelec 9101A-B Wireless Volume Control



The Genelec 9101A-B Wireless Volume Control is designed for use with Genelec F One and F Two subwoofers and the GLM Network Adaptor. This instruction leaflet covers the use with the GLM Adaptor, for use with the F Series subwoofers please refer to the subwoofer's operating manual. The 9101A-B is available in white (9101AW-B) and black (9101AM-B) colour.

The 9101A-B uses radio frequency communication and does not need a line of sight to the GLM adaptor. The typical maximum operating range is 30 meters.

The 9101A-B works with the GLM adaptor after pairing:

The pairing happens during the first 10 seconds after powering up the GLM Adaptor. To pair the 9101A-B with a GLM Adaptor, first press and hold '+ volume up' button and then press and hold '- volume down' button on the 9101A-B. To check that the pairing has succeeded, observe the back LEDs on the GLM Adaptor. The LEDs will start blinking after successful pairing when you press any button on the 9101A-B. If you do not observe this, repeat the pairing process.

When the GLM adaptor is connected to a computer running the GLM software, the 9101A-B can adjust the audio output volume level, select between loudspeaker groups, turn the system on and off and mute the system. When using the GLM adaptor in standalone mode with an USB power supply and no computer, the 9101A-B does not change loudspeaker groups. All other functions listed above work. For the standalone use the acoustic settings can be stored to the monitors and they are loaded when monitors turn ON.