



### BELUGA 295 C

New spearhead, its high-end construction combined with nano ceramic technology provides a deep black shade, allowing privacy while effectively rejecting heat.



SOLAR SCREEN® Warranty  
**15 YEARS**



Storage from -5°C to +40°C  
**3 YEARS**



REACH RoHS compliant  
**RESPECTED**

### WIDTHS AVAILABLE:

↔ **152 cm**

### TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	1 %
Visible light transmission	5 %
Reflection of external visible light	6 %
Reflection of internal visible light	5 %
Total solar energy rejected	67 %
Total solar energy rejected 2*	%
Solar ratio :	
Solar energy reflection	7 %
Solar energy absorption	76 %
Solar energy transmission	16 %
Reduction in Solar Glare	94 %
g-value	
u-value	
Rejected Infrared (760-2500 nm)	85%
Shading coefficient	
Installation type : Interior	
Roll length	30.5 m
Film composition	PET
Thickness	50 µ

Colour from the outside : BLACK

### CONSTRUCTION

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. High optical quality dyed polyester without optical distortion
3. Bonding adhesive
4. High optical quality dyed polyester, with anti-heat nano cermaic particles
5. PS adhesive, glass polymerization within 15 days
6. Protection release liner, disposable after installation



### MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

*Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.*

### INSTALLATION ADVICE

Vertical installation and on standard glass surface\*\*

Clear single pane	!
Tinted single pane	×
Reflective tinted single pane	!
Clear double pane	×
Tinted double pane	×
Reflective tinted double pane	!
Gas-filled double pane - Low E	×
STADIP EXT. clear double pane	×
STADIP INT. clear double pane	×

✓ Yes ! Caution ✗ Not recommended

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m<sup>2</sup>, contact us for definitive details or to obtain a thermal chock analysis report.