

TECHNICAL NOTE: WRB COATINGS AND ROOF UNDERLAYMENTS APPLIED TO LP® FLAMEBLOCK® FIRE-RATED SHEATHING

Some water-resistive coatings and roof underlayments may be used in conjunction with LP® FlameBlock® Fire-Rated Sheathing. In general, most coatings and underlayments designed for masonry, concrete, or gypsum surfaces are chemically compatible with the Pyrotite® surface of LP FlameBlock Fire-Rated OSB. The LP FlameBlock sheathing should be cleaned of all residue, dust, dirt, and loose particles prior to commencing application.

The following products have been evaluated and demonstrated chemical compatibility with LP FlameBlock sheathing by the manufacturers. For detailed application procedures, please follow the manufacturers instructions. Consult the manufacturer should additional confirmation be required regarding adhesion properties onto LP FlameBlock Fire-Rated OSB.

BASF	W.R. MEADOWS	GRACE	DRYVIT	HENRY	DUPONT
Sonoshield® HLM® 5000 Sensershield-R	Air-Shield® LMP	Perm-A-Barrier® VP Perm-A-Barrier® VPS Vycor® enV™	Backstop® NT™	<u>Air Barriers:</u> Air-Bloc® 16MR Air-Bloc® 17MR Air-Bloc® 31MR Air-Bloc® 32MR Air-Bloc® 33MR Blueskin® VP160* Blueskin® VP100 Blueskin® SA Blueskin® Metalclad <u>Roof Underlayments:</u> Blueskin® PE200HT Blueskin® RF200TM Blueskin® RF200 Eaveguard®	Tyvek® Fluid Applied WB

*Used with a Henry approved primer

PROSOCO	DORKEN	DELTA	STO	VAPROSHIELD	TREMCO	SOPREMA
R-Guard® Spray Wrap MVP Cat-5 R-Guard® VB Joint and Seam Filler FastFlash®	Delta®-Vent SA	Delta®-Vent SA Delta®-Stratus SA Delta®-Fassade SA	Sto Gold Coat®	WrapShield SA® RevealShield SA® VaproLiquiFlash	ExoAir® 230 ExoAir® 130 ExoAir® 220 ExoAir® 120 ExoAir® 110AT Enviro-Dri®	Sopraseal® LM 204 VP Sopraseal® LM 202 VP Sopraseal® LM 203 Sopraseal® Stick VP Sopraseal® Stick 1100T Colphene® 3000



For more information, please visit LPCorp.com/FlameBlock or call 1-888-820-0325.

⚠ WARNING: Drilling, sawing, sanding or machining wood products can expose you to wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection. For more information, go to www.P65Warnings.ca.gov/wood.

© 2025 Louisiana-Pacific Corporation. All rights reserved. Sustainable Forestry Initiative and associated logo are registered trademarks of the Sustainable Forestry Initiative, Inc. Sto Gold Coat is the registered trademark of Sto SE & Co, KGAA Ltd Partnership. Sonoshield and HLM are registered trademarks of the BASF Group. PROSOCO, PROSOCO R Guard, and FastFlash are registered trademarks of Boyer Industries Corporation. Backstop and NT are trademarks of Dryvit Systems, Inc. Tyvek is a registered trademark of E. I. du Pont de Nemours and Company or its affiliates. Perm-A-Barrier, Vycor, and enV are trademarks of GCP Applied Technologies Inc. Air-Bloc, BlueSkin, BlueSkin VP, and EaveGuard are registered trademarks of Henry Company Canada, Inc. Delta is a registered trademark of Dörken Systems Inc. Air-Shield is a registered trademark of W.R. Meadows, Inc. RevealShield SA and WrapShield SA are registered trademarks of VaproShield LLC. ExoAir is a registered trademark of Tremco Inc. Enviro-Dri is a registered trademark of Tremco Barrier Solutions, Inc. SOPREMA AND COLPHENE are registered trademarks of Holding Soprema Societe Anonyme France; SOPRASEAL is a registered trademark of Soprema, Inc. All other trademarks are owned by Louisiana-Pacific Corporation. Specifications subject to change without notice. LPFB0169 3/2025