


















# EN: Quick Start Guide

Follow the instructions in this Quick Start Guide to connect your cable modem or gateway.

**Before you start:** Carefully read the Safety Instructions and Regulatory Notices document included in your package before continuing with the installation of your cable modem or gateway.

**Important:** Before you connect your device, establish an Internet service account with your preferred Internet service provider. When establishing an account, your Internet service provider may ask you to provide information listed on the device label, such as the device serial number (S/N) or MAC address.

- 1 CABLE** ( (optional): If your device supports digital telephone service (VoIP), connect one end of a telephone cable to a telephone outlet in your home or to a telephone or fax machine. Connect the other end of the cable to the first **TELEPHONE** port on the back of the device. The first port is labeled **1** or **1/2** depending on the device model.
- 4 POWER** (/ / / ): Connect the barrel end () of the power adapter (included) to the **POWER** input on the back of the device. Then, plug the adapter into a wall outlet. If your device has a power switch (/ ) on the back of the device, make sure that the switch is in the ON position.
- 5** Wait for the **POWER** (/ ) and (if applicable) **WIRELESS** () , **DS** (/ ) , **US** (/ ) , **ONLINE** (/ ) LEDs on the front panel to stop blinking and remain on continuously. It may take up to 10 minutes for all LEDs to stop blinking.

You are now ready to surf the Internet and use other networked devices.

**Problems?** If you encounter problems, make sure that all connections are secure. For further assistance, contact your service provider.