

## 5A60 *Varos*. Right from the start.

*Varos* is designed to benefit transfemoral amputees starting in the rehabilitation phase as well as later during treatment with the final prosthesis.

### ***Varos* offers the user noticeable benefits in everyday life.**

- adjustable by the user to volume fluctuations and everyday activities (sitting, driving a car) at any time and any place
- easy donning and doffing – even when seated
- low complexity and low product weight

### ***Varos* offers professionals modern treatment and a distinguishing feature.**

- technological milestone in treatment solution
- fast & easy fitting with a simple process – saves time and effort for patient and CPO
- improves the user's perceived safety and stability
- secure suspension may contribute to better control of prosthesis & movements
- greater variety of training possibilities



## 5A60 Varos. Flexible, customized and lightweight.



The *Varos* socket (5A60) and *Varos* liner (6Y200) are recommended as a combination for reliable interim and definitive fitting for users with a transfemoral amputation. The prefabricated socket allows a quick assembly and custom adaptation. This significantly reduces both the number and duration of visits the patient requires for adjusting the prosthesis.

The special *Varos* liner evenly distributes pressure on the residual limb. Contact of the liner with fabric adhesive strips in the socket and the distal magnetic connector result in especially good adhesion in the socket. As a result, this offers users the advantages of high flexibility and functionality in comparison with conventional sockets.

### Technical data

#### 5A60 Varos Socket (Example 5A60=R-MC)

Size	S	SC*	M	MC*	L
<b>Mobility grade (MOBIS)</b>	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4
<b>Maximum body weight</b>	100 kg	100 kg	100 kg	100 kg	125 kg
<b>Proximal residual limb circumference (mm)</b>	410–510	460–580	460–580	520–650	520–650
<b>Distal residual limb circumference (mm)</b>	320–390	320–390	350–440	350–440	400–490
<b>Residual limb length (mm)</b>	200–320	200–320	200–320	200–320	200–320

#### 6Y200 Varos liner

Size	S-1	SC-1*	S-2	SC-2*	M-1	MC-1*	M-2	MC-2*	L-1	L-2
<b>Proximal residual limb circumference (mm)</b>	420–490	480–550	450–520	510–580	480–550	530–610	510–580	560–650	530–610	560–650
<b>Distal residual limb circumference (mm)</b>	310–350	310–350	330–370	330–370	360–410	360–410	390–440	390–440	400–450	430–490

Please note, it is not possible to combine size L liners with sockets of any other size.

\*-C included in an item number indicates “conical”