

ottobock.

Triton side flex.

Your will. Your way.

Triton side flex was designed for highly active individuals who navigate varied indoor and outdoor environments and place a high value on uncompromised response and control even when performing high-impact activities.

Designed for optimal outcomes

- Unique side-to-side flexibility of $\pm 10^\circ$ for immediate and full-ground contact while walking and standing, including on uneven surfaces
- An interconnected, linear spring design provides the level of midstance support needed for activities where responsiveness is essential
- For users with limited clearance
- Robust and maintenance-free technology
- Customisable shock absorption with two different heel wedge options
- Suitable for a broad range of application, from everyday life to demanding professions and even leisure sports
- Slim footshell option
- Protected against fresh, salt, and chlorinated water

More than a foot. A foundation.



Technical data

Mobility grade	3, 4
Max. body weight	125 kg
Side	left (L), right (R)
Sizes	22 – 30 cm
Weight without footshell*	585 g
Footshell shape	Slim shape (S) with 15 ± 5 mm heel height (size 22 – 27 cm) Normal shape (N) with 10 ± 5 mm heel height (size 24 – 30 cm)
Footshell colour	beige (4), light brown (15)
Weight with normal footshell*	805 g
Build height with normal footshell*	86 mm

* Reference size is 26 cm.



Strong and dynamic rollover

Energetic walking

Supports agile and high-impact movements

Comfortable adjustment for an enhanced feeling of safety

1C68 Order form.

Customer

Customer no.	
Company	
Street	
Postal code	City
O&P professional	

Shipping address (if different from customer address)

Customer no.	
Company	
Street	
Postal code	City
Customer ref.	

Selection of the spring stiffness relative to body weight and foot size*

Body weight \ Foot size	Foot size									
	22 cm	23 cm	24 cm	25 cm	26 cm	27 cm	28 cm	29 cm	30 cm	
up to 55 kg	1	1	1	1	1	-	-	-	-	-
56 – 75 kg	2	2	2	2	2	2	2	2	2	2
76 – 100 kg	3	3	3	3	3	3	3	3	3	3
101 – 125 kg	-	-	-	4	4	4**	4**	4**	4**	4**

- Slim footshell available (15 ± 5 mm heel height)
- Both footshells available
- Normal footshell available (10 ± 5 mm heel height)

* Please read the 1C68 instructions for use regarding potentially excluded combinations of configurations with Ottobock structural components.

** Do not combine this configuration with a 3C88-3/3C98-3 C-Leg 4.




Example for ordering 1C68=R26-3-P/4N

Article no.	Side	Size	Stiffness	Colour	Shape
1C68	=		-	P /	
	↓	↓	↓	↓	↓
	Side	Size (cm)	Colour	Shape	
	R Right L Left	22, 23, ..., 30	4 Beige 15 Light brown	S Slim 21-27 cm N Normal 24-30 cm	



The scope of delivery includes the 1C68 foot module, the 2C6 footshell including connection cover, the 2F60 heel wedge set (comprising two different degrees of hardness) and a black Spectra sock.

Recommended combinations***

TT	TF
 6Y95 Caleo 3D + 453A30/40 ProFlex Plus sealing sleeve + 21Y2=M10 QuickValve or 4R180 Harmony P4 + 6Y512=*-P Uneo Fresh + 453A30/40 ProFlex Plus sealing sleeve	 7T451=1 SiOCX TF Pro + 21Y21 ClickValve or 6Y110/6Y111 Skeo Sealing + 21Y2=M10 QuickValve
 4R11 Quickchange	 3B5-4 Genium X4 3C88-4/3C98-4 C-Leg 3R85 Dynion
	 4R57=WR Rotation adapter 4R11 Quickchange
	 3F2=0 + 99B122* Functional cosmesis or 4P110=7/4P100 Protector long/short

*** All components are sold separately and are available Ottobock products that are compatible with the 1C68 **Triton side flex** foot, which helps ensure optimal performance. Practitioners need to select components based upon individual patient criteria.