

More than a foot. A foundation.

With every fitting, your goal is the same as ours: to craft the best possible solution for your patients. Whether you're fitting an above or below knee amputee, the quality and performance of the whole prosthesis will be impacted by the quality and performance of the foot. That's why we at Ottobock believe the foot plays such a vital role.

To make sure that you can achieve the best possible fitting outcome for your patients, our extensive carbon foot portfolio offers a wide range of options to choose the right solution that best suits your patients' needs. It's more than just a component. It's a foundation.



Terion K2 – Confidence in every step.

Designed for **less active individuals** who mainly navigate indoor environments and will utilise a walking aid for outdoor ambulation and place a high value on dependable support from their prosthetic foot.

MG 1-2 | Up to 175 kg





Trias – Secure as expected.

Designed for **moderately active individuals** who navigate indoor and familiar outdoor environments and place a high value on consistent stability when walking.

MG 2-3 | Up to 125 kg Protected against fresh, salt and chlorinated water





Taleo - Ready for everyday life.

Designed for **active individuals** who navigate varied indoor and outdoor environments and place a high value on effortless walking and the ability to go wherever life takes them.

MG 3-4 | Up to 150 kg Protected against fresh, salt and chlorinated water*

Family members:

- *1C50 Taleo, 1C51 Taleo Vertical Shock, 1C52 Taleo Harmony
- *1C53 Taleo Low Profile
- *1C56 Taleo Adjust (MG 2-3)
- *1C58 Taleo Side Flex
- *1C59 Taleo Adapt





Triton – Your will. Your way.

Designed for **highly active individuals** who navigate varied indoor and outdoor environments and place a high value on uncompromised response and control even when performing high-impact activities.

MG 3-4 | Up to 150 kg Protected against fresh, salt and chlorinated water*

Family members: 1C60 *Triton*, 1C61 *Triton Vertical Shock*, 1C62 *Triton Harmony* *1C63 *Triton Low Profile*

*1C64 Triton Heavy Duty

*1C68 Triton side flex





Taleo.Ready for everyday life.

Our development continues: with the *Taleo* prosthetic feet, our expanded family of carbon feet provides you with more options to choose the right foot for your patient.

Taleo family.

The prosthetic feet of the *Taleo* family feel comfortable, so active users can manage life completely on their own terms. They feature smooth rollover, and their efficient energy return supports a dynamic gait. In doing so, the *Taleo* prosthetic feet adapt flexibly to each user's individual gait characteristics and various surfaces.





Energy efficient walking for less fatigue at the end of the day

The *Taleo* prosthetic feet give users the right amount of energy return for every step. This means they have more energy to cover longer distances or walk at varying walking speeds.

Smooth rollover for easy walking

The *Taleo* prosthetic feet's seamless rollover from heel strike to toe off allow easy and comfortable walking without dead spots. It lets users move smoothly when spontaneously changing speed and direction.

Freely navigating uneven terrain

The *Taleo* prosthetic feet accomodate to varying terrain conditions that we encounter every day.

Users can move freely and easily on uneven or sloping terrain – whether at home or out on grassy areas, forest paths or rocky ground.

Made for optimal fitting results.

1 Unique flexible connection of the carbon springs in the forefoot

The flexible design allows *Taleo* to adapt to varying terrain conditions and makes walking on uneven terrain and slopes easy and comfortable. This is also supported by the flexible, non-screw connection of the three carbon springs in the forefoot area.





The footshell

Openings in the sole of the footshell prevent water from collecting in the prosthesis. Alignment marks on the footshell facilitate bench alignment.





2 Double springs and a long carbon base

Thin double carbon springs and a long carbon base spring ensure high flexibility and efficient energy return. The design delivers a smooth rollover, without dead spots. A dynamic gait is possible, even at varying speeds, thanks to the highly efficient ratio between energy input and return.



3 Customisable impact stress at heel strike and gait dynamics

The large selection of heel wedges makes it possible to customise the impact stress at heel strike as well as the gait dynamics.





With the *Taleo* prosthetic foot users are ready for everyday life.







The *Taleo* is the first product in the *Taleo family* of prosthetic feet. The carbon foot enables a smooth rollover for energy efficient walking and adaptation to various types of terrain.

The thing about the Taleo foot, it is easy. It makes every step glide. It is ready to walk.

And it is ready to walk you.

- Three different heel wedge options can be used to customise the impact stress at heel strike as well as the gait dynamics.
- The slim connection adapter is suitable for a cosmetic fitting.
- Water runoff contours on the adapter and openings in the sole of the footshell prevent water from collecting in the prosthesis.
- Protected against fresh, salt and chlorinated water.

1C51Taleo Vertical Shock.

The *Taleo* for users who lead an active life and want to relieve their residual limb.








The *Taleo Vertical Shock* absorbs even more torsion and supports the natural rotation movements that occur not only during various turning motions in everyday life but also when walking straight ahead, as the pelvis rotates over the foot when weight is placed on it.

Natural pelvis rotation during walking



- The +/- 10° of torsion absorption of the functional ring prevents the transmission of torsion moments from the socket to the residual limb and skin.
- This type of unit can reduce shear forces occurring on the residual limb and the resulting skin irritation. ^{1, 2}
- The vertical spring deflection of up to 15 mm absorbs the impacts the user feels when setting the foot down. This enhances comfort, especially in situations such as going down stairs.³
- Three different heel wedge options can be used to customise the impact stress at heel strike as well as the gait dynamics.
- Water runoff contours on the adapter and openings in the sole of the footshell prevent water from collecting in the prosthesis.
- Weatherproof

^[1] Pasquina PF; Cooper RA (Hg.) (2009): Care of the combat amputee. Borden Institute, Walter Reed Army Medical Center; (Textbooks of military medicine).

^[2] Segal ADet al. (2009): Transtibial amputee joint rotation moments during straight-line walking and a common turning task with and without a torsion adapter. Journal of rehabilitation R&D 46.

^[3] Popielarz Set al. (2014): Shock absorbers for vascular trans-tibial amputees in environmental situations seem more efficient on comfort than on oxygen consumption. Science & Sports 29 (4).

1C52 Taleo Harmony.

The Taleo for users who value a firm hold and control of their prosthesis throughout the day and want to relieve their residual limb.







In addition to absorbing torsion even more effectively, the Taleo Harmony also offers users a firm fit at all times thanks to the integrated Harmony P3 pump. 4

66 Of course you shouldn't expect the impossible, but I don't see any difference to my life before the accident and after the amputation. I can go back to doing whatever I want.

- The integrated active vacuum gives users better control over the prosthesis, minimises residual limb problems and skin irritation caused by pistoning and also stabilises the residual limb volume. 5, 6
 - The +/- 10° of torsion absorption of the functional ring prevents the transmission of torsion moments from the socket to the residual limb and skin. This type of unit can considerably reduce shear forces occurring on the residual limb and the resulting skin irritation. 1, 2
 - The vertical spring deflection of up to 15 mm absorbs the impacts the user feels when setting the foot down. This enhances comfort, especially in situations such as going down stairs.3
 - Three different heel wedge options can be used to customise the impact stress at heel strike as well as the gait dynamics.
 - Water runoff contours on the adapter and openings in the sole of the footshell prevent water from collecting in the prosthesis.
 - Weatherproof
- [4] Klute GK et al. (2011): Vacuum-assisted socket suspension compared with pin suspension for lower extremity amputees: effect on fit, activity, and limb volume. Archives of physical medicine and rehabilitation 92(10). [5] Board, W et al. (2001): A comparison of transtibial amputee suction and vacuum socket conditions. Prosthet Orthot Int 25(3). [6] Traballesi M et al. (2012): Residual limb wounds or ulcers heal in transtibial amputees using an active suction socket system. A randomized controlled

study. European journal of physical and rehabilitation medicine 48(4).

1C53Taleo Low Profile.

The Taleo for users with limited build height.







Thanks to the *Taleo Low Profile*, users who have only limited build height available for the installation of their prosthetic foot can also benefit from the high energy return and flexibility of the *Taleo* family.

66

The Taleo Low Profile is a very smooth foot. It feels very stable and it is not hard to walk in. I love to play with my dogs in the water so it's nice having a foot that is waterproof.

Cassie

- The curved bottom of the pyramid enables more controlled forward movement during the rollover than with low profile feet with a conventional foot adapter.
- Three different heel wedge options can be used to customise the impact stress at heel strike as well as the gait dynamics.
- A distinguishing feature of the *Taleo Low Profile* is its low weight.
- Water runoff contours on the adapter and openings in the sole of the footshell prevent water from collecting in the prosthesis.
- Protected against fresh, salt and chlorinated water.

1C56Taleo Adjust.

The *Taleo* for users who place a high value on flexibility in the choice of footwear.







With the *Taleo Adjust* users can wear different shoes with different heel heights. At the touch of a push of a button, they can set the appropriate heel height from 0 up to 7 cm.

66

I am wearing my
Taleo Adjust which is
amazing because it has new
features. And it is the special
button, if you just push it,
you can wear different types
of shoes.

Natálie

- Heel height adjustable carbon foot
- The easy, stepless heel height adjustment from 0 to 7 cm allows users to wear different shoes.
 The individually optimal prosthetic alignment can be reproduced.
- The seamless rollover from heel strike to toe-off allows easy and comfortable walking without dead spots – depending on the footwear.
- Thanks to three different heel wedges, both the impact stress at heel strike and the gait dynamics can be customised to individual needs.
- Openings in the sole of the foot prevent water from collecting in the prosthesis.
- Protected against fresh, salt and chlorinated water.

1C58Taleo Side Flex.

The *Taleo* for users who value a high degree of socket comfort on uneven surfaces.







The *Taleo Side Flex* sets a new standard for mediolateral flexibility. Compared with conventional prosthetic feet, its Terrain Adaptation Unit (TAU) lets it adapt to slopes right after heel strike to an exceptional degree.



Benefits for users

- Secure full-surface ground contact while walking and standing ^{7,8}
- Reduced sideward tilting moments in the prosthetic socket or knee⁸
- Fewer compensating movements⁸
- Improved comfort and enhanced feeling of safety ⁸

- The Terrain Adaptation Unit enables mediolateral adaptation of 20° in total for immediate and full-surface ground contact while walking and standing, even on uneven surfaces and slopes. ^{7,8}
- The curved bottom of the Terrain Adaptation Unit enables more controlled forward movement during the rollover than with low profile feet with conventional foot adapter.
- Three different heel wedge options can be used to customise the impact stress at heel strike as well as the gait dynamics.
- The technology is robust and maintenance-free.
- Suitable for users who have only limited build height available for the installation of their prosthetic foot.
- Openings in the sole of the footshell prevent water from collecting in the prosthesis.
- Protected against fresh, salt and chlorinated water.

1C59Taleo Adapt.

The *Taleo* for users who navigate a lot on uneven surfaces and slopes.







The *Taleo Adapt*'s hydraulic ankle unit allows the foot to adapt to slopes and uneven surfaces for greater flexibility and comfort. An added benefit of the foot is that it also provides improved socket comfort on various terrains.

66

With the prosthesis
that I have, I feel like I can
push the limit and do whatever,
there is no fear. I like the way that
there is flexion, movement in my
ankle. It feels pretty close like
how my other leg feels.

Carlos

- Hydraulic ankle allows up to 2 degrees dorsiflexion and 10 degrees plantarflexion for a total range of 12 degrees.
- The dorsiflexion and plantarflexion adjustment valves allow resistance to be optimised to the individual user needs.
- Dorsiflexed position during swing phase for improved toe clearance.
- Three different angle indicator lines show the location of the hydraulic ankle joint (PF, neutral position, DF). These provide the technician with an orientation aid and enable a functionally correct alignment
- Three different heel wedge options can be used to customise the impact stress at heel strike and the gait dynamics.
- Openings in the sole of the footshell prevent water from collecting in the prosthesis.
- Protected against fresh, salt and chlorinated water.



Order information 1C50, 1C51, 1C52, 1C53, 1C58

Selection of the spring stiffness depending on

1 body weight and activity as well as

2 foot size

Normal activity level	High activity level
1	2
2	3
3	4
4	5
5	6
6	7
7	8
8	9*
9*	_
	1 2 3 4 5 6 7 8

Stiffnes	1	2	3	4	5	6	7	8	9*
Foot size (cm)									
22						-	-	-	-
23							-	-	-
24							-	-	-
25								-	-
26								***	-
27	-	-						***	***
28	-	-						***	***
29	-	-	-				**	***	***
30	-	-	-				**	***	***
Slim footshell available	e Both footshells available Normal footshell available								

(10 ± 5 mm heel height)

Order example for 1C50, 1C51, 1C52, 1C53, 1C58

1C5*=R26-4-P/4N

Quantity	Article no.		Side	Size	-	Stiffness	-	P	1	Colour	Shape
	1C50	=	R	26	-	4	-	Р	/	4	N
	1C51	=			-		-	Р	/		
	1C52	=			-		-	Р	/		
	1C53	=			-		-	Р	/		
	1C58	=			-		-	Р	/		
			↑	†		↑				†	^
			Side	Size [cm]		Stiffness				Colour	Shape
			R right	22, 23,, 30		1, 2,, 9				4 Beige	S Slim 22 – 25 cr
			L left							15 Light brown	N Norma 24 – 30 cr

(15 ± 5 mm heel height)



1C50 Taleo / 1C53 Taleo LP / 1C58 Taleo SF

The scope of delivery includes the respective foot module 1C50, 1C53 or 1C58, the 2C15 footshell including the connection cover, the 2F50 heel wedge set (comprising three different degrees of hardness) and a black Spectra sock.



1C51 Taleo Vertical Shock / 1C52 Taleo Harmony

The scope of delivery includes the respective foot module 1C51 or 1C52, the 2C15 footshell including the connection cover, the 2F50 heel wedge set (comprising three different degrees of hardness), a functional ring set for replacement, a pre-compression kit and a black Spectra sock. The scope of delivery of the 1C52 also includes the 2R117=0 socket connector.

 $^{^{\}ast}$ This stiffness category is not available for the 1C58. ** Do not combine this 1C50, 1C53 and 1C58 configuration with a 3C88-3/3C98-3 C-Leg 4.

^{***} Do not combine this 1C50, 1C51, 1C52, 1C53, 1C58 with a 3C88-3/3C98-3 C-Leg 4.

Order information 1C56

Selection of the spring stiffness depending on

1 body weight and activity as well as

2 foot size

Body weight (kg)	Low activity level	Normal activity level
Up to 51	1	2
52 – 58	2	3
59 – 67	3	4
68 – 77	4	5
78 – 88	5	6
89 – 100	6	7
101 – 115	7	_

Stiffnes Foot size (cm)	1	2	3	4	5	6	7
22			_	-			
23			-	-			
24						-	-
25		no	restricti	ons			
26							
27							
28	-	-					

Order example for 1C56 with 2C8* footshell

1C56=R26-4-P/4



Order example for 1C56 with 2C15* low cut footshell

1C56=R26-4-P/4N-L

Quantity	Article no.		Side	Size	-	Stiffness	-	P	1	Colour	Shape
	1C56	=	R	26	-	4	-	Р	/	4	N
			†	↑		^				^	↑
			Side	Size [cm]		Stiffness				Colour	Shape
			R right	22, 23,, 26		1, 2,, 7				4 Beige	N-L Normal low cut 24 – 26 cm
Teld "			L left							15 Light brown	S-L Slim low cut 22 – 23 cm

Scope of delivery



1C56 Taleo Adjust

The scope of delivery includes the foot module 1C56, the 2C8 footshell including the connection cover or the 2C15 low cut footshell, the 2F50 heel wedge set (comprising three different degrees of hardness) and a black Spectra sock.

Order information 1C59

Selection of the spring stiffness relative to

1 body weight and activity as well as

2 foot size

Body weight (kg)	Normal activity level	High activity level
Up to 51	1	2
52 – 58	2	3
59 – 67	3	4
68 – 77	4	5
78 – 88	5	6
89 – 100	6	7
101 – 115	7	8
116 – 130	8	8

Stiffnes Foot size (cm)	1	2	3	4	5	6	7	8	
22			_	-					
23		_							
24									
25			nc	restri	ctions			-	
26			110	restin	Ctions				
27	-	_							
28									
29									
30	-	-	-						

Order example for 1C59

1C59=R-26-4-P/4N

Quantity	Article no.		Side	-	Size	-	Stiffness	-	P	1	Colour	Shape
	1C59	=	R	-	26	-	4	-	Р	/	4	N
			↑		↑						↑	
			Side		Size [cm]						Colour	
			R right		22, 23,, 30						4 Beige	
			L left								15 Light brown	_

Scope of delivery



1C56 Taleo Adapt

The scope of delivery includes the 1C59 foot module, 2C8 footshell including connection cover, 2F50 heel wedge set (comprising three different degrees of hardness) and a black Spectra sock.



Technical data.







Taleo
1050

Taleo Vertical Shock 1C51

+/- 10° torsion movement, up to 15 mm

vertical shock absorption

Taleo Harmony

Vacuum, +/- 10° torsion

movement, up to 15 mm

vertical shock absorption

	1C50	1C51	1C52
Mobility grade		3,	, 4
Max. body weight		150) kg
Side			
Sizes	22 – 30 cm	22 – 30 cm	22 – 30 cm
Weight without footshell*	450 g	751 g	751 g
Footshell shape		Slim shape (S) with 15 +/- 5 mm h Normal shape (N) with 10 +/- 5 mm	
Footshell colour			
Weight*	690 g (with normal footshell)	980 g (with normal footshell)	980 g (with normal footshell)
Build height*	150 mm (with normal footshell)	185 mm (with normal footshell)	185 mm (with normal footshell)

Other features

^{*} Reference size is 26 cm.













Taleo Low Profile
1C53

Taleo Side Flex 1C58

Taleo Adapt 1C59

115 kg

2, 3 3, 4

left (L), right (R)

22 – 30 cm 22 – 28 cm 22 – 30 cm

22 – 30 cm

130 kg

355 g

680 g

normal, normal low cut, slim

low cut

602 g

622 g

see Taleo 1C50

normal

beige (4), light brown (15)

584 g (with normal footshell) 930 g (with normal footshell)

826 g

899 g

65 mm (with normal footshell)

118 mm (with normal footshell)

97 mm

134 mm

easy, infinitely variable heel height adjustment from 0 up to 7 cm

20° mediolateral adaptability (10° medial and 10° lateral)

Hydraulic ankle (2° DF and 10° PF)

The right components** for individual prosthesis solutions

6Y95 Caleo 3D Liner

- Designed to protect the bony structures thanks to the reinforced material (6 mm) in the front area
- Flexibility in the knee area is maintained by using thinner material (3 mm) in the posterior area
- Thermoformable: liner can be adapted in the oven to the user's residual limb shape

453A30 ProFlex Plus

- Pre-flexion of 15° for easy knee flexion and reduction of folds at the back of the knee
- Proximal end is barely felt thanks to flat seam



1C56 Taleo Adjust



1C58 Taleo Side Flex



1C59 Taleo Adapt



1C51 Taleo Vertical Shock



1C52 Taleo Harmony



1C53 Taleo Low Profile

^{**} All components are sold separately and are available as Ottobock products that are compatible with the Taleo product family feet which helps ensure optimal performance. O&P professionals need to select components based upon individual patient criteria.



21Y14 PushValve

- Threadless valve for transfemoral prosthesis
- Easy handling for the user
- Water and corrosion resistant

4R11* Quickchange

- Allows users to remove their distal prosthetic components from the socket by themselves when needed, in just one step. This makes dressing and undressing easier and sitting more comfortable.
- A fitting with various feet or knee-foot combinations is possible
- Water and corrosion resistant

4R57=WR / 4R57=WR-ST

Waterresistant rotation adapter

- Allows users the flexed lower leg to be rotated against the socket – for more freedom of movement and a relaxed sitting position, allows movement that is gentle on the back, e.g. when putting on shoes
- Water and corrosion resistant

3C88-3 / 3C98-3 C-Leg 4

- Harmonious gait pattern and more freedom of movement
- Proven performance and reliability in everyday activities
- Two customised MyModes Plus from a fantastic selection of movement patterns
- Peace of mind if product is occasionally exposed to fresh water (IP 68, not corrosion-resistant)
- Two colour options and a customisable shield insert

3B5-4 **Genium X4**

- OPG 3.0 for an exceptionally smooth walking experience
- Real-time support in challenging everyday movements
- Extensive customisability with a range of cover options and adjustable MyModes
- Waterproof and corrosion-resistant design (IP68)





3F1=2 + 99B120=* Functional cosmesis

- Natural look and function combined in one solution
- High degree of prefabrication
- Highly durable

2C15 Footshell

Solution adapted to prosthesis functionality