

# 1C70 *Evanto*. Feel the flow.

*Evanto* was designed for active individuals who navigate varied indoor and outdoor environments and place a high value on a natural walking feeling, increased endurance and a high degree of comfort on uneven terrain.

## Designed for optimal outcomes

- *Evanto*'s innovative design stores the highest amount of energy at heel strike and returns it at toe off for enhanced forward propulsion.\*
- High-performance wedges allow for up to 24 mm of shock absorption at heel strike.\*
- When going down stairs or stepping off curbs, *Evanto* provides up to 9 mm of vertical shock absorption.\*
- Excellent multi-axial compliance provides stability and a high degree of comfort with up to 20° of sagittal plane motion, +/- 10° of m-l flexibility, and +/- 4° of torsional motion.\*
- Customisable forefoot and heel behaviour to meet individual user needs.
- Protected against fresh, salt and chlorinated water.

\*Comparison to state-of-the-art energy storing and return prosthetic feet like Taleo

More than a foot. A foundation.



waterproof

## Technical data

<b>Mobility grade</b>	2 – 4
<b>Max. body weight</b>	125 kg
<b>Sizes</b>	22 – 30 cm
<b>Weight without footshell*</b>	450 g
<b>Footshell shape</b>	Normal shape with 10 +/- 5 mm heel height
<b>Footshell colour</b>	beige (4), light brown (15)
<b>Weight with footshell*</b>	725 g
<b>Build height*</b>	82 mm

\* Reference size is 26 cm.



Shock absorption for user comfort

Multi-axial flexibility for adaptation to uneven terrain

Innovative energy management for improved endurance

# 1C70

## Order form.

### Customer

Customer no.

Company

Street

Postal code  City

O&P professional

### Shipping address (if different from customer address)

Customer no.

Company

Street

Postal code  City

Customer ref.

### Selection of the spring stiffness relative to body weight and foot size

Body weight	Foot size									
	22 cm	23 cm	24 cm	25 cm	26 cm	27 cm	28 cm	29 cm	30 cm	
up to 58 kg	1	1	1	1	-	-	-	-	-	
59 - 72 kg	2	2	2	2	2	2	2	2	2	
73 - 86 kg	3	3	3	3	3	3	3	3	3	
87 - 100 kg	4	4	4	4	4	4	4	4	4	
101 - 125 kg	-	-	-	-	5	5	5*	5*	5*	

\* Do not combine this configuration with a 3C88-3 C-Leg or a 3C98-3 C-Leg.

### Example for ordering

#### 1C70=R26-4-P/4






Article no.	Side	Size	Stiffness	Colour
1C70	=		-	P /
	↓	↓	↓	↓
	<b>Side</b>	<b>Size (cm)</b>	<b>Stiffness</b>	<b>Colour</b>
	R Right L Left	22, 23, ..., 30	1, 2, ..., 5	4 Beige 15 Light brown

To order the foot module and footshell separately, please refer to our online shop and catalogue.



The scope of delivery includes the 1C70 foot module, the 2C70 footshell including connection cover, the upper wedge set (comprising two wedges with different degrees of hardness), the lower wedge set (comprising two wedges with different degrees of hardness) and a black Spectra sock.

### Recommended combinations\*\*

TT	TF
 4R140 One-way valve + 453A30/40 ProFlex Plus sleeve + 6Y95 Caleo 3D or 4R180 Harmony P4 + 453A30/40 ProFlex Plus sleeve + 6Y512=*-P Uneo Fresh	 7T451=1 SiOCX TF Pro or Laminated socket + 6Y110 Skeo Sealing + 21Y21 ClickValve
 4R11=* Quickchange	 3C60* Kenevo, 3R85* Dynion, 3C98* C-Leg, 3B1* Genium or 3B5* Genium X3  4R57=WR Waterproof Rotation Adapter 4R11=* Quickchange
	 3F1=* + 99B120=* Functional cosmesis

\*\* All components are sold separately and are available Ottobock products that are compatible with the 1C70 Evanto foot, which helps ensure optimal performance. Practitioners need to select components based upon individual patient criteria.