

Genium X4 – Prosthetic knee joint.

Order form.

Contact person	Customer no.	Date
----------------	--------------	------

Customer

Company	
Street	
Postal code	City
Email	
Commision	

Shipping address (if different from customer address)

Company	
Street	
Postal code	City
Email	

Gender

- Female Male

Weight

kg

Foot size

cm

Side of amputation

- left right bilateral

Prosthetic attachment to residual limb

- Conventional socket
 Osseous anchored implant

Mobility Grade

- Mobility Grade 2
 Mobility Grade 3
 Mobility Grade 4



Amputation Level

- Knee Disarticulation
 Transfemoral
 Hip Disarticulation / Hemipelvectomy

Fitting

- Initial fitting (of microprocessor controlled knee joint made by Ottobock)

- previous prosthetic knee joint is known:

<input type="text"/>	<input type="text"/>
Manufacturer	Model

- previous prosthetic knee joint is unknown
 no previous prosthetic knee joint

- Follow-up fitting (of microprocessor controlled knee joint made by Ottobock)

- previous microprocessor controlled knee joint

<input type="text"/>	<input type="text"/>
Model	Serial number

Genium X4 – Prosthetic knee joint. Order form.

Knee joint

3B5-4=P	Genium X4	3B5-4=ST	Genium X4 – for long residual limb
----------------	-----------	-----------------	------------------------------------

Including following additional components: 757L48=1 AC Adapter (EU and US compatible), 757L47=1 USB Adapter for charging, 4H110=7.5 Flexion Stop 7,5°, 4H110=15 Flexion Stop 15° (pre-assembled), 4H110=22.5 Flexion Stop 22,5°.

Warranty (please choose one)

SP-3B5-4=3	3-year warranty package	SP-3B5-4=6	6-year warranty package
-------------------	-------------------------	-------------------	-------------------------

Electronic Tube Adapter

2R68=280	AXON Tube adapter (waterproof and corrosion resistant)	2R69=280	AXON Tube adapter (torsion unit= weatherproof, not corrosion resistant)
-----------------	--	-----------------	---

Connection components

4R47=5.0	Refit adapter for lamination anchor	4R11=P-1-3	Quickchange set with pyramid
4R48=5.0	Refit socket adapter	4R11=R-1-3	Quickchange set with pyramid receiver
4R57=WR	Rotation adapter (waterproof and corrosion resistant)	4R11=ST-1-3	Quickchange set with thread
4R57=WR-ST	Rotation adapter screw top (waterproof and corrosion resistant)	4R11=R-3-2	Quickchange base element with pyramid receiver
		4R11=P-1-1	Quickchange connecting element with pyramid
		4R11=R-1-1	Quickchange connecting element with pyramid receiver
		4R11=ST-1-1	Quickchange connecting element with thread

Feet parts

1A1-2	Empower	1C63	Triton Low Profile ²
1B1-2	Meridium	1C64	Triton Heavy Duty ²
1C10	Terion	1C68	Triton side flex ²
1C30-1	Trias	1C70	Evanto
1C40	C-Walk	1D35	Dynamic Motion
1C60	Triton	1E56	Axtion
1C61	Triton Vertical Shock	1E95	Challenger
1C62	Triton Harmony		

Color of footshell ● beige ● light brown¹

Shape of footshell ● slim¹ ● normal

1C50	Taleo ²	F21	Maverick Xtreme AT ²
1C51	Taleo Vertical Shock	F22	Maverick Comfort AT ²
1C52	Taleo Harmony	F23	Maverick Vertical Shock
1C53	Taleo Low Profile ²	FS5	Thrive
1C56	Taleo Adjust	Activity level	● low ● moderate ● high
1C58	Taleo Side Flex ²	Color of footshell	● light ● medium ● dark
		LP2-W2	Freestyle Swim ²

Activity level ● normal ● high

Color of footshell ● beige ● light brown¹

Shape of footshell ● slim¹ ● normal

In combination with a prosthetic knee joint, some foot sizes and stiffnesses may be excluded. Please follow the information in the foot order sheet and the instructions for use. In case of any questions, please contact Ottobock customer service.

¹ Not available for all feet and/or sizes. Please visit our homepage for more information.

² Recommended combination, because of water & corrosion resistant components.

Genium X4 – Prosthetic knee joint. Order form.

Cover Solutions

	4P100=7	Genium X4 Protective cover, short		3D13=1	Thigh kit/Magnetic closure
	4P110=7	Genium X4 Protective cover, long		3F2=0	Functional cosmesis Genium X4
	4P112=1	Functional knee part		99B122	Functional stocking
					Size ● S ● L Color ● beige-4 ● light brown-15

Accessories Included in scope of delivery.

	757L48=1	AC Adapter		4H110=7.5	Flexion Stop 7,5°
	757L47=1	USB Adapter for charging		4H110=15	Flexion Stop 15°
				4H110=22.5	Flexion Stop 22,5°

The General Terms and Conditions of Ottobock SE & Co. KGaA apply.
The expected lifetime given compliance with the prescribed maintenance intervals is 6 years.
For additional information please contact / visit:

Date

Place

Signature