

636K40 - Repositionable Spray Adhesive

Material number 636K40

Page: 1 of 13

1. Product and company identification

Product identifier

Trade name: 636K40 - Repositionable Spray Adhesive

Recommended use and restrictions on use

General use: Adhesive-Aerosol for orthopedic procedures.
Reserved for industrial and professional use.

Initial supplier identifier

Company name: Otto Bock HealthCare Canada Ltd.

Street/POB-No.: 5470 Harvester Road

Postal Code, city: Burlington, ON L7L 5N5, CA
Canada

WWW: www.ottobock.ca

E-mail: info.canada@ottobock.com

Telephone: (800) 665-3327

Telefax: (800) 463-3659

Department responsible for information:

Mark Agro, Telephone: (800) 665-3327 (9 am - 5 pm)

Additional information:

Corporate headquarters:
Ottobock SE & Co. KGaA
Max-Näder-Straße 15
Duderstadt
Germany

Emergency phone number

COLLECT, Telephone: (613) 996-6666

Transport:

CONSULTANK Lutz Harder GmbH (Contract QUALI003)

Telephone: +49 (0)178-4337434 (from USA: 01149 178 4337434)

2. Hazards identification

Emergency overview

Appearance: Physical state at 20 °C and 101.3 kPa: liquid

Form: Aerosol

Color: colorless

Odor: sweet

Classification: Aerosol 1. Skin Irritation 2. Eye Irritation 2A.

Specific Target Organ Toxicity (Single Exposure) 3. Aquatic toxicity - chronic 3.

Hazard symbols:



Signal word:

Danger

636K40 - Repositionable Spray Adhesive

Material number 636K40

Revision date: 23/7/2024
Version: 11.3
Replaces version: 11.2
Language: en-CA
Date of print: 2/9/2025

Page: 2 of 13

Hazard statements:

- Extremely flammable aerosol.
- Pressurised container: May burst if heated.
- Causes skin irritation.
- Causes serious eye irritation.
- May cause drowsiness or dizziness.
- Harmful to aquatic life with long lasting effects.

Precautionary statements:

- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Do not spray on an open flame or other ignition source.
- Do not pierce or burn, even after use.
- Avoid breathing spray.
- Wear protective gloves/protective clothing/eye protection.
- Call a POISON CENTER/doctor if you feel unwell.
- Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Regulatory status

This material is considered hazardous by the WHMIS in Canada.

Hazards not otherwise classified

Potentially explosive mixtures may form if adequate ventilation is not provided.
Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may lead to a narcotic effect.
see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterisation: Blend of active ingredients with propellant.
Contains acrylate polymer (5-10%) and non volatile content (1-5%)

Relevant ingredients:

CAS No.	Designation	Concentration	Classification
CAS 67-64-1	Acetone	25 - 35 %	Flammable Liquid 2. Eye Irritation 2A. Specific Target Organ Toxicity (Single Exposure) 3.
CAS 64742-49-0	Hydrocarbons, C6, isoalkanes, < 5% n-hexane	7 - 13 %	Flammable Liquid 2. Skin Irritation 2. Specific Target Organ Toxicity (Single Exposure) 3. Aspiration Toxicity 1. Aquatic toxicity - chronic 2.
CAS 64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	7 - 13 %	Flammable Liquid 2. Skin Irritation 2. Specific Target Organ Toxicity (Single Exposure) 3. Aspiration Toxicity 1. Aquatic toxicity - chronic 2.
CAS 109-66-0	n-Pentane	1 - 5 %	Flammable Liquid 2. Specific Target Organ Toxicity (Single Exposure) 3. Aspiration Toxicity 1. Aquatic toxicity - chronic 2.
CAS 78-78-4	i-Pentane	0.5 - 1.5 %	Flammable Liquid 1. Specific Target Organ Toxicity (Single Exposure) 3. Aspiration Toxicity 1. Aquatic toxicity - chronic 2.
CAS 106-97-8	n-Butane, pure	10 - 20 %	Flammable Gas 1. Liquefied Gas.
CAS 74-98-6	Propane	10 - 20 %	Flammable Gas 1. Liquefied Gas.
CAS 75-28-5	Isobutane	5 - 10 %	Flammable Gas 1. Liquefied Gas.

4. First aid measures

General information:	In case of accident or if you feel unwell, seek medical advice immediately.
In case of inhalation:	Move victim to fresh air, put at rest and loosen restrictive clothing. If the casualty has difficulty breathing, call a doctor immediately.
Following skin contact:	Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with soap and plenty of water. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Seek the attention of an ophthalmologist immediately.
After swallowing:	Do not induce vomiting. Rinse mouth and seek medical attention immediately.

Most important symptoms and effects, both acute and delayed

In case of inhalation: Cough, sneeze, shortage of breath, hoarseness, sore throat.
After resorption: nausea, drowsiness, headache, agitation, fatigue, dizziness, unconsciousness. Reaction time and coordination may be impaired.
In case of high vapor concentrations: Causes damage to heart if inhaled. Attention Fatal.
Symptoms: cardiac arrhythmias, Thoracic oppression.
After contact with skin:
Upon direct contact with skin may cause itching and redness. Other symptoms: oedema (swelling).
Repeated exposure may cause skin dryness or cracking.
After eye contact:
redness, swelling of the conjunctive tissues, pain, Risk of corneal clouding.
vision impairment

Information to physician

Do not give adrenaline or other stimulants. (Except in case of absolute necessity.)
No specific antidote known. Treatment methods and measures are determined by the physician's judgement in consultation with the patient.

5. Fire fighting measures

Flash point/flash point range:	<= -46 °C
Auto-ignition temperature:	No data available
Suitable extinguishing media:	Extinguishing is to be in accordance with the surrounding fire.
Extinguishing media which must not be used for safety reasons:	Full water jet

Specific hazards arising from the chemical

Extremely flammable aerosol. Pressurised container: May burst if heated.
Vapors may proceed on the ground over great distances and cause fire and backflashes.
In case of fire may be liberated: hydrocarbons, Carbon monoxide and carbon dioxide.

Special protective equipment and precautions for fire-fighters:	Wear self-contained breathing apparatus.
Additional information:	Heating causes rise in pressure with risk of bursting. Use fine water spray to cool endangered containers.

6. Accidental release measures

Personal precautions:	Remove all sources of ignition. Provide for good room ventilation, suctioning/venting. Do not breathe vapor/aerosol. Avoid contact with the substance. Keep unprotected people away. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse.
Environmental precautions:	Do not allow to enter soil, sewage, water bodies, lower level rooms or pits.
Methods for clean-up:	Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Final cleaning.
Additional information:	Special danger of slipping by leaking/spilling product.

7. Handling and storage

Handling

Advices on safe handling:	Use only in well-ventilated areas. Do not breathe vapor/aerosol. Avoid contact with skin, eyes, and clothing. When using do not eat, drink or smoke. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Have eye wash bottle or eye rinse ready at work place.
Precautions against fire and explosion:	Air combined with vapors may form potentially explosive mixtures that are heavier than air. Keep away from sources of ignition - No smoking. Use only non-sparking tools. Protect from direct exposure to sunlight and temperatures exceeding 50 °C. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Take precautionary measures against static discharges. Do not open or incinerate, even when empty. Do not spray into flames or on incandescent objects.
Specific use(s)	Adhesive-Aerosol for orthopedic procedures.

Storage

Requirements for storerooms and containers:	Keep container tightly closed and in a well-ventilated place. Keep container dry. Keep only in the original container. Protect from heat and direct sunlight. Store containers in upright position. Electrical equipment must be explosion protected according to standards. (DIN VDE 0165)
Hints on joint storage:	Do not store together with combustible or self-igniting materials or any highly flammable solids. keep away from Oxidizing agents (e.g. chlorine, Chromic acid). Keep away from food, drink and animal feedingstuffs.
Further details:	Heating causes rise in pressure with risk of bursting.

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
67-64-1	Acetone	Canada: OEL 15 min	1,800 mg/m ³ ; 750 ppm
		Canada: OEL 8 hour	1,200 mg/m ³ ; 500 ppm
		Canada: OEL STEL	500 ppm
		Canada: OEL TWA	250 ppm
		Canada: VECD	500 ppm
		Canada: VEMP	250 ppm
109-66-0	n-Pentane	Canada: OEL 8 hour	1,770 mg/m ³ ; 600 ppm
		Canada: OEL TWA	1,000 ppm
		Canada: VEMP	1,000 ppm
78-78-4	i-Pentane	Canada: OEL 8 hour	1,770 mg/m ³ ; 600 ppm
		Canada: OEL TWA	1,000 ppm
		Canada: VEMP	1,000 ppm
106-97-8	n-Butane, pure	Canada: OEL 8 hour	1,000 ppm
		Canada: OEL STEL	1,000 ppm
		Canada: VEMP	1,900 mg/m ³ ; 800 ppm
74-98-6	Propane	Canada: OEL 8 hour	1,000 ppm
75-28-5	Isobutane	Canada: OEL STEL	1,000 ppm
		Canada: VECD	1,000 ppm

Engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

See also information in chapter 7, section storage.

Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection: Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.
Protective gloves according to OSHA Standard - 29 CFR: 1910.138.
Glove material: Fluororubber (Viton) - Breakthrough time: > 480 min.
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.
Wear half-mask respirator with combination filter for organic vapors and particles.

General hygiene considerations:
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools.
Protect from direct exposure to sunlight and temperatures exceeding 50 °C. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.
Avoid contact with skin, eyes, and clothing. When using do not eat, drink or smoke. Do not breathe vapor/aerosol. Wash hands before breaks and after work.
Take off contaminated clothing and wash it before reuse. Have eye wash bottle or eye rinse ready at work place.

Environmental exposure controls

Refer to 6.: Section "Environmental precautions".

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:	Physical state at 20 °C and 101.3 kPa: liquid Form: Aerosol Color: colorless
Odor:	sweet
Odor threshold:	No data available
pH:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point/flash point range:	<= -46 °C
Evaporation rate:	No data available
Flammability:	No data available
Explosion limits:	No data available
Vapor pressure:	No data available
Vapor density:	No data available
Density:	0.71 g/mL (active agent)
Water solubility:	insoluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Thermal decomposition:	No data available
Additional information:	No data available

10. Stability and reactivity

Reactivity:	Extremely flammable aerosol. Air combined with vapors may form potentially explosive mixtures that are heavier than air. Vapors may proceed on the ground over great distances and cause fire and backflashes.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions:	Pressurised container: May burst if heated.
Conditions to avoid:	Do not heat spray cans over 50 °C. Do not force spray can open. Do not open or incinerate, even when empty. Do not spray into flames or on incandescent objects. Keep away from sources of ignition - No smoking.
Incompatible materials:	No data available
Hazardous decomposition products:	No hazardous decomposition products when regulations for storage and handling are observed.
Thermal decomposition:	No data available

11. Toxicological information

Toxicological tests

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.

ATEmix (calculated): 2,000 mg/kg \leq ATE < 5,000 mg/kg

Acute toxicity (dermal): Based on available data, the classification criteria are not met.

ATEmix (calculated): 2,000 mg/kg \leq ATE < 5,000 mg/kg

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.

ATEmix (calculated): 20 - 50 mg/L

Skin corrosion/irritation: Skin Irritation 2 = Causes skin irritation.

Serious eye damage/irritation: Eye Irritation 2A = Causes serious eye irritation.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Lack of data.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Specific Target Organ Toxicity (Single Exposure) 3 = May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

636K40 - Repositionable Spray Adhesive

Material number 636K40

Revision date: 23/7/2024
Version: 11.3
Replaces version: 11.2
Language: en-CA
Date of print: 2/9/2025

Page: 8 of 13

Other information:

Information about Acetone:

LD50 Rat, oral: 5,800 mg/kg
LD50 Rabbit, dermal: > 15,688 mg/kg
LC50 Rat, inhalative (vapor): 76 mg/L/4h

Information about Hydrocarbons, C6, isoalkanes, < 5% n-hexane:

LD50 Rat, oral: > 16,750 mg/kg
LD50 Rabbit, dermal: > 3,350 mg/kg
LC50 Rat, inhalative (vapor): > 259 mg/L/4h

Information about Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

LD50 Rat, oral: > 5,840 mg/kg
LD50 Rabbit, dermal: > 2,920 mg/kg
LC50 Rat, inhalative (vapor): > 23.3 mg/L/4h

Information about acrylate polymer:

LD50 oral (estimated): > 2,000 mg/kg
LD50 dermal (estimated): > 5,000 mg/kg

Information about non volatile content:

LD50 oral: > 34,000 mg/kg
LD50 dermal (estimated): > 5,000 mg/kg

Information about Pentane:

LD50 Rat, oral: > 2,000 mg/kg
LD50 Rabbit, dermal: 3,000 mg/kg
LC50 Rat, inhalative (vapor): > 18 mg/L/4h

Information about 2-Methylbutane (i-Pentane):

LD50 Rat, oral: > 2,000 mg/kg
LD50 Rabbit, dermal: 3,000 mg/kg
LC50 Rat, inhalative (vapor): > 18 mg/L/4h

Information about Butane:

LC50 Rat, inhalative (gas): 277,000 ppm

Information about Propane:

LC50 Rat, inhalative (gas): > 200,000 ppm

Information about Isobutane:

LC50 Rat, inhalative (gas): 276,000 ppm

Symptoms

In case of inhalation: Cough, sneeze, shortage of breath, hoarseness, sore throat.

After resorption: nausea, drowsiness, headache, agitation, fatigue, dizziness, unconsciousness. Reaction time and coordination may be impaired.

In case of high vapor concentrations: Causes damage to heart if inhaled. Attention Fatal.

Symptoms: cardiac arrhythmias, Thoracic oppression.

After contact with skin:

Upon direct contact with skin may cause itching and redness. Other symptoms: oedema (swelling).

Repeated exposure may cause skin dryness or cracking.

After eye contact:

redness, swelling of the conjunctive tissues, pain, Risk of corneal clouding.
vision impairment

12. Ecological information

Ecotoxicity

Aquatic toxicity: Harmful to aquatic life with long lasting effects.

Information about Hydrocarbons, C6, isoalkanes, < 5% n-hexane:

Fish toxicity:

LL50 Oncorhynchus mykiss: 18.27 mg/L/96h (QSAR)

NOELR Oncorhynchus mykiss: 4.089 mg/L/28d (QSAR)

Daphnia toxicity:

EL50 Daphnia magna (Big water flea): 31.9 mg/L/48h (QSAR)

NOELR Daphnia magna (Big water flea): 7.138 mg/L/21d (QSAR)

Algae toxicity:

EL50 Pseudokirchneriella subcapitata (green algae): 13.56 mg/L/72h (QSAR)

NOELR Pseudokirchneriella subcapitata (green algae): 3.034 mg/L/72h (QSAR)

Information about Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Fish toxicity:

LL50 Oncorhynchus mykiss: > 13.4 mg/L/96h (OECD 203)

NOELR Oncorhynchus mykiss: 1.534 mg/L/28d (QSAR)

Daphnia toxicity:

EL50 Daphnia magna (Big water flea): 3 mg/L/48h (OECD 202)

NOELR Daphnia magna (Big water flea): 1 mg/L/21d (OECD 211)

Algae toxicity:

EL50 Pseudokirchneriella subcapitata (green algae): 10-30 mg/L/72h (OECD 201)

NOELR Pseudokirchneriella subcapitata (green algae): 6.3 mg/L/72h (OECD 201)

Mobility in soil

No data available

Persistence and degradability

Further details: No data available

Additional ecological information

Volatile organic compounds (VOC): 90 % by weight / 639 g/L

General information: Do not allow to penetrate into soil, waterbodies or drains.

13. Disposal considerations

Product

Recommendation: Do not open with force or incinerate, even when empty.
Dispose of as hazardous waste. Dispose of waste according to applicable legislation.

Package

Recommendation: Empty carefully and completely, if possible.
Dispose of waste according to applicable legislation.

636K40 - Repositionable Spray Adhesive

Material number 636K40

Page: 10 of 13

14. Transport information

UN number

ADR/RID, IMDG, IATA-DGR:

UN 1950

UN proper shipping name

ADR/RID, IMDG:

UN 1950, AEROSOLS

IATA-DGR:

UN 1950, AEROSOLS, FLAMMABLE

Transport hazard class(es)

ADR/RID:

Class 2, Code: 5F

IMDG:

Class 2.1, Subrisk -

IATA-DGR:

Class 2.1



Packing group

ADR/RID, IATA-DGR:

not applicable

IMDG:

-

Environmental hazards

Marine pollutant:

no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

Canada: Transportation of Dangerous Goods (TDG)

UN Number:

UN1950

Shipping name:

UN 1950, AEROSOLS

TDG class:

2.1 (6.1)

Special provisions:

80

Explosive limit and limited quantity index:

0.125 L

Passenger carrying road or rail index:

75 L



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

636K40 - Repositionable Spray Adhesive

Material number 636K40

Revision date: 23/7/2024
Version: 11.3
Replaces version: 11.2
Language: en-CA
Date of print: 2/9/2025

Page: 11 of 13

Sea transport (IMDG)

UN number: UN 1950
Proper shipping name:: UN 1950, AEROSOLS
Class or division, Subsidiary risk: Class 2.1, Subrisk -
Packing Group: -
EmS: F-D, S-U
Special Provisions: 63 190 277 327 344 381 959
Limited quantities: 1000 mL
Excepted quantities: E0
Package - Instructions: P207, LP200
Package - Provisions: PP87, L2
IBC - Instructions: -
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: -
Tank instructions - Provisions: -
Stowage and handling: SW1 SW22
Segregation: SG69
Properties and observations: -
Marine pollutant: no
Segregation group: none

Air transport (IATA)

UN/ID number: UN 1950
Proper shipping name:: UN 1950, AEROSOLS, FLAMMABLE
Class or division, Subsidiary risk: Class 2.1
Hazard label: Flamm. gas
Excepted Quantity Code: E0
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg
Special Provisions: A145 A167 A802
Emergency Response Guide-Code (ERG): 10L

15. Regulatory information

National regulations - Canada

Acetone: DSL: listed
n-Pentane: DSL: listed
i-Pentane: DSL: listed
n-Butane, pure: DSL: listed
Propane: DSL: listed
Isobutane: DSL: listed

16. Other information

Text for labeling:

Contains 25 - 35 % Acetone, 7 - 13 % Hydrocarbons, C6, isoalkanes, < 5% n-hexane, 7 - 13 % Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, 1 - 5 % n-Pentane, 0.5 - 1.5 % i-Pentane, 10 - 20 % n-Butane, pure, 10 - 20 % Propane, 5 - 10 % Isobutane.
38 percent of the mixture consists of ingredient(s) of unknown acute toxicity (oral).
3 percent of the mixture consists of components of unknown hazards to the aquatic environment.

Hazard rating systems:



NFPA Hazard Rating:

Health: 2 (Moderate)
Fire: 4 (Severe)
Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 2 (Moderate)
Flammability: 4 (Severe)
Physical Hazard: 0 (Minimal)
Personal Protection: X = Consult your supervisor

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	0
	X

Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
Aerosol: Aerosol
Aquatic toxicity - chronic: Hazardous to the aquatic environment - chronic
AS/NZS: Australian Standards/New Zealand Standards
Aspiration Toxicity: Aspiration toxicity
ATEmix: Acute Toxicity Estimate of mixture
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC: European Community
EL50: Effective loading rate 50%
EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods
EN: European Standard
EQ: Excepted quantities
Eye Irritation: Eye irritation
Flammable Gas: Flammable gases
Flammable Liquid: Flammable liquid
IATA: International Air Transport Association
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
IMO: International Maritime Organization
LC50: Median lethal concentration
LD50: Lethal dose 50%
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD: Organisation for Economic Co-operation and Development
OEL: Occupational Exposure Limit Value
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
QSAR: Quantitative Structure-Activity Relationship
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
Skin Irritation: Skin irritation
STOT SE: Specific target organ toxicity - single exposure
TLV: Threshold Limit Value
TRGS: Technical Rules for Hazardous Substances
UN: United Nations
vPvB: Very persistent and very bioaccumulative
WEL: Workplace Exposure Limit
WHMIS: Workplace Hazardous Materials Information System



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

636K40 - Repositionable Spray Adhesive

Material number 636K40

Revision date: 23/7/2024
Version: 11.3
Replaces version: 11.2
Language: en-CA
Date of print: 2/9/2025

Page: 13 of 13

Reason of change: Changes in section 8: Occupational exposure limit values
Date of first version: 3/5/2011

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.