

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 30/12/2022
Version: 15.2
Replaces version: 15.1
Language: en-CA,US
Date of print: 2/9/2025

ottobock.

640F18 - Donning spray for silicone liners and prosthetic gloves (silicone, PVC)

Material number 640F18

Page:

1 of 11

1. Product and company identification

Product identifier

Trade name: 640F18 - Donning spray for silicone liners and prosthetic gloves (silicone, PVC)

This safety data sheet pertains to the following products:
640F18=900 = Nachfüllpackung f. 640F18

Recommended use and restrictions on use

General use: Pump spray: Solvent for orthopedic procedures

Initial supplier identifier

Company name: Otto Bock HealthCare Canada Ltd.

Street/POB-No.: 5470 Harvester Road

Postal Code, city: Burlington, ON L7L 5N5, CA
Canada

WWW: www.ottobock.ca

E-mail: info.canada@ottobock.com

Telephone: (800) 665-3327

Telefax: (800) 463-3659

Department responsible for information:

Mark Agro, Telephone: (800) 665-3327 (9 am - 5 pm)

Additional information: Corporate headquarters:
Ottobock SE & Co. KGaA
Max-Näder-Straße 15
Duderstadt
Germany

Emergency phone number

COLLECT, Telephone: (613) 996-6666

Transport:

CONSULTANK Lutz Harder GmbH (Contract QUALI003)

Telephone: +49 (0)178-4337434 (from USA: 01149 178 4337434)

2. Hazards identification

Emergency overview

Appearance: Form: liquid
Color: colorless, clear

Odor: alcoholic

Classification: Flammable Liquid 3. Eye Irritation 2A. Specific Target Organ Toxicity (Single Exposure) 3.

Hazard symbols:



Signal word:

Warning

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 30/12/2022
Version: 15.2
Replaces version: 15.1
Language: en-CA, US
Date of print: 2/9/2025

ottobock.

640F18 - Donning spray for silicone liners and prosthetic gloves (silicone, PVC)

Material number 640F18

Page:

2 of 11

Hazard statements: Flammable liquid and vapor.
Causes serious eye irritation.
May cause drowsiness or dizziness.

Precautionary statements: If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Store in a well-ventilated place. Keep container tightly closed.

Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and WHMIS in Canada.

Hazards not otherwise classified

see section 11: Toxicological information

3. Composition / Information on ingredients

Relevant ingredients:

CAS No.	Designation	Concentration	Classification
CAS 67-63-0	Isopropyl alcohol	30 - 60 %	Flammable Liquid 2. Eye Irritation 2A. Specific Target Organ Toxicity (Single Exposure) 3.

4. First aid measures

In case of inhalation: Move victim to fresh air. Do not allow victim to become chilled. Keep victim warm. If breathing becomes irregular or ceases, apply rescue breathing or artificial respiration immediately, where required supply oxygen. Seek medical attention.

Following skin contact: Change contaminated clothing.
Thoroughly wash skin with soap and water.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult an ophthalmologist.

After swallowing: Do not induce vomiting. Rinse mouth immediately and drink plenty of water. Immediately get medical attention.

Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness.
High concentrations of vapors irritate the eyes and mucous membranes.
After resorption: Headache, dizziness, inebriation, unconsciousness.
Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 30/12/2022
Version: 15.2
Replaces version: 15.1
Language: en-CA,US
Date of print: 2/9/2025

ottobock.

640F18 - Donning spray for silicone liners and prosthetic gloves (silicone, PVC)

Material number 640F18

Page: 3 of 11

Information to physician

Treat symptomatically.

5. Fire fighting measures

Flash point/flash point range:

24 °C (DIN 51755)

Auto-ignition temperature: No data available

Suitable extinguishing media:

Carbon dioxide, extinguishing powder, water spray jet
In case of large fires water spray jet or alcohol resistant foam.

Extinguishing media which must not be used for safety reasons:

Strong water jet

Specific hazards arising from the chemical

Flammable. Liquid evaporates quickly.
Vapors are heavier than air and will travel at floor level.
Vapors may form explosive mixtures with air. Beware of reignition.
In case of fire may be liberated: Carbon monoxide and carbon dioxide.

Special protective equipment and precautions for fire-fighters:

Wear self-contained breathing apparatus.

Additional information:

Use fine water spray to cool endangered containers.

6. Accidental release measures

Personal precautions:

Remove all sources of ignition. Remove persons not involved upwind.
Wear suitable protective clothing. Do not breathe vapors. Provide adequate ventilation.

Environmental precautions:

Do not allow to penetrate into soil, waterbodies or drains.
Risk of explosion if the liquid enters the sewage system.
If necessary, notify appropriate authorities.

Methods for clean-up:

Soak up with absorbent materials such as sand, siliceous earth, acid- or universal binder.
Store in special closed containers and dispose of according to ordinance.
Keep away from sources of ignition - No smoking.

7. Handling and storage

Handling

Advices on safe handling:

Provide adequate ventilation, and local exhaust as needed.
Wear appropriate protective equipment. Do not allow containers to stand open.
Store product in a quantity adequate for 1 work-shift only.
Do not spray in the eyes.

Precautions against fire and explosion:

Take precautionary measures against static discharges.
Keep away from sources of ignition - No smoking.
Avoid sparks. Do not use any spark discharging tools/utensils.
Air combined with vapors may form potentially explosive mixtures that are heavier than air.

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 30/12/2022
Version: 15.2
Replaces version: 15.1
Language: en-CA,US
Date of print: 2/9/2025

ottobock.

640F18 - Donning spray for silicone liners and prosthetic gloves (silicone, PVC)

Material number 640F18

Page:

4 of 11

Storage

Requirements for storerooms and containers:

Keep container tightly closed in a cool, well-ventilated place.
Keep away from heat sources, sparks and open flames.
Protect from direct sunlight.

Hints on joint storage:

Do not store together with combustible or self-igniting materials or any highly flammable solids.

Avoid contact with strong oxidizing agents.

Further details:

Air combined with vapors may form potentially explosive mixtures that are heavier than air.

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
67-63-0	Isopropyl alcohol	Canada: OEL 15 min	984 mg/m ³ ; 400 ppm
		Canada: OEL 8 hour	492 mg/m ³ ; 200 ppm
		Canada: OEL STEL	400 ppm
		Canada: OEL TWA	200 ppm
		Canada: VECD	400 ppm
		Canada: VEMP	200 ppm
		USA: ACGIH: STEL	984 mg/m ³ ; 400 ppm
		USA: ACGIH: TWA	492 mg/m ³ ; 200 ppm
		USA: IDLH: TWA	2,000 ppm [10% LEL]
		USA: NIOSH: STEL	1,225 mg/m ³ ; 500 ppm
		USA: NIOSH: TWA	980 mg/m ³ ; 400 ppm
		USA: OSHA: TWA	980 mg/m ³ ; 400 ppm

Biological limit values:

CAS No.	Designation	Type	Limit value	Parameter	Sampling
67-63-0	Isopropyl alcohol	USA: ACGIH-BEI, urine	40 mg/L	Acetone in urine	end of shift at end of work week

Engineering controls

Provide good ventilation and/or an exhaust system in the work area.
Take precautionary measures against static discharges. Keep away from sources of ignition. Avoid sparks.
See also information in chapter 7, section storage.

Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection: Wear suitable protective clothing.
If necessary: Flame retardant protective clothing.

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 30/12/2022
Version: 15.2
Replaces version: 15.1
Language: en-CA, US
Date of print: 2/9/2025

ottobock.

640F18 - Donning spray for silicone liners and prosthetic gloves (silicone, PVC)

Material number 640F18

Page:

5 of 11

protective gloves according to OSHA Standard - 29 CFR: 1910.138.

Glove material:

- Butyl caoutchouc (butyl rubber), thickness $\geq 0,5$ mm, breakthrough time 8 h
- Fluororubber (Viton), thickness $\geq 0,4$ mm, breakthrough time 8 h
- Nitrile rubber, thickness $\geq 0,35$ mm, breakthrough time 8 h
- Polychloroprene, thickness $\geq 0,5$ mm, breakthrough time 4 h

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection:

When vapors form, use respiratory protection.

Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded. Use filter type A (= against vapors of organic substances) according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2.

When vapors form $< 0.5\%$: Filter A2

When vapors form $> 0.5\% - < 1\%$: Filter A3

When vapors form $> 1\%$: Respiratory protective device.

General hygiene considerations:

When using do not eat, drink or smoke.

Keep away from food and drinks.

Do not spray in the eyes. Provide a conveniently located eye rinse station.

Environmental exposure controls

Refer to 6.: Section "Environmental precautions".

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:	Form: liquid Color: colorless, clear
Odor:	alcoholic
Odor threshold:	No data available
pH:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point/flash point range:	24 °C (DIN 51755)
Evaporation rate:	No data available
Flammability:	No data available
Explosion limits:	LEL (Lower Explosion Limit): (Isopropyl alcohol) 2.00 Vol-% UEL (Upper Explosive Limit): (Isopropyl alcohol) 12.00 Vol-%
Vapor pressure:	at 20 °C: (Isopropyl alcohol) 44 hPa at 50 °C: (Isopropyl alcohol) 225 hPa
Vapor density:	No data available
Density:	at 20 °C: 0.908 g/mL
Water solubility:	at 20 °C: soluble
Partition coefficient: n-octanol/water:	(Isopropyl alcohol) $-0.16 \log P(o/w)$ Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.

640F18 - Donning spray for silicone liners and prosthetic gloves (silicone, PVC)

Material number 640F18

Page: 6 of 11

Auto-ignition temperature: No data available
Thermal decomposition: No data available
Ignition temperature: 425 °C (DIN 51794)

10. Stability and reactivity

Reactivity: Highly flammable liquid and vapor.

Chemical stability: Product is stable under normal storage conditions.

Possibility of hazardous reactions:
Liquid evaporates quickly.
Vapors are heavier than air and will travel at floor level.
Vapors may form explosive mixtures with air. Beware of reignition.

Conditions to avoid: Keep away from heat sources, sparks and open flames.
Take precautionary measures against static discharges.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible materials: Do not store together with combustible or self-igniting materials or any highly flammable solids.

Hazardous decomposition products:
In case of fire may be liberated: Carbon monoxide and carbon dioxide.

Thermal decomposition: No data available

11. Toxicological information

Toxicological tests

Acute toxicity: LD50 Rat, oral: 9,140 mg/kg

Toxicological effects: Acute toxicity (oral): Lack of data.
Acute toxicity (dermal): Lack of data.
Acute toxicity (inhalative): Lack of data.
Skin corrosion/irritation: Lack of data.
Serious eye damage/irritation: Eye Irritation 2A = Causes serious eye irritation.
Sensitisation to the respiratory tract: Lack of data.
Skin sensitisation: Lack of data.
Germ cell mutagenicity/Genotoxicity: Lack of data.
Carcinogenicity: Lack of data.
Reproductive toxicity: Lack of data.
Effects on or via lactation: Lack of data.
Specific target organ toxicity (single exposure): Specific Target Organ Toxicity (Single Exposure) 3 = May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure): Lack of data.
Aspiration hazard: Lack of data.

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 30/12/2022
Version: 15.2
Replaces version: 15.1
Language: en-CA,US
Date of print: 2/9/2025

ottobock.

640F18 - Donning spray for silicone liners and prosthetic gloves (silicone, PVC)

Material number 640F18

Page:

7 of 11

Symptoms

High concentrations of vapors irritate the eyes and mucous membranes.
After resorption: Headache, dizziness, inebriation, unconsciousness.
After contact with skin:
Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

12. Ecological information

Ecotoxicity

Aquatic toxicity: Isopropyl alcohol:
LC50 Leuciscus idus test: 8970 mg/l/48h
LC50 Goldfish: > 5000 mg/l/24h
EC50 Daphnia magna: 9740 mg/l/24h

Mobility in soil

No data available

Persistence and degradability

Further details: Product is readily biodegradable.

Additional ecological information

Volatile organic compounds (VOC):
50 % by weight / 454 g/L
General information: Do not allow to penetrate into soil, waterbodies or drains.

13. Disposal considerations

Product

Recommendation: Recycling or special waste incineration.

Package

Recommendation: Dispose of waste according to applicable legislation.
Non-contaminated packages may be recycled. Cleaning agent (recommendation): water

14. Transport information

UN number

ADR/RID, IMDG, IATA-DGR:
UN 1993

UN proper shipping name

ADR/RID, IMDG, IATA-DGR:
UN 1993, FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol, mixture)

640F18 - Donning spray for silicone liners and prosthetic gloves (silicone, PVC)

Material number 640F18

Page: 8 of 11

Transport hazard class(es)

ADR/RID: Class 3, Code: F1
IMDG: Class 3, Subrisk -
IATA-DGR: Class 3



Packing group

ADR/RID, IMDG, IATA-DGR:
III

Environmental hazards

Marine pollutant: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

USA: Department of Transportation (DOT)

Identification number: UN1993
Proper shipping name: UN 1993, FLAMMABLE LIQUIDS, N.O.S. (Isopropyl alcohol, mixture)
Hazard class or Division: 3
Packing Group: III
Labels: 3
Symbols: G
Special Provisions: B1, B52, IB3, T4, TP1, TP29
Packaging – Exceptions: 150
Packaging – Non-bulk: 203
Packaging – Bulk: 242
Quantity limitations – Passenger aircraft / rail: 60 L
Quantity limitations – Cargo only: 220 L
Vessel stowage – Location: A



Canada: Transportation of Dangerous Goods (TDG)

UN Number: UN1993
Shipping name: UN 1993, Flammable liquid, n.o.s. (Isopropyl alcohol, mixture)
TDG class: 3
Packing group: III
Special provisions: 16, 150
Explosive limit and limited quantity index: 5 L
Passenger carrying road or rail index: 60 L
Marine pollutant: P

640F18 - Donning spray for silicone liners and prosthetic gloves (silicone, PVC)

Material number 640F18

Page:

9 of 11

Sea transport (IMDG)

UN number: UN 1993
Proper shipping name: UN 1993, FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol, mixture)
Class or division, Subsidiary risk: Class 3, Subrisk -
Packing Group: III
EmS: F-E, S-E
Special Provisions: 223 274 955
Limited quantities: 5 L
Excepted quantities: E1
Package - Instructions: P001, LP01
Package - Provisions: -
IBC - Instructions: IBC03
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: T4
Tank instructions - Provisions: TP1, TP29
Stowage and handling: Category A.
Properties and observations: -
Marine pollutant: no
Segregation group: none

Air transport (IATA)

UN/ID number: UN 1993
Proper shipping name: UN 1993, FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol, mixture)
Class or division, Subsidiary risk: Class 3
Packing Group: III
Hazard label: Flamm. liquid
Excepted Quantity Code: E1
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y344 - Max. Net Qty/Pkg. 10 L
Passenger and Cargo Aircraft: Pack.Instr. 355 - Max. Net Qty/Pkg. 60 L
Cargo Aircraft only: Pack.Instr. 366 - Max. Net Qty/Pkg. 220 L
Special Provisions: A3
Emergency Response Guide-Code (ERG): 3L

15. Regulatory information

National regulations - Canada

Isopropyl alcohol: DSL: listed

National regulations - U.S. Federal Regulations

Isopropyl alcohol: TSCA Inventory: listed
Carcinogen Status:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed
NIOSH Recommendations:
Occupational Health Guideline: 0359

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 30/12/2022
Version: 15.2
Replaces version: 15.1
Language: en-CA,US
Date of print: 2/9/2025

ottobock.

640F18 - Donning spray for silicone liners and prosthetic gloves (silicone, PVC)

Material number 640F18

Page: 10 of 11

National regulations - U.S. State Regulations

Isopropyl alcohol:

Idaho Air Pollutant List:

Title 585: AAC: 49 -- EL: 65.3 -- WEL: 980 -Title 586: -

Massachusetts Haz. Substance codes: 2,4,5,6 F9

Minnesota Haz. Substance:

Codes: ANO -- Ratings: 7.84 -- Status: Title III. TRI.

New Jersey RTK Hazardous Substance:

DOT: 1219 - Sub No.: 1076 - TPQ: -

Pennsylvania Haz. Substance code: E

Washington Air Contaminant:

TWA: 400 ppm - 980 mg -- STEL: 500 ppm - 1225 mg

16. Other information

Text for labeling:

Contains 30 - 60 % Isopropyl alcohol. Safety data sheet available on request.

Contains Isopropyl alcohol.

Hazard rating systems:

NFPA Hazard Rating:

Health: 1 (Slight)

Fire: 2 (Moderate)

Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 1 (Slight)

Flammability: 2 (Moderate)

Physical Hazard: 0 (Minimal)

Personal Protection: K



HEALTH	1
FLAMMABILITY	2
PHYSICAL HAZARD	0
	K

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 30/12/2022
Version: 15.2
Replaces version: 15.1
Language: en-CA,US
Date of print: 2/9/2025

ottobock.

640F18 - Donning spray for silicone liners and prosthetic gloves (silicone, PVC)

Material number 640F18

Page: 11 of 11

Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
AS/NZS: Australian Standards/New Zealand Standards
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC: European Community
EC50: Effective Concentration 50%
EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods
EN: European Standard
EQ: Excepted quantities
Eye Irritation: Eye irritation
Flammable Liquid: Flammable liquid
IATA: International Air Transport Association
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
IMO: International Maritime Organization
LC50: Median lethal concentration
LD50: Lethal dose 50%
LEL: Lower Explosion Limit
log P(o/w): Partition coefficient: octanol/water
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OEL: Occupational Exposure Limit Value
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
STOT SE: Specific target organ toxicity - single exposure
TLV: Threshold Limit Value
TRGS: Technical Rules for Hazardous Substances
UN: United Nations
vPvB: Very persistent and very bioaccumulative
WEL: Workplace Exposure Limit
WHMIS: Workplace Hazardous Materials Information System

Reason of change: General revision

Date of first version: 23/4/2005

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.