

## 1. Product and company identification

### Product identifier

Trade name: BBI-2200S - Split cell battery

### Recommended use and restrictions on use

General use: Lithium-ion battery for orthopedic procedures  
For commercial user only.

### Initial supplier identifier

Company name: Otto Bock HealthCare Canada Ltd.

Street/POB-No.: 5470 Harvester Road

Postal Code, city: Burlington, ON L7L 5N5, CA  
Canada

WWW: [www.ottobock.ca](http://www.ottobock.ca)

E-mail: [info.canada@ottobock.com](mailto:info.canada@ottobock.com)

Telephone: (800) 665-3327

Telefax: (800) 463-3659

Department responsible for information:

Mark Agro, Telephone: (800) 665-3327 (9 am - 5 pm)

Additional information:

Corporate headquarters:  
Ottobock SE & Co. KGaA  
Max-Näder-Straße 15  
Duderstadt  
Germany

### Emergency phone number

**COLLECT, Telephone: (613) 996-6666**

**Transport:**

**CONSULTANK Lutz Harder GmbH (Contract QUALI003)**

**Telephone: +49 (0)178-4337434 (from USA: 01149 178 4337434)**

## 2. Hazards identification

### Emergency overview

Appearance: Physical state at 20 °C and 101.3 kPa: solid

Color: silvery

Odor: No data available

Classification: Article not subject to hazard labeling or classification.

### Regulatory status

This material is not considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and WHMIS in Canada.

## Hazards not otherwise classified

The battery is hermetically sealed.

danger of releasing ingredients, mentioned in section 3, by damaging the battery

- with strong mechanical action,
- in case of heating and/or fire,
- with influence of water,
- short circuit

Hazard statements:

In contact with water releases flammable gases. Formation of Hydrogen fluoride.

Toxic if swallowed. Causes severe skin burns and eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

Vapors irritate eyes, mucous membranes and respiratory system.

see section 11: Toxicological information

## 3. Composition / Information on ingredients

Chemical characterisation: Lithium-ion battery - Article, contains:  
Metals (inert), aluminium-plastic film, PCB

Electrolyte: Lithium hexafluorophosphate

The chemical materials are stored in a hermetically sealed metal case.

Relevant ingredients:

CAS No.	Designation	Concentration	Classification
CAS 12190-79-3	Cobalt lithium dioxide	40 %	Respiratory Sensitizer 1. Sensitization - skin 1. Carcinogenicity 2.
CAS 21324-40-3	Lithium hexafluorophosphate	15 %	Acute Toxicity 3 (oral). Skin Corrosion 1A. Eye Damage 1. Specific Target Organ Toxicity (Repeated Exposure) 1.
CAS 7440-50-8	Copper	10 %	Acute Toxicity 4 (oral). Aquatic toxicity - acute 1 (M-factor = 10). Aquatic toxicity - chronic 2.

Additional information: Contains Graphite and aluminium: The maximum workplace exposure limits are, where necessary, listed in section 8.

## 4. First aid measures

General information: First aider: Pay attention to self-protection!  
In case of damaged battery cases /  
In case of exposure to hazardous ingredients: Release of dangerous ingredients possible.  
The product may release harmful vapours by heating.

In case of inhalation: In case of damaged battery cases:  
Provide fresh air. Keep victim at rest in half upright position. Seek medical attention.

Following skin contact: In case of damaged battery cases / In case of exposure to hazardous ingredients:  
Clean with plenty of water. If possible, also wash with polyethylene glycol 400.  
Take off immediately all contaminated clothing. Seek medical attention.

After eye contact: In case of damaged battery cases / In case of exposure to hazardous ingredients: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Afterwards, consult an ophthalmologist immediately.

After swallowing: In case of damaged battery cases / In case of exposure to hazardous ingredients: Drink large quantities of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Risk of perforation in case of vomiting! Immediately get medical attention. Do not try to neutralize.

### Most important symptoms and effects, both acute and delayed

No hazardous reaction when handled and stored according to provisions.

In case of damaged battery cases /

In case of exposure to hazardous ingredients: Toxic if swallowed. Causes severe skin burns and eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

### Information to physician

Treat symptomatically.

## 5. Fire fighting measures

Flash point/flash point range:

Not applicable

Auto-ignition temperature: 130 °C

Suitable extinguishing media:

Only in case of small fires: metal fire extinguisher, sand

In case of large fires: water spray jet, extinguishing powder

### Specific hazards arising from the chemical

After contact with water: Formation of hydrogen fluoride

In case of fire may be liberated: Hydrogen fluoride, carbon monoxide and carbon dioxide, metal oxide smoke, toxic gases/vapours

Special protective equipment and precautions for fire-fighters:

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information:

Cool endangered containers with water spray and, if possible, remove from danger zone.

Temperatures > 125 °C: Danger of explosion!

Do not allow fire water to penetrate into surface or ground water.

## 6. Accidental release measures

Personal precautions:

In case of damaged battery cases:

Remove all sources of ignition.

Provide fresh air. Avoid contact with skin and eyes.

Wear suitable gloves.

Do not inhale vapors or dust particles.

Environmental precautions:

Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary. If necessary, notify appropriate authorities.

Methods for clean-up: Take up mechanically. Dispose of waste according to applicable legislation.  
Avoid generation of dust.

Information about electrolyte:  
Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents) and place in closed containers for disposal. Final cleaning.

Additional information: Danger of releasing ingredients, mentioned in section 3, by damaging the battery:

- with strong mechanical action,
- in case of heating and/or fire,
- with influence of water,
- short circuit.

## 7. Handling and storage

### Handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed.  
Avoid damage to the battery casing.  
In case of damaged battery cases: Avoid exposure.  
Work place should be equipped with a shower and an eye rinsing apparatus.

Precautions against fire and explosion:

- Avoid short circuit. Avoid open flames.
- Avoid temperatures exceeding 70 °C.
- Avoid damage to the battery casing.
- In case of damaged battery cases: Remove all sources of ignition.

### Storage

Requirements for storerooms and containers:

- Provide adequate ventilation. Store in a dry place. Keep only in original container.
- Protect from: humidity, heat, UV-radiation/sunlight
- Storage temperature: approx. 0 °C up to 35 °C at approx. 3.7 - 4.2 V/Cell

Hints on joint storage:

- Keep away from water, acids, bases and oxidizing agents
- Keep away from food, drink and animal feedingstuffs.

## 8. Exposure controls / personal protection

### Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
7782-42-5	Graphite	Canada: OEL 8 hour	2 mg/m <sup>3</sup> (respirable fraction)
		Canada: OEL TWA	2 mg/m <sup>3</sup> (respirable fraction)
		Canada: VEMP	2 mg/m <sup>3</sup> (respirable fraction)
		USA: ACGIH: TWA	2 mg/m <sup>3</sup> (respirable fraction)
		USA: IDLH: TWA	1,250 mg/m <sup>3</sup>
		USA: NIOSH: TWA	2.5 mg/m <sup>3</sup> (respirable fraction)
		USA: OSHA: TWA	15 mg/m <sup>3</sup> (total dust)
		USA: OSHA: TWA	5 mg/m <sup>3</sup> (respirable fraction)
7440-50-8	Copper	Canada: OEL 8 hour	0.2 mg/m <sup>3</sup> (Smoke)
		Canada: OEL 8 hour	1 mg/m <sup>3</sup> (Dusts and mist)
		Canada: OEL TWA	0.2 mg/m <sup>3</sup> (Smoke)
		Canada: OEL TWA	1 mg/m <sup>3</sup> (Dusts and mist)
		Canada: VEMP	0.2 mg/m <sup>3</sup> (Smoke, calculated as Cu)
		Canada: VEMP	1 mg/m <sup>3</sup>
			(Dusts and mist calculated as Cu)
		USA: ACGIH: TWA	0.2 mg/m <sup>3</sup> (Smoke)
		USA: ACGIH: TWA	1 mg/m <sup>3</sup>
			(Dusts and mist calculated as Cu)
		USA: IDLH: TWA	100 Cu/m <sup>3</sup> (dust and mist)
		USA: IDLH: TWA	100 Cu/m <sup>3</sup> (Smoke)
		USA: NIOSH: TWA	1 mg/m <sup>3</sup>
		USA: OSHA: TWA	0.1 mg/m <sup>3</sup> (Smoke; calculated as Cu)
		USA: OSHA: TWA	1 mg/m <sup>3</sup>
			(Dusts and mist calculated as Cu)
7429-90-5	Aluminium	Canada: OEL 8 hour	10 mg/m <sup>3</sup> (metal, dust)
		Canada: OEL 8 hour	5 mg/m <sup>3</sup>
			(Aluminium powder, pyrotechnic)
		Canada: OEL TWA	1 mg/m <sup>3</sup> (Pyrotechnical powders)
		USA: ACGIH: TWA	1 mg/m <sup>3</sup>
		USA: NIOSH: Ceiling	5 mg/m <sup>3</sup> (inhalable fraction)
		USA: NIOSH: TWA	10 mg/m <sup>3</sup> (inhalable fraction)
		USA: NIOSH: TWA	5 mg/m <sup>3</sup> (inhalable fraction)
		USA: OSHA: TWA	15 mg/m <sup>3</sup> (inhalable fraction)
		USA: OSHA: TWA	5 mg/m <sup>3</sup> (respirable fraction)

### Engineering controls

In case of damaged battery cases: Provide adequate ventilation.

In case of development of vapors or dust:

The use of local exhaust ventilation is recommended.

See also information in chapter 7, section storage.

### Personal protection equipment (PPE)

Eye/face protection:

In case of damaged battery cases:

Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection:	In case of damaged battery cases: Protective gloves according to OSHA Standard - 29 CFR: 1910.138. Glove material: neoprene or nitrile rubber Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
Respiratory protection:	Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded. The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, closed-circuit breathing apparatus must be used!
General hygiene considerations:	In case of damaged battery cases: Do not inhale vapors or dust particles. Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking. Wash hands before breaks and after work. When using do not eat or drink. Keep away from food, drink and animal feedingstuffs. Work place should be equipped with a shower and an eye rinsing apparatus.

### Environmental exposure controls

Refer to 6.: Section "Environmental precautions".

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Appearance:	Physical state at 20 °C and 101.3 kPa: solid Color: silvery
Odor:	No data available
Odor threshold:	No data available
pH:	Not applicable
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point/flash point range:	Not applicable
Evaporation rate:	No data available
Flammability:	No data available
Explosion limits:	No data available
Vapor pressure:	No data available
Vapor density:	No data available
Density:	No data available
Water solubility:	insoluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	130 °C
Thermal decomposition:	> 125 °C: Danger of explosion!
Additional information:	No data available

## 10. Stability and reactivity

Reactivity:	In case of damaged battery cases: May be corrosive to metals. Keep away from food, drink and animal feedingstuffs.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions:	Fire hazard in case of technical defects. In case of damaged battery cases: In contact with water releases flammable gases. Formation of Hydrogen fluoride
Conditions to avoid:	In case of strong heating: development of gas/vapor possible. Protect from: humidity, heat, UV-radiation/sunlight Avoid short circuit. Avoid damage to the battery casing. In case of damaged battery cases: Keep away from water. Keep away from sources of ignition - No smoking.
Incompatible materials:	Keep away from water, acids, bases and oxidizing agents.
Hazardous decomposition products:	No decomposition when used properly.
Thermal decomposition:	> 125 °C: Danger of explosion!

## 11. Toxicological information

### Toxicological tests

Toxicological effects:	Acute toxicity (oral): Lack of data. Acute toxicity (dermal): Lack of data. Acute toxicity (inhalative): Lack of data. Skin corrosion/irritation: Lack of data. Serious eye damage/irritation: Lack of data. Sensitisation to the respiratory tract: Lack of data. Skin sensitisation: Lack of data. Germ cell mutagenicity/Genotoxicity: Lack of data. Carcinogenicity: Lack of data. Reproductive toxicity: Lack of data. Effects on or via lactation: Lack of data. Specific target organ toxicity (single exposure): Lack of data. Specific target organ toxicity (repeated exposure): Lack of data. Aspiration hazard: Lack of data.
Other information:	In case of damaged battery cases / In case of exposure to hazardous ingredients: Toxic if swallowed. Causes severe skin burns and eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

## 12. Ecological information

### Ecotoxicity

Aquatic toxicity: In case of damaged battery cases:  
Very toxic to aquatic life with long lasting effects.

### Mobility in soil

No data available

### Persistence and degradability

Further details: Product is not biodegradable.

### Additional ecological information

General information: Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary.

## 13. Disposal considerations

### Product

Recommendation: Dispose of waste according to applicable legislation. The product contains: Metallic oxides containing heavy metals  
Recycling or special waste incineration.

### Package

Recommendation: Dispose of waste according to applicable legislation.  
Packing can be recycled or disposed of.

## 14. Transport information

### UN number

ADR/RID, IMDG, IATA-DGR:  
UN 3480

### UN proper shipping name

ADR/RID, IMDG, IATA-DGR:  
UN 3480, LITHIUM ION BATTERIES

### Transport hazard class(es)

ADR/RID: Class 9, Code: M4  
IMDG: Class 9, Subrisk -  
IATA-DGR: Class 9



### Packing group

ADR/RID, IATA-DGR: not applicable  
IMDG: -

### Environmental hazards

Marine pollutant: no



### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

#### USA: Department of Transportation (DOT)

Identification number: UN3480  
 Proper shipping name: UN 3480, LITHIUM ION BATTERIES  
 Hazard class or Division: 9  
 Labels: 9  
 Special Provisions: 388, 422, A54, A100  
 Packaging – Exceptions: 185  
 Packaging – Non-bulk: 185  
 Packaging – Bulk: 185  
 Quantity limitations – Passenger aircraft / rail: Forbidden  
 Quantity limitations – Cargo only: 35 kg  
 Vessel stowage – Location: A  
 Vessel stowage – Other: 156



#### Canada: Transportation of Dangerous Goods (TDG)

UN Number: UN3480  
 Shipping name: UN 3480, LITHIUM ION BATTERIES  
 TDG class: 9  
 Special provisions: 34, 123, 137, 138, 1  
 Explosive limit and limited quantity index: 0  
 Passenger carrying road or rail index: 5 kg

#### Sea transport (IMDG)

UN number: UN 3480  
 Proper shipping name: UN 3480, LITHIUM ION BATTERIES  
 Class or division, Subsidiary risk: Class 9, Subrisk -  
 Packing Group: -  
 EmS: F-A, S-I  
 Special Provisions: 188 230 310 348 376 377 384 387  
 Limited quantities: 0  
 Excepted quantities: E0  
 Package - Instructions: P903, P908, P909, P910, P911, LP903, LP904, LP905, LP906  
 Package - Provisions: -  
 IBC - Instructions: -  
 IBC - Provisions: -  
 Tank instructions - IMO: -  
 Tank instructions - UN: -  
 Tank instructions - Provisions: -  
 Stowage and handling: Category A. SW19  
 Properties and observations: Electrical batteries containing lithium ion may react (e.g., flame, heat, emission of toxic, corrosive or flammable gases or vapours) or disassemble due to damage, defects or short circuit.  
 Marine pollutant: no  
 Segregation group: none

### Air transport (IATA)

UN/ID number: UN 3480  
 Proper shipping name: UN 3480, LITHIUM ION BATTERIES  
 Class or division, Subsidiary risk: Class 9  
 Hazard label: Lithium batt or Sodium-ion batt  
 Excepted Quantity Code: E0  
 Passenger and Cargo Aircraft: Ltd.Qty.: Forbidden  
 Passenger and Cargo Aircraft: Forbidden  
 Cargo Aircraft only: Pack.Instr. See 965 - Max. Net Qty/Pkg. See 965  
 Special Provisions: A88 A99 A154 A183 A201 A213 A331 A334 A802  
 Emergency Response Guide-Code (ERG): 12FZ

## 15. Regulatory information

### National regulations - Canada

Cobalt lithium dioxide: DSL: listed  
 Graphite: DSL: listed  
 Lithium hexafluorophosphate: NDSL: listed  
 Copper: DSL: listed  
 Aluminium: DSL: listed

### National regulations - U.S. Federal Regulations

This product is an article as defined by TSCA regulations, and is exempt from TSCA inventory listing requirements.

### National regulations - U.S. State Regulations

No data available


### National regulations - EC member states

Further regulations, limitations and legal requirements:

Aluminium: Regulation (EU) 2019/1148 (marketing and use of explosives precursors): listed

## 16. Other information

Hazard rating systems:



NFPA Hazard Rating:  
 Health: 0 (Minimal)  
 Fire: 0 (Minimal)  
 Reactivity: 0 (Minimal)

HMIS Version III Rating:  
 Health: 0 (Minimal)  
 Flammability: 0 (Minimal)  
 Physical Hazard: 0 (Minimal)  
 Personal Protection: X = Consult your supervisor

In case of damaged battery cases: NFPA/HMIS: H3 / F2

HEALTH	0
FLAMMABILITY	0
PHYSICAL HAZARD	0
	X

### Abbreviations and acronyms:

Acute Toxicity: Acute toxicity  
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road  
 Aquatic toxicity - acute: Hazardous to the aquatic environment - acute  
 Aquatic toxicity - chronic: Hazardous to the aquatic environment - chronic  
 AS/NZS: Australian Standards/New Zealand Standards  
 Carcinogenicity: Carcinogenicity  
 CAS: Chemical Abstracts Service  
 CFR: Code of Federal Regulations  
 CLP: Classification, Labelling and Packaging  
 DMEL: Derived minimal effect level  
 DNEL: Derived no-effect level  
 EC: European Community  
 EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods  
 EN: European Standard  
 EQ: Excepted quantities  
 Eye Damage: Eye damage  
 IATA: International Air Transport Association  
 IATA-DGR: International Air Transport Association – Dangerous Goods Regulations  
 IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk  
 IMDG Code: International Maritime Dangerous Goods Code  
 IMO: International Maritime Organization  
 MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships  
 M-factor: Multiplication factor  
 OEL: Occupational Exposure Limit Value  
 OSHA: Occupational Safety and Health Administration  
 PBT: Persistent, bioaccumulative and toxic  
 PNEC: Predicted no-effect concentration  
 Respiratory Sensitizer: Sensitisation to the respiratory tract  
 RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail  
 Sensitization - skin: Skin sensitisation  
 Skin Corrosion: Skin corrosion  
 STOT RE: Specific target organ toxicity - repeated exposure  
 TLV: Threshold Limit Value  
 TRGS: Technical Rules for Hazardous Substances  
 TSCA: Toxic Substance Control Act  
 UN: United Nations  
 UV: Ultraviolet  
 vPvB: Very persistent and very bioaccumulative  
 WEL: Workplace Exposure Limit  
 WHMIS: Workplace Hazardous Materials Information System

Reason of change: Changes in section 14: IMDG 2025

Date of first version: 18/4/2017

### Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.