ottobock.

Shipping Address (if different from billing adress)

Genium X3 – Prosthetic knee joint - Order form

Order no.

Complete and send order to: order@ottobock.se

Billing Address

Customer no.

Company			Company			
Address			Address			
Orthopedic technici	an		Com.			
Prosthesis user					Mobility Grade	
Gender	☐ male	☐ female			☐ Mobility Grade 3	
Weight			kg		☐ Mobility Grade 4	
Foot size			cm			
Side of amputation	☐ left	☐ right	☐ bilateral		Amputation level	
Prosthetic attachment					☐ Knee Disarticulation	
to residual limb		onal socket anchored implant		☐ Transfemoral		
		r			☐ Hip Disarticulation / Hemipelvectomy	
Fitting						
☐ Initial fitting (of mic	roprocessor coi	ntrolled knee joint	made by Ottobock)			
	☐ previous	prosthetic knee joi	nt is known:			
	Manufacturer			Model		
	☐ previous	prosthetic knee joi	nt is unknown			
	☐ No previo	ous prosthetic knee	joint			
☐ Follow-up fitting (of	microprocessor	r controlled knee jo	oint made by Ottoboo	ck)		
	\rightarrow previous	microprocessor co	ntrolled knee joint			
	Model			Serial number	<u>.</u>	

ottobock.

Genium X3 – Prosthetic knee joint - Order form

Complete and send order to: order@ottobock.se

/maa !e!+								
nee joint 3B5-3	Carriana V2	apr a 61	F Continue V2 for large models and	11:1-				
	Genium X3		「 Genium X3 − for long residual					
cluding following	g additional components: 757L16-4 A	C Adapter, 4E60 Induc	tive Charger, 4H102/4H104 Kne	e Flexion Stops				
rotective co	ver (please select one)							
4X193-1	Protective Cover (graphite black	4 X900	4X900 Protective Cover (umbra grey)					
M	\.							
	ase choose one)	C						
3 years		6 years						
lectronic Tul	be Adapter							
2R19	AXON Tube Adapter							
Connection c	omponents							
4R11=F	R-3-2 Quickchange female pyr base	4R	11=ST-2-1 Quickchange thre	aded child adap	oter			
4R11=F	R-1-1 Quickchange female pyr adapt	er 4X	(907=1 Quickchange chil	d adapter ring				
4R11=P-1-1 Quickchange male pyr base		44	R57=WR Waterproof Rotati	on Adapter				
4R11=9	ST-1-1 Quickchange threaded adapter	4R	57=WR-ST Waterproof Rotati	on Adapter with	Thread			
oot parts								
1A1-2	Empower	1C60	Triton		1D35 Dynamic Mo			
1B1-2	Meridium	1C61	Triton Vertical Shock	:	1E56 Axtion			
1C30-1	Trias	1C62	Triton Harmony	:	1E57 Lo Rider			
1C40	C-Walk	1C63	Triton Low Profile ²		1E95 Challenger			
		1C64	Triton Heavy Duty ² Triton side flex ²					
olor of footshell	beige light brown ¹	1C68	Triton side flex ²					
nape of footshell	beige light brown slim normal							
	all feet and/or sizes. Please visit our hom	enage for more informa	ation)					
Trot available for t	an reet ana/or sizes. I rease visit our non	repage for more imprine	anom,					
1C50	Taleo ²	F21	21 Maverick Xtreme AT ²					
1C51	Taleo Vertical Shock	F22	Maverick Comfort AT ²					
1C52	Taleo Harmony	RS2-00	RS2-00 Runway					
1C53	Taleo Low Profile ²	RS2-K1						
1C58	Taleo Side Flex ²	LP2-W2	Freestyle Swim ²					
ctivity level	moderate high	Activity level	low moderate	high				
olor of footshell	beige light brown 1	Color footshell	light medium	dark				
nape of footshell	slim ¹ normal	Shape footshell [sandal toe¹ regular					
Not available for omponents.)	all feet and/or sizes. Please visit our ho	mepage for more inform	mation. ² Recommended combina	ation, because of	water & corrosion resista			
ccessories								
757L16-4	AC Adapter (additional)	4H101	Knee flexion stop (7,5°)					
4 E 60	Inductive Charger (additional)	60X5=2	BionicLink PC					

ottobock.

Genium X3 – Prosthetic knee joint - Order form

Complete and send order to: order@ottobock.se

The General Terms and Conditions of Ottobock SE & Co. KGaA apply.

The expected lifetime given compliance with the prescribed maintenance intervals is 6 years.

Additional information:

Date _______ Place ______ Signature