



ottobock.

## The C-Leg 4. Choose proven performance.

With over 100,000 fittings to date, the C-Leg is trusted by more users than any other microprocessor knee in the world. Studies show the C-Leg provides the exceptional reliability and performance users need to focus on what really matters — enjoying a healthy, active lifestyle<sup>1</sup>. The legacy lives on with the newest C-Leg 4 update.

### For users

- New!** ● User-controlled adjustments and select function activation via the **connectgo** user app
- Stumble recovery Plus active at all times
  - Reliable swing and stance phase control
  - Safe backward walking
  - Choice between intuitive and deliberate stance
  - Training function for stance release exercises
  - Improved stance release with short or quick steps
  - Supported descent on ramps and stairs
  - Increased support for sitting down
  - Deep sleep mode to save battery
  - Redesigned charger allowing one-handed operation
  - Manual locking function to conveniently secure the knee in extension via a simple tapping pattern
  - Intuitive Cycling feature: C-Leg recognizes when the user begins pedaling or dismounts the bike, adjusting the resistance automatically
  - Customizable shield insert
  - **IP68 Fresh Waterproof:** C-Leg is safe for occasional submersion in fresh water up to 3 meters for 1 hour. Not corrosion resistant.\*

### For professionals

Programming via the **connectgo.pro** set-up app.

Compatible with both Apple (iOS) and Android devices.

- Training function for ensuring consistent stance release
- Delivered in Safety Mode until patient-specific data is entered - A recommendation is then provided
- Standard 34 mm, easily shortened tube adapters
- Access usage statistics to see progress at each appointment
- Can be connected to an osseointegrated, percutaneous implant system\*\*

<sup>1</sup> Wismer, N., Mileusnic, M., Sreckovic, I., & Hahn, A. (2016). First results on next generation C-Leg. Poster presentation at OTWorld, Leipzig, Germany

\*Electronics are protected from dust, sand, dirt and occasional submersion in fresh water (up to 3m for 1hr). Mechanical components are not corrosion resistant.

\*\*Verify that the manufacturer of the implant system and the manufacturers of the corresponding exoprosthetic components/adapters also permit this combination.

# The C-Leg 4.

## Choose proven performance.

- 1 Integrated Bluetooth® technology**  
Enables direct communication with the knee for programming by the prosthetist (**connectgo.pro** app) and patient access via the **connectgo** user app
- 2 Lithium-ion battery**  
Located directly in the rotation axis – should be charged overnight when used on a daily basis
- 3 Inertial motion unit (IMU)**  
Gyroscope and accelerometers track spatial positioning and acceleration, enabling control based on motion analysis and additional force determination
- 4 Carbon frame design**  
Strong, high-grade, and lightweight to provide structural strength for the entire knee joint as well as protect the electronics, hydraulics, and battery during everyday activities
- 5 IP68 Rating: Fresh waterproof**  
Electronics are protected from fresh water up to 3m for 1 hour. Not corrosion resistant
- 6 Knee angle sensor**  
Measures flexion angle and angular velocity
- 7 Integrated microprocessor electronics**  
Coordinates all measurement and control processes
- 8 Hydraulic unit**  
Generates motion resistance for flexion and extension during the stance and swing phase
- 9 Charging receptacle**  
Easily accessed at the back of the joint and protected by a cover  
Compatible with the 757L43 USB-Adapter for charging



max. 136 kg

### Technical data

<b>Mobility grade</b>	2 – 4
<b>Max. body weight</b>	136 kg (300 lbs)
<b>Knee flexion angle</b>	130° without flexion stop <sup>1</sup>
<b>Weight (without tube adapter)</b>	1.250 g (pyramid) 1.255 g (threaded connector)
<b>Frame material</b>	Carbon
<b>Moisture protection</b>	Fresh waterproof (IP68), not corrosion-resistant
<b>Available colors</b>	Midnight shadow, desert pearl
<b>Tube adapter</b>	2R57, 2R67

<sup>1</sup>The flexion stop reduces the knee flexion angle by 8° (pre-assembled) or 16°.

### Prosthesis solution



6Y110 Skeo Sealing TF/  
6Y111 Skeo Sealing 3D TF  
7T450=1 SiOCX Socket  
21Y21 ClickValve



1B1-2 Meridium  
1C63 Triton Low Profile  
1C70 Evanto  
1C50 Taleo  
1C53 Taleo Low Profile

1C56 Taleo Adjust  
1C58 Taleo Side Flex  
F22 Maverick Comfort AT

[www.ottobock.com](http://www.ottobock.com)

US: P 800 328 4058 | F 800 962 2549  
CA: P 800 665 3327 | F 800 463 3659