

Foot portfolio.

| Category | Product | Max. body weight | Sizes | Build height | MG | |
|-----------------------------|--------------------------------------|--|-------------------------------|--|---|---|
| Low active | 1C10 Terion | 125 kg | 22–28 cm | 67 mm | 2, 3 | |
| | 1C11 Terion K2 | 175 kg | 22–30 cm | 65 mm | 1, 2 | |
| | 1C30-1 Trias | 125 kg | 21–30 cm | 113 mm | 2, 3 | |
| | 1D35 Dynamic Motion | 100 kg | 22–30 cm | 85 mm | 2, 3 | |
| | VS4 Kintrol | 136 kg | 23–30 cm | 112 mm | 1, 2 | |
| | VS5 Restore | 136 kg | 22–30 cm | 89 mm | 1, 2 | |
| Active | 1C40 C-Walk | 100 kg | 24–30 cm | 97 mm | 3, 4 | |
| | 1C50 Taleo | 150 kg | 22–30 cm | 150 mm | 3, 4 | |
| | 1C51 Taleo Vertical Shock | 150 kg | 22–30 cm | 185 mm | 3, 4 | |
| | 1C52 Taleo Harmony | 150 kg | 22–30 cm | 185 mm | 3, 4 | |
| | 1C53 Taleo Low Profile | 150 kg | 22–30 cm | 65 mm | 3, 4 | |
| | 1C56 Taleo Adjust | 115 kg | 22–28 cm | 118 mm | 2, 3 | |
| | 1C58 Taleo Side Flex | 130 kg | 22–30 cm | 97 mm | 3, 4 | |
| | 1C59 Taleo Adapt | 130 kg | 22–30 cm | 134 mm | 3, 4 | |
| | 1C70 Evanto | 125 kg | 22–30 cm | 82 mm | 3, 4 | |
| | 1E56 Axtion | 125 kg | 22–31 cm | 53 mm | 3, 4 | |
| | F22 Maverick Comfort AT | 166 kg | 23–30 cm | 117 mm | 2, 3 | |
| | Highly active | 1C60 Triton | 150 kg (MG 3) / 125 kg (MG4) | 21–30 cm | 163 mm | 3, 4 |
| 1C61 Triton Vertical Shock | | 150 kg (MG 3) / 125 kg (MG4) | 21–30 cm | 210 mm | 3, 4 | |
| 1C62 Triton Harmony | | 150 kg (MG 3) / 125 kg (MG4) | 21–30 cm | 210 mm | 3, 4 | |
| 1C63 Triton Low Profile | | 150 kg | 21–30 cm | 73 mm | 3, 4 | |
| 1C64 Triton Heavy Duty | | 150 kg | 21–30 cm | 149 mm | 3, 4 | |
| 1C68 Triton side flex | | 125 kg | 22–30 cm | 86 mm | 2, 3 | |
| F21 Maverick Xtreme AT | | 166 kg | 23–30 cm | 170 mm | 3, 4 | |
| F23 Maverick Vertical Shock | | 147 kg | 23–30 cm | 217 mm | 3, 4 | |
| R11 Renegade AT | | 166 kg | 22–31 cm | 184 mm | 3, 4 | |
| R16 Renegade LP-AT | | 166 kg | 22–31 cm | 140 mm | 3, 4 | |
| Mechatronic | | 1A1-2 Empower | 130 kg | 25–30 cm | 221 mm (size 27 cm) | 3, 4 |
| | | 1B1-2 Meridium | 125 kg | 24–29 cm | 160 mm | 2, 3 |
| | Limited build height | 1C20 ProSymes | 125 kg | 25–28 cm | 43 mm (with distance plate) 52 mm (without distance plate) | 2, 3 |
| | | 1E57 Lo Rider | 136 kg (MG 3) / 100 kg (MG 4) | 24–31 cm | 36 mm | MG 3, 4 |
| | | 1E81 Chopart footplate | 136 kg | 22–31 cm | 20 mm | 3, 4 |
| | | Sports | 1E2 ProCarve | 100 kg | universal | 138 mm (with attachment for ski binding) / 121 mm (with footshell) |
| 1E90 Sprinter | 125 kg | | universal | 100–394 mm (depending on selected adapter) | | |
| 1E91 Runner | 104 kg | | universal | 300 mm | | |
| 1E93 Runner junior | 45 kg | | universal | 185 mm | | |
| 1E95 Challenger | 110 kg | | 23–30 cm | 174 mm | | |
| LP2-W2 Freestyle Swim | 116 kg | | 22–31 cm | 103 mm | | |
| Children | 1K10 Dynamic foot for children | 35 kg (14–17 cm) / 45 kg (18–21 cm) | 14–21 cm | 58 mm | | |
| | 1K30 SACH foot for children | 35 kg (14–17 cm) / 45 kg (18–21 cm) | 14–21 cm | 58 mm | | |
| | 1S30 SACH foot for children | 35 kg | 12–13 cm | 51 mm | | |
| Other | 1WR95 Aqua foot with modular adapter | 150 kg | 24–28 cm | 85 mm | | |

The data refer to the build height of the prosthetic foot in size 26 cm and include the build height of the normal footshell if the prosthetic foot is to be used with a footshell (except for children's feet).

Waterproof: Resistant to fresh, chlorine and salt water. Submersion in water is possible. Clean and dry after contact with water. See product instructions for further information.

Weatherproof: Resistant to fresh water in the form of splash water (e.g. rain or shower). Clean and dry after contact with water. See product instructions for further information.