

# RS2 Runway

The Runway is intended for active users with mobility grade 2-3 and a body weight of up to 116 kg.

**Product features:**

- The easy heel-height adjustment from 0 to 5 cm allows users to wear different shoes
- RS1-00 Runway: push-button function to switch between 10 different heel heights
- RS1-K1 Runway HX: infinite adjustment of heel height using a hex key
- The design of the adjustable ankle elements makes it possible to adapt the heel height without the technician changing the static alignment
- Weatherproof

More than a foot.  
A foundation.




**Technical data**

K-Level / Mobility grade	2, 3
Max. body weight	255 lbs / 116 kg
Side	left (L), right (R)
Sizes	22-28 cm
Footshell shape	Sandal toe, Regular
Footshell colour	Light, Medium, Dark
Weight with footshell*	27.94 oz / 792 g
Heel height	0"-2" / 0-50 mm
Build height*	3 15/16" / 100 mm

\* Reference size is 26 cm.

**Compatible mechatronic knee joints  
(see next page for details)**



## RS2 Runway

### Order form

Customer		Shipping address (if different from customer address)	
Customer no.		Customer no.	
Company		Company	
Street		Street	
Postal code/city		Postal code/city	
O&P professional		Customer ref.	

### Selection of the spring stiffness relative to

#### 1 body weight and activity as well as

Body weight	Activity level		
	Low	Moderate	High
100 – 115 lbs / 44 – 52 kg	1	1	2
116 – 130 lbs / 53 – 59 kg	1	2	3
131 – 150 lbs / 60 – 68 kg	2	3	4
151 – 170 lbs / 69 – 77 kg	3	4	5
171 – 195 lbs / 78 – 88 kg	4	5	6
196 – 220 lbs / 89 – 100 kg	5	6	–
221 – 255 lbs / 101 – 116 kg	6	–	–

#### 2 foot size

Stiffness	Foot size					
	1	2	3	4	5	6
22					***	**
23					***	**
24		no restrictions			***	**
25					***	**
26					***	**
27	***	***	***	***	***	**
28	***	***	***	***	***	**

\*\* Do not combine this configuration with a 3C88-3 / 3C98-3 C-Leg 4.

\*\*\* Do not combine this configuration with a 3C88-3 / 3C98-3 C-Leg 4 for body weight > 75 kg (165 lbs)

### Foot module part number

Reference number	Product ID	Stiffness	Size	Toe Configuration
RS2	-	0	A	-
	Product ID	Stiffness	Size (cm)	Toe Configuration
	00 Runway	1–6	22, 23, ..., 28	RL Regular toe, left
	K1 Runway HX			RR Regular toe, right
				SL Sandal toe, left
				SR Sandal toe, right

### Scope of delivery

- RS2-0\* Runway or RS2-K1\* Runway HX
- 2F11=1 Set of heel wedges
- Spectra protective sock black
  - 22-23 cm: S0-NPS-20025-00
  - 24-26 cm: S0-NPS-20030-00
  - 27-28 cm: S0-NPS-20035-00
- ACC-00-10400-00 Shim wrench
- Runway HX: ACC-00-10400-4M Adjustment wrench

### Footshell part number

Reference number	Footshell shape	Profile	Size	Colour	Toe	Side
FTC	-	-	1	-	4	-
	Footshell shape	Profile	Size (cm)	Colour	Toe	Side
	2 Sandal toe	D Runway	22, 23, ..., 28	L Light	R Regular	L Left
	3 Regular	E Runway HX		M Medium	S Sandal	R Right
				D Dark		

### Accessories & spare parts

- SL=SPECTRA-SOCK7 Spectra protective sock black
- ACC-00-10300-00 Footshell removal tool

### Available footshells

- FTC-3D-1\*: Footshell Runway regular
- FTC-2D-1\*: Footshell Runway sandal toe
- FTC-3E-1\*: Footshell Runway HX regular
- FTC-2E-1\*: Footshell Runway HX sandal toe