

C-Leg. Order form.

Contact person	Customer no.	Date
----------------	--------------	------

Customer

Company	
Street	
Postal code	City
Email	
Commision	




Shipping address (if different from customer address)

Company	
Street	
Postal code	City
Email	

Prosthesis user

Gender	Male	Female	Diverse
Weight	kg		
Foot size	cm		
Side of amputation	Left	Right	Bilateral
Prosthetic attachment to residual limb	Osseous anchored implant Conventional socket		

Mobility grade

Mobility grade 2	
Mobility grade 3	
Mobility grade 4	

Amputation level

Knee disarticulation
Transfemoral
Hip disarticulation/Hemipelvectomy

Fitting

Initial fitting (of microprocessor-controlled knee joint made by Ottobock)
 Previous prosthetic knee joint is known

Manufacturer	Model
Previous prosthetic knee joint is unknown	
No previous prosthetic knee joint (initial amputation)	

Follow-up fitting (of microprocessor-controlled knee joint made by Ottobock)
 Previous microprocessor-controlled knee joint

Model	Serial number
-------	---------------

Knee joint (incl. AC adapter and battery charger)

- 3C98-3=8.5-4 C-Leg (midnight shadow)
- 3C88-3=8.5-4 C-Leg (midnight shadow) for long residual limb
- 3C98-3=9.2-4 C-Leg (desert pearl)
- 3C88-3=9.2-4 C-Leg (desert pearl) for long residual limb

Warranty (please select one)

- 3 years (SP-3C98-3=3)
- 6 years (SP-3C98-3=6)

Tube adapter

	2R57	Tube adapter		2R67	Tube adapter (torsion unit)
--	-------------	--------------	--	-------------	-----------------------------

Connection components

	4R57	Rotation adapter		4R11=P-1-3	Quickchange set with pyramid
	4R57=ST	Rotation adapter with thread		4R11=R-1-3	Quickchange set with pyramid receiver
	4R57=WR	Rotation adapter (waterproof and corrosion resistant)		4R11=ST-1-3	Quickchange set with thread
	4R57=WR-ST	Rotation adapter with thread (waterproof and corrosion resistant)		4R11=R-3-2	Quickchange base element with pyramid receiver
				4R11=P-1-1	Quickchange connecting element with pyramid
				4R11=R-1-1	Quickchange connecting element with pyramid receiver
				4R11=ST-1-1	Quickchange connecting element with thread

Feet parts

	1A1-2	Empower		1C63	Triton Low Profile
	1A30	Greissinger plus		1C64	Triton Heavy Duty
	1B1-2	Meridium		1C68	Triton side flex
	1C10	Terion		1C70	Evanto
	1C11	Terion K2		1D10	Dynamic foot with adapter
	1C30-1	Trias		1D11	Dynamic foot
	1C40	C-Walk		1D35	Dynamic Motion
	1C60	Triton		1E56	Axtion
	1C61	Triton Vertical Shock		1E57	Lo Rider
	1C62	Triton Harmony		1M10	Adjust

Color of footshell Beige Light brown¹
Shape of footshell Slim¹ Normal

¹ Not available for all feet and/or sizes. Please visit our homepage for more information.

	1C50	Taleo		F21	Maverick Xtreme AT
	1C51	Taleo Vertical Shock		F22	Maverick Comfort AT
	1C52	Taleo Harmony		F23	Maverick Vertical Shock
	1C53	Taleo Low Profile			
	1C56	Taleo Adjust			
	1C58	Taleo Side Flex			
	1C59	Taleo Adapt			

Activity level Normal High Moderate High
Color of footshell Beige Light brown¹
Shape of footshell Slim¹ Normal Sandal toe

¹ Not available for all feet and/or sizes. Please visit our homepage for more information.

Accessories

	757L16-4	Power adapter		4H105	Knee-extender
	4E50-3	Charger		4H106	Flexion stop 16°
	757L43	USB adapter for charging		757P48	Y-adapter cable
	4X156-1	Charger extension cable – ankle		560X29-1*	connectgo.pro
	4X157-1	Charger extension cable – knee			
	4X158-1	Charger extension cable – ankle, long			



C-Leg. Order form.

Cosmesis

	3S26	Standard foam cover		99B120	Stocking
	3F1=1	Functional cosmesis	Size	S L	
			Color	Beige Brown Black	

Protective cover

	4X860=S/M/L	Protective cover (champagne) ²		4P863=2	Shield insert
	4X860=S/M/L-8.4	Protective cover (dark volcano) ²		4P863=3	Shield insert
	4P862	C-Leg guard		4P863=4	Shield insert
	4P863=1	Shield insert blank			

The general terms and conditions of Ottobock SE & Co. KGaA apply.
The expected lifetime given compliance with the prescribed maintenance intervals is 6 years.
For additional information please contact / visit:

Date

Place

Signature