

ottobock.

Dynion.

Be independent and go beyond.

Dynion is designed for active individuals who lead the way on their own terms and are looking for a reliable companion in their everyday lives.

Made for optimal fitting results:

- Dynamic, dependable control throughout the gait cycle thanks to a powerful rotary hydraulic
- Support when going down stairs, ramps and declines provided by consistent flexion resistance
- More freedom in daily life with a waterproof solution
- Effortless standing with activated manual lock
- Easy participation in bicycling with family and friends thanks to a Bicycle Mode

Dynion consistently supports through a wide range of daily activities, and provides stability where additional balance is required (i.e., from the Manual Lock).



Technical data

Article number	3R85
Recommended mobility grade	Mobis 3 – 4
Max. body weight	100 kg / 220 lbs
Moisture protection	Waterproof
Weight of the knee joint	1.240 g / 2,73 lbs
Build height	216,5 mm
Included in scope of delivery	2R37, waterproof tube adapter
Knee flexion angle	145°



Suitable components. For individual prosthetic solutions.

6Y110

Skeo Sealing liner

The Skeo Sealing liner ensures Derick a secure and reliable prosthetic connection. The smooth outer coating and visual and haptic orientation guide on the inside makes it easier for him to put the liner on and take it off.

4R57 = WR

Waterproof rotation adapter

The rotation adapter allows Derick to sit in a relaxing position, cross his legs or put on socks and shoes without strain.



3R85

Dynion prosthetic knee joint

Dynion is a reliable companion in Derick's daily activities, because it adapts to varying walking speeds, provides him reliable support when going down stairs, ramps and declines. The Bicycle Mode allows Derick to easily ride a bike.

1C50

Taleo prosthetic foot

The *Taleo* foot provides Derick a smooth rollover and efficient energy return at a wide range of walking speeds – with varying ground condition, which enables him to keep up with his family and friends.

Tried and tested: components for a *Dynion* fitting**

Liner and adapter



21Y21
Click valve



4R57 = WR
Rotation adapter



4WR95 = 1
Lamination anchor



6Y110
Skeo Sealing liner



2R37
Tube adapter (incl.)

Feet



1C30
Trias



1C50
Taleo



1C58
Taleo SF



1C60
Triton



1C68
Triton SF

** All components are sold separately and are Ottobock products which help to ensure the optimal performance of the 3R85 *Dynion* knee joint. Practitioners need to select components based upon individual patient criteria.

www.ottobock.com