

DIAMOND SERIES

LED HIGHBAY 80W-200W









Features

- 1. Die casting aluminum housing.
- 2. Perfectly suitable for logistical centers, warehouses.
- 3. Beam angle optional: 60°; 90°; 120°
- 4. Unique style, mason own design.
- 5. Branded LED driver and LED components
- 6. Easy to install, fast replacement.
- 7. Flexible solutions for different efficiency and lumens output.

Application

Warehouse, Workshop, Garage, Stadium, Supermarket, Hall and other indoor public/private places.







Technical parameter

Model No.	Model No. System Power Luminous Efficiency		Structure Description	Product Size(Φ*H)mm	Weight(kg)	
MS-SP263080	80W	130-160lm/W	Die casting aluminium	255*126	2.5	
MS-SP263100	100W	130-160lm/W	Die casting aluminium	255*126	2.55	
MS-SP264150	150W	130-160lm/W	Die casting aluminium	305*136	3.5	
MS-SP265200	200W	130-160lm/W	Die casting aluminium	305*136	3.55	



- 1. Up to 3 hours rated duration.
- 2. Built-in non-replaceable Li-lon battery pack.
- 3. Over-charge, over-current, short-circuit and deep discharge protection for battery.
- 4. For maintained or non-maintained emergency lighting systems.
- 5. Wired between LED module and LED driver via water-proof connector.
- 6. Suitable for use in luminaires for high-risk task area lighting.



Application

Warehouse, Workshop, Garage, Stadium, Supermarket, Hall and other indoor public/private places.











Battery Pack Options

Output Wattage	Battery Type	Battery Capacity	Rated Duration Time	Test Function	Charging Time	Battery Life
4W	Li-lon 18650	2600mAh	3Hrs	Manual	24Hrs	2 Years
8W	Li-lon 18650	5200mAh	3Hrs	Manual	24Hrs	2 Years
10W	Li-lon 18650	6000mAh	3Hrs	Manual	24Hrs	2 Years

ID65	CRI 80	220-2401/	-₩\- 47-63Hz	PF >0.95	20-95% PH	CCT 3000K / 4000K	CCT 5700K	50000H
IP65	80	220-2407	47-63HZ	>0.95	20-95%RH	5000K	6500K	50000H



DIAMOND SERIES

LED HIGHBAY **EMERGENCY VERSION**









