

## BPL SERIE

Model	Voltage	Capacity(Ah)			Weight Kg	Terminal Standard	Terminal Optional	Terminal Type	Terminal Optional	L mm	W mm	H mm	TH mm
		20Hr	5Hr	30min									
BPL3.3-12	12 V	3.3	2.81	1.65	1.35	T1	4	T2		134	67	60	66
BPL7-12	12 V	7	5.95	3.5	2.6	T2	5	T1		151	65	93	98
BPL7.5-12	12 V	7.5	6.38	3.75	2.7	T2		T1		151	65	94	100
BPL12-12	12 V	12	10.2	6	3.98	T2	5	T1					
BPL17-12	12 V	17	14.45	8.5	6.15	B1	7	T2 I1	6	181	76	166	166
BPL20-12	12 V	20	17	10	6.4	B1	7	T2 I1	6	181	76	166	166
BPL26-12	12 V	26	22.1	13	9.6	B1	7	T2 I1	9	175	166	125	125
BPL28-12	12 V	28	23.8	14	9.7	B1	7	T2 I1	9	175	166	125	125
BPL33-12 Standard Type	12 V	33	28.05	16.5	11.5	B7	8			195	129	155	179
BPL33-12 Handle Type	12 V	33	28.05	16.5	11.5	B7	8	I2		210	129	168	179
BPL33-12 Finger Type	12 V	33	28.05	16.5	11.5	B7	8	I2		195	129	168	179
BPL40-12	12 V	40	34	20	14.6	B2	7	I1 I2		197	165	171	171
BPL65-12	12 V	65	55.25	32.5	25	B5	15	I2		350	166	174	174
BPL80-12	12 V	80	68	40	26.8	I2	7			260	168	213	215
BPL85-12	12 V	85	72.25	42.5	31.2	B3	15	I2		329	172	215	238
BPL110-12	12 V	110	93.5	55	40	B4	18	I2		407	173	210	239
BPL150-12	12 V	150	127.5	75	51.8	B9	15	I3		483	171	240	240
BPL170-6	6 V	170	144.5	85	29.2	B9	19	I3		260	171	220	244
BPL210-12	12 V	210	178.5	105	73.2	B9	13	I3		522	240	216	240
BPL95-12	12 V	95	80.8	47.5	33.2	B3	15	I2		329	172	215	238