

HR SERIE

Model	Voltage	Capacity(Ah)		Weight Kg	Terminal				Dimension			
		15Min W/Cell	10Hr Ah		Standard Type	Position	Optional Type	Position	L mm	W mm	H mm	TH mm
HR9-6	6 V	36	8	1.4	T2	2	T1		151	34	94	100
HR4-12	12 V	16	3.5	1.4	T1	3	T2		134	67	60	66
HR5.5-12	12 V	22	5	1.8	T1	3	T2		90	70	102	106
HR5.8-12	12 V	23	5.3	1.88	T1	3	T2		90	70	102	106
HR6-12	12 V	24	5.5	2.1	T1	5	T2		151	51	94	100
HR8-12	12 V	32	7	2.6	T2	5	T1		151	65	94	100
HR9-12	12 V	36	8	2.75	T2	5	B0 B1		151	65	94	100
HR15-12	12 V	60		4.2	T2	5	T1		151	98	94	98
HR22-12	12 V	88	20	6.5	B1	7	T2 l1	6	181	76	166	166
HR33-12	12 V	132	31	10	B1	7	T2 l1	9	175	166	125	125
HR40-12 Standard Type	12 V	160	38	12.1	B7				195	129	155	179
HR40-12 Handle Type	12 V	160	38	160	B7	8	l2		210	129	168	179
HR40-12 Finger Type	12 V	160	38	12.1	B7	8	l2		195	129	168	179
HR50-12	12 V	200	48	15.3	B2	7	l1 l2		197	165	171	171
HR75-12	12 V	300	73	24.75	B5	15	l2		350	166	174	174