

Boat Battery Products

NO.	P/N	Picture	Description (LifePO4)	Specification	Size Weight
1	S220Pro		NMEA2000 compliant VICTRON inverter compatible CE, UN38.3, SDS, IP67, UL94-V0 Max continous current: 150A Crank current: 800A (3.5S) Surge Current: 400A (30S)	12.8V 220AH LiFePO4	378*205*257mm 20Kg/ 44.1lbs
2	S24110Pro		NMEA2000 compliant VICTRON inverter compatible CE, UN38.3, SDS, IP67, UL94-V0 Max continous current: 100A Crank current: 1500A (3.5S) Surge Current: 400A (30S)	25.6V 110AH LiFePO4	378*205*257mm 19.8Kg/ 43.6lbs
3	S110BT		Superior DUAL CE, UN38.3, SDS, IP67, UL94-V0 Max continous current: 100A Crank current: 800A (3.5S) Surge Current: 400A (30S)	12.8V 110AH LiFePO4	279*185*179mm 11Kg/ 24.3lbs
4	S200BT		Superior DUAL CE, UN38.3, SDS, IP67, UL94-V0 Max continous current: 100A Crank current: 1500A (3.5S) Surge Current: 300A (60S)	12.8V 200AH LiFePO4	376*194*227mm 19.8Kg/ 43.6lbs
5	S24110BT		Superior DUAL CE, UN38.3, SDS, IP67, UL94-V0 Max continous current: 100A Crank current: 800A (3.5S) Surge Current: 300A (60S)	25.6V 110AH LiFePO4	376*194*227mm 19.8Kg/ 43.6lbs
6	D105BT		DEEP CYCLE SUPPLY CE, UN38.3, SDS Max continous current: 100A Peak current: 300A (3.5S)	12.8V 105AH LiFePO4	329*172*235mm 12.5Kg/ 27.6lbs
7	D125BT		DEEP CYCLE SUPPLY CE, UN38.3, SDS Max continous current: 100A Peak current: 300A (3.5S)	12.8V 125AH LiFePO4	329*172*235mm 13.5Kg/ 29.7lbs

5. Warranty: 2 years after the battery leaves the factory