

## **PHANTOM SERIES**

LED FLOOD LIGHT 400W-1200W







## **Features**


- Light source: CREE/PHILIPS/OSRAM original high-power LED is selected, which fully guarantees the stability of the light color and maintenance rate of luminous flux.
- 2. Driver: Adopted the world-wild branded driver, the reliability and stability of the lights have been greatly improved.
- 3. Light distribution: Patented secondary light distribution design, with multiple angles to meet the needs of different places.
- 4. Heat dissipation: The radiator adopts a cold forging manufacturing process to ensure the LED has a good performance in heat dissipation, and the temperature rise is within the design range. Appearance: The novel and unique design to make a excellent visual and physical texture.
- Structure: Modular design is adopted to meet the needs of different powers of customers.
- Control System: Receptacle/ dimming/ remote control interfaces is reserved, which can easily realize various controls.
- 7. Protection: 5mm thick tempered glass is used to reach the impact protection level IKO8, and the waterproof protection IP66.






## **Application**

Golf courses, football fields, other outdoor courts, ports, airports, entrances and exits of railway





## **Technical parameter**

Model No.	System Power	Luminous Efficiency	Structure Description	Product Size(L*W*H)mm	Weight(kg)
MS-FL1190400	400W	130lm/W, 150lm/W	Die-casting	559*485*113mm	14
MS-FL1200500	500W	130lm/W, 150lm/W	Die-casting	559*485*113mm	14
MS-FL1210600	600W	130lm/W, 150lm/W	Die-casting	559*485*113mm	14
MS-FL1220800	800W	130lm/W, 150lm/W	Die-casting	780*616*113mm	25.25
MS-FL1231000	1000W	130lm/W, 150lm/W	Die-casting	780*616*113mm	25.25
MS-FL1241200	1200W	130lm/W, 150lm/W	Die-casting	780*616*113mm	25.25





100-240V 120-277V <del>- ₩\</del> 47-63H PF >0.95

20-95%RF

CCT 3000K / 4000K 5000K T OK 50000H



45