

HRL SERIE

Model	Voltage	Capacity(Ah) 15Min W/Cell	10Hr Ah	Weight Kg	Terminal Standard Type	Optional Type	Dimension			TH mm
							L mm	W mm	H mm	
HRL5.5-12	12 V	2.75	5	1.8	T1	T2	90	70	102	106
HRL5.8-12	12 V		5.3	1.88	T1	T2	90	70	102	106
HRL8-12	12 V		7		T2	T1	151	65	94	100
HRL9-12	12 V		8	2.75	T2	T1 B0	151	65	94	100
HRL15-12	12 V		13	4.2	T2	T1	151	98	94	98
HRL22-12	12 V		20		B1	T2 I1	181	76	166	166
HRL33-12	12 V		31	10	B1	T2 I1	175	166	123	125
HRL40-12 (F Type)	12 V		38	12.1	B7	I2	195	129	168	B7:179, I2:168
HRL40-12 (H Type)	12 V		38	12.1	B7	I2	210	129	168	B7:179, I2:168
HRL40-12	12 V		38		B7		195	129	155	B7:179, I2:168
HRL50-12	12 V		48	15.3	B2	I1 I2	197	165	171	171
HRL75-12	12 V		73	24.75	B5	I2	350	166	174	174
HRL215-12	12 V		205	66	I3	I4	522	202	218	221.5
HRL1234W	12 V		7	2.6	T2	T1	151	65	94	100