

PATRON SERIES

LED TRI-PROOF LIGHT

12W-80W





Features

1. Ingress protection: IP67 / IP68, IP69K (Suitable for hotwater washing)
2. Mechanical Strength: IK08-10
3. UV resistance
4. Ammonia resistance
5. Corrosion resistance

Application

Car washing yard, Parking lot, Meat processing, Farm,
Food processing yard, Low temperature storage room, Department store



Technical parameter

Model No.	System Power	Luminous Efficiency	Diameter	Length(mm)
MS-LL060012-50BF	12W	≥ 130lm/W	φ48mm	0.6m
MS-LL060012-40BF	12W	≥ 130lm/W	φ48mm	0.6m
MS-LL012024-50BF	24W	≥ 130lm/W	φ48mm	1.2m
MS-LL012024-40BF	24W	≥ 130lm/W	φ48mm	1.2m
MS-LL015032-50BF	32W	≥ 130lm/W	φ48mm	1.5m
MS-LL015032-40BF	32W	≥ 130lm/W	φ48mm	1.5m
MS-LL060020-50BF	20W	≥ 130lm/W	φ70mm	0.6m
MS-LL060020-40BF	20W	≥ 130lm/W	φ70mm	0.6m
MS-LL012035-50BF	35W	≥ 130lm/W	φ70mm	1.2m
MS-LL012035-40BF	35W	≥ 130lm/W	φ70mm	1.2m
MS-LL015045-50BF	45W	≥ 130lm/W	φ70mm	1.5m
MS-LL015045-40BF	45W	≥ 130lm/W	φ70mm	1.5m
MS-LL060024-50BF	24W	≥ 130lm/W	φ100mm	0.6m
MS-LL060024-40BF	24W	≥ 130lm/W	φ100mm	0.6m
MS-LL012050-50BF	50W	≥ 130lm/W	φ100mm	1.2m
MS-LL012050-40BF	50W	≥ 130lm/W	φ100mm	1.2m
MS-LL150080-50BF	80W	≥ 130lm/W	φ100mm	1.5m
MS-LL150080-40BF	80W	≥ 130lm/W	φ100mm	1.5m

IP66 IK03 CRI 220-240V 47-63Hz PF 20-95%RH CCT 5000K 3000K 50000H 20°C 45°C