

MSB SERIE

Model	Voltage	Capacity(Ah)			Weight Kg	Terminal Standard Type	Optional Type	Dimension			
		10Hr	3Hr	1Hr				L mm	W mm	H mm	TH mm
MSB-200 (2V, 200Ah)	2 V	200	150	110	16	B6	I3	173	111	329	357
MSB-300 (2V, 300Ah)	2 V	300	225	165	24	B6	I3	171	151	330	358
MSB-400 (2V, 400Ah)	2 V	400	300	220	31.5	B6	I3	211	176	329	357
MSB-500 (2V, 500Ah)	2 V	500	375	275	36	B6	I3	241	172	331	359
MSB-600 (2V, 600Ah)	2 V	600	450	330	46	B6	I3	301	175	331	359
MSB-800 (2V, 800Ah)	2 V	800	600	440	63	B6	I3	410	175	330	358
MSB-1000 (2V, 1000Ah)	2 V	1000	750	550	72	B6	I3	475	175	328	356
MSB-1500 (2V, 1500Ah)	2 V	1500	1125	825	128	B6		400	350	341	369
MSB-2000 (2V, 2000Ah)	2 V	2000	1500	1100	153	B6		490	350	343	371
MSB-3000 (2V, 3000Ah)	2 V	3000	2250	1650	215	B6		710	353	341	369