

BP SERIE

Model	Voltage	Capacity(Ah)			Weight Kg	Terminal		Terminal		L mm	W mm	H mm	TH mm
		20Hr	10Hr	5Hr		Standard	Position	Optional	Position				
BP10-4	4 V	10	9.5	8.5	1.31	T1	2	T2		101	50	94	100
BP1.0-6	6 V	1	0.95	0.85	0.25	T1	1			51	42	51	56
BP1.2-6	6 V	1.2	1.14	1.02	0.3	T1	2			97	25	51	56
BP3-6	6 V	3	2.85	2.55	0.65	T1	2	T2		134	34	60	66
BP4-6	6 V	4	3.8	3.4	0.85	T1	1	T2		70	47	101	106
BP4.5-6	6 V	4.5	4.28	3.83	0.91	T1	1	T2		70	48	102	107
BP7-6	6 V	7	6.65	5.95	1.26	T1	2	T2		151	34	94	100
BP8-6	6 V	8	7.6	6.8	1.35	T1	14	T2		151	34	94	100
BP8-6V	6 V	8	7.6	6.8	1.55	T1	14	T2		98	56	118	118
BP10-6	6 V	10	9.5	8.5	1.9	T1	2	T2		151	50	94	100
BP12-6	6 V	12	11.4	10.2	1.98	T1	2	T2		151	50	94	100
BP13-6 S	6 V	13	12.35	11.05	2.5	T3	10			108	71	140	140
BP33-6	6 V	33	31.35	28.05	6	B1	7	T2	6	181	76	166	166
BP180-6	6 V	180	171	153	28.8	B9	19	I3		260	171	220	244
BP1.2-12	12 V	1.2	1.14	1.02	0.59	T1	4			97	45	53	59
BP2.3-12	12 V	2.32	2.19	1.96	0.94	T1	2			178	34	60	65
BP3-12	12 V	3	2.85	2.55	1.32	T1	4	T2		134	67	60	66
BP3.6-12	12 V	3.6	3.42	3.06	1.32	T1	4	T2		134	67	60	66
BP4-12	12 V	4	3.8	3.4	1.67	T1	3	T2		90	70	102	106
BP4.5-12	12 V	4.5	4.28	3.83	2.7	T1	3	T2		90	70	102	106
BP5-12	12 V	5	4.75	4.25	1.8	T1	3	T2		90	70	102	106
BP7-12	12 V	7	6.65	5.95	2.54	T2	5	T1		151	65	93	98
BP7.5-12	12 V	7.5	7.13	6.38	2.65	T2	5	T1		151	65	94	100
BP8-12	12 V	8	7.6	6.8	2.65	T2	5	T1		151	65	94	100
BP10-12	12 V	10	9.5	8.5	3.3	T2	5	T1		151	65	112	116
BP12-12	12 V	12	11.4	10.2	3.94	T2	5	T1		151	98	94	98
BP17-12	12 V	17	16.15	14.45	6.15	B1	7	T2 I1	6	181	76	166	166
BP20-12	12 V	20	19	17	6.35	B1	7	T2 I1	6	181	76	166	166
BP26-12	12 V	26	24.7	22.1	9.4	B1	7	T2 I1	9	175	166	125	125
BP28-12	12 V	28	26.6	23.8	9.6	B1	7	T2 I1	9	175	166	125	125
BP33-12 Standard Type	12 V	33	31.35	28.05	11.25	B7	8			195	129	155	179
BP33-12 Handle Type	12 V	33	31.35	28.05	11.25	B7	8	I2		210	129	168	179
BP33-12 Finger Type	12 V	33	31.35	28.05	11.25	B7	8	I2		195	129	168	179
BP35-12 Standard Type	12 V	35	33.25	29.75	11.45	B7	8			195	129	155	179
BP35-12 Handle Type	12 V	35	33.25	29.75	11.45	B7	8	I2		210	129	168	179
BP35-12 Finger Type	12 V	35	33.25	29.75	11.45	B7	8	I2		195	129	168	179
BP40-12	12 V	40	38	34	14.3	B2	7	I1 I2		197	165	171	171
BP65-12	12 V	65	61.75	55.25	22.4	B5	15	I2		350	166	174	174
BP90-12	12 V	90	85.5	76.5	30.8	B3	15	I2		329	172	215	238
BP100-12	12 V	100	95	85	32.7	B3	15	I2		329	172	215	238
BP120-12	12 V	120	114	102	39.5	B4	18	I2		407	173	210	239
BP160-12	12 V	160	152	136	51.2	B9	15	I3		483	171	240	240
BP200-12	12 V	200	190	170	61.5	B9	13	I3		522	202	216	240
BP230-12	12 V	230	218.5	195.5	72.5	B9	13	I3		522	240	216	240
BP13-6 H	6 V	13	12.35	11.05	2.5	H	11			108	71	140	140
BP7.2-12	12 V	7.2	6.84	6.12	2.35	T2	5	T1		151	65	93	98
BP4.5-12RT	12V	4.5	4.28	3.83	1.78	RT	12		16	140	48	102	104
BP5.5-12RT	12 V	5.5	5.23	4.68	1.85	RT	12		16	140	48	102	104
BP7-12RT	12 V	7	6.65	5.95	2.4	RT	12		16	140	48	126	128
BP5-6	6 V	5	4.75	4.25	0.905	T1	1	T2		70	48	102	107