

## EP SERIE

Model	Voltage	Capacity(Ah)			Weight Kg	Terminal		Terminal		L mm	W mm	H mm	TH mm
		20Hr	5Hr	30min		Standard	Position	Optional	Position				
EP7-12	12 V	7	5.95	3.5	2.6	T2	5	T1		151	65	93	98
EP12-12	12 V	12	10.2	6	4.2	T2	5	T1		151	98	94	98
EP17-12	12 V	17	14.45	8.5	6.2	B1	7	T2 I1	6	181	76	166	166
EP26-12	12 V	26	22.1	13	9.6	B1	7	T2 I1	9	175	166	125	125
EP28-12	12 V	28	23.8	14	9.7	B1	7	T2 I1		175	166	125	125
EP33-12 Standard Type	12 V	33	28.05	16.5	11.5	B7	8			195	129	155	179
EP33-12 Handle Typ	12 V	33	28.05	16.5	11.5	B7	8	I2		210	129	168	179
EP33-12 Finger Type	12 V	33	28.05	16.5	11.5	B7	8	I2		195	129	168	179
EP40-12	12 V	40	34	20	14.6	B2	7	I1 I2		197	165	171	171
EP65-12	12 V	65	55.25	32.5	25	B5	15	I2		350	166	174	174
EP80-12	12 V	80	68	40	31.2	B3	15	I2		329	172	215	238
EP100-12	12 V	100	85	50	40	B4	18	I2		407	173	210	239