

## BC SERIE

Model	Voltage	Capacity(Ah) 20Hr	Weight Kg	Terminal Standard	Terminal Optional	L mm	W mm	H mm	TH mm
BC4.5-6	6V	4.5	0.72	T1	T2	70	48	102	107
BC7-12	12 V	7	2.2	T2	T1	151	65	94	100
BC7.2-12	12 V	7.2	2.2	T2	T1	151	65	94	100
BC10-12	12 V	10	3	T2	T1	151	65	112	117
BC17-12	12 V	17	5.62	B1	T1	181	76	166	166
BC18-12	12 V	18	5.62	B1	T2	181	76	166	166
BC28-12	12 V	28	7.9	B1	T2	175	166	125	125
BC35-12F	12 V	35	9.6	B7	I2	195	129	168	179
BC35-12H	12 V	35	9.6	B7	I2	195	129	168	179
BC35-12 Standard	12 V	35	9.6	B7		195	129	155	179
BC42-12	12 V	42	12.2	B2	I1	197	165	171	171
BC65-12	12 V	65	20	B5	I1	350	166	174	174
BC75-12	12 V	75	20.2	B5	I2	350	166	174	174
BC100-12	12 V	100	28.5	B3	I2	329	172	215	238
BC120-12	12 V	120	35	B4	I2	407	173	210	239
BC160-12	12 V	160	45	B9	I3	483	171	240	240
BC200-12	12 V	200	55.2	B9	I3	522	202	216	240
BC230-12	12 V	230	62.4	B9	I3	522	240	216	240