
BIG ROUND PANEL LIGHT DATA SHEET



APPLICATION

Hotel, meeting room, office, school, art gallery, hospital etc.

PRODUCT OVERVIEW

Shape design: smart design,easy installation for both surface mouting and suspension mounting. Aluminum material,good heat dissipation function;

LED Light source: high brightness,stable performance,low lumen depreciation,long lifespan;

Optical design: unique anti-glare design,nice luminance uniformity,comfortable application;

Environment-friendly: free of mercury,lead and any other poisonous substances. This green product has no environment pollution,no UV,low glare,makes it a comfort and secure item for use;

PARAMETER

Model ID	MS-PLD500-50-XW	MS-PLD300-25-XW
Luminaire Classification	Class II	Class II
Input voltage	AC220-240V	AC220-240V
Frequency	50/60Hz	50/60Hz
Power	50W	25W
CRI	>80	>80
UGR	<19	<19
CCT	3000K/4000K/5000K	3000K/4000K/5000K
Lumen Efficiency	>100Lm/w	>100Lm/w
Total Lumen	>5000Lm	>2500Lm
Beam angle	115°	115°
Dimension	D500*H50mm	D300*H50mm
LED Diode	408pcs Mason 2835 LED Diode	204pcs Mason 2835 LED Diode
LED Lifespan	50,000 hours	50,000 hours
Driver Brand	CN driver brand	CN driver brand
IP Rating	IP20	IP20
Working temperature	-20 ~ 40 °C	-20 ~ 40 °C
Mounting	Suspension or Surface Mounting	Suspension or Surface Mounting
Warranty	2 years	2 years
Standard	CE &ROHS	CE &ROHS
Packing	1PC/CTN	1PC/CTN
	L575*W575*H125mm	L375*W375*H125mm
	Packing with logo is available	