Enabling higher accuracy for your SITE SURVEYING NEEDS

TO A					
100		III III	1		
				4675100	
			40	2700	
			200		
		ide B		Alb.	

	CenterPoint® RTX Use promocode FREE30 at 30daytrial.trimble.com	VRS Now [™]	
BENEFITS	High accuracy GNSS corrections available worldwide; ideal when working in remote locations across large geographic areas; no local base station or VRS network required	Instant access to real-time kinematic (RTK) corrections; no base station required	
DELIVERY	The or	<u></u>	
ACCURACY	Horizontal < 2 cm Vertical < 5 cm	Horizontal < 2 cm Vertical < 3 cm	
APPLICATIONS	Site positioning applications including: initial site topography, design review, site planning and layout, site clearing, estimation support and as-built surveys, rough staking and more	Site positioning and machine control	
COMPATIBLE DEVICES	Trimble: R750, R780, SPS986, MPS865, SPS855, SPS985, SPS585, SPS785 Spectra Geospatial: SP60, SP80, SP85, SP90M	CMRx, CMR+, RTCM v2.3, RTCM v3.1 or RTCM v3.2 MSM via NTRIP	
CONVERGENCE TIME ¹	< 1 min in Trimble RTX Fast coverage regions < 3 min² in Trimble RTX coverage regions	Instant	

^{1.} RMS performance based on repeatable in field measurements. Achievable accuracy and initialization time may vary based on type and capability of receiver and antenna, user's geographic location and atmospheric activity, scintillation levels, GNSS constellation health and availability and level of multipath including obstructions such as large trees and buildings.



^{2. &}lt; 3 min for ProPointTM capable receivers only. Global average initialization time when using GPS, GLÖNASS, Galileo, and BeiDou, available globally via IP and regionally via L-band.