

Applanix POS MV

WaveMaster II


Maximize your ROI with Applanix® POS MV WaveMaster II. WaveMaster II is a user-friendly, turnkey system designed and built to provide accurate attitude, heading, heave, position, and velocity data of your marine vessel and onboard sensors.

Applanix POS MV is proven in all conditions, and is the georeferencing and motion compensation solution of choice for the hydrographic professional.

POS MV blends GNSS data with angular rate and acceleration data from an IMU and heading from the GNSS Azimuth Measurement System (GAMS) to produce a robust and accurate full six degrees-of-freedom position and orientation solution.

Key Features

- Up to 0.02° roll and pitch performance
- IN-Fusion™ 2.0 ensures optimal GNSS aiding for any given conditions
- TrueHeave™ - no requirement to tune filter for specific conditions, no settling time so no run in time
- High accuracy inertial measurement units featuring SmartCal™
- Data time tagged to microsecond accuracy



Applanix POS MV

WaveMaster II

PERFORMANCE SUMMARY (APPLANIX POS MV WAVEMASTER II ACCURACY ¹⁾							
	DGNSS	FUGRO MARINESTAR®	IARTK	POSPac™ MMS PPP	POSPac MMS IAPPK	ACCURACY FOLLOWING 60 s GNSS OUTAGE	CENTERPOINT® RTX MARINE ⁸
Position	0.5 - 2 m ²	Horizontal: 10 cm 95% Vertical: 15 cm 95%	Horizontal: +/- (8 mm + 1 ppm x baseline length) ³ Vertical: +/- (15 mm + 1 ppm x baseline length) ³	Horizontal: < 0.1 m Vertical: < 0.2 m	Horizontal: +/- (8 mm + 1 ppm x baseline length) ³ Vertical: +/- (15 mm + 1 ppm x baseline length) ³	~ 9 m for 60 s outage(RTK) ~ 3 m for 30 s outages (RTK) ~ 2 m for 60 s outages (IAPPK)	Horizontal: 3 cm Vertical: 6 cm
Roll & Pitch ⁴	0.03°	0.02°	0.02°	< 0.02°	0.015°	0.04°	0.02°
Heading ⁴	0.015° with 4 m baseline 0.03° with 2 m baseline	0.015° with 4 m baseline 0.03° with 2 m baseline	0.015° with 4 m baseline 0.03° with 2 m baseline	0.015° with 4 m baseline 0.03° with 2 m baseline	0.015° with 4 m baseline 0.03° with 2 m baseline	< 2° per hour degradation (negligible for outages <60 s)	0.015° with 4 m baseline 0.03° with 2 m baseline
Heave TrueHeave	5 cm or 5% ⁵ 2 cm or 2% ⁶	5 cm or 5% ⁵ 2 cm or 2% ⁶	5 cm or 5% ⁵ 2 cm or 2% ⁶	-	-	5 cm or 5% ⁵ 2 cm or 2% ⁶	5 cm or 5% ⁵ 2 cm or 2% ⁶

PCS OPTIONS						
COMPONENT	DIMENSIONS	WEIGHT	TEMPERATURE	HUMIDITY	POWER	
Rack Mount PCS	L = 442 mm, W = 356 mm, H = 46 mm	3.9 kg	-20 °C to +70 °C	10 - 80% RH	AC 120/230 V, 50/60 Hz, auto-switching 40 W	
Small Form Factor PCS	L = 167 mm, W = 185 mm, H = 68 mm	2.5 kg	-20 °C to +60 °C	0- 100% RH	DC 10-34 V, 35 W (peak)	

INERTIAL MEASUREMENT UNIT (IMU)				
ENCLOSURE	DIMENSIONS	WEIGHT	TEMPERATURE	IP RATING
Between Decks	L = 158 mm, W = 158 mm, H = 124 mm	2.5 kg	-40 °C to +60 °C	IP65
Submersible	Ø100 mm (base plate Ø132 mm) X 104 mm ⁷	2.7 kg	-40 °C to +60 °C	IP68

GLOBAL NAVIGATION SATELLITE SYSTEM (GNSS)				
COMPONENT	DIMENSIONS	WEIGHT	TEMPERATURE	HUMIDITY
GNSS antenna (S40AP)	Ø178 mm, W = 73 mm	0.45 kg	-50 °C to +70 °C	0-100% RH
GNSS Antenna (GA830)	Ø149 mm, W = 99 mm	0.82 kg	-40 °C to +70 °C	0-100% RH

ETHERNET INPUT/OUTPUT

Ethernet.....(10/100 base-T)
Parameters Time tag, status, position, attitude, velocity, track and speed, dynamics, performance metrics, raw IMU data, raw GNSS data
Display Port Low rate (1 Hz) UDP protocol output
Control Port TCP/IP input for system commands
Primary Port Real-time (up to 200 Hz) TCP/IP protocol output
Secondary Port Buffered TCP/IP protocol output for data logging to external device

SERIAL RS232 INPUT OUTPUT

5 COM Ports..... User assignable to: NMEA output (0-5), Binary output (0-5), Auxiliary GNSS input (0-2), Base GNSS correction input (0-2)

NMEA ASCII OUTPUT

ParametersNMEA Standard ASCII messages: Position (\$INGGA), Heading (\$INHDT), Track and Speed (\$INVTG), Statistics (\$INGST) Attitude (\$PASHR, \$SPRID), Time and Date (\$INZDA, \$UTC)
Rate Up to 50 Hz (user selectable)
Configuration Output selections and rate individually configurable on each assigned com port

HIGH RATE ATTITUDE OUTPUT

ParameterUser selectable binary messages: attitude,heading, speed
Rate Up to 200 Hz (user selectable)
Configuration Output selections and rate individually configurable on each assigned com port

AUXILIARY GNSS INPUTS

Parameter NMEA Standard ASCII messages: \$GPGGA, \$GPGST, \$GPGSA, \$GPGSV
Uses Aux input with best quality
Rate 1 Hz

BASE GNSS CORRECTION INPUTS

Parameter RTCM V2.x, RTCM V3.x, CMR, CMR+, and CMRx input formats accepted.
Combined with raw GNSS observables in navigation solution
Rate 1 Hz

DIGITAL I/O

1PPS..... 1 pulse-per-second Time Sync output, normally high, active low pulse

USER SUPPLIED EQUIPMENT

- PC for POSView™ Software (Required for configuration): Pentium 90 processor(minimum), 256 MB RAM, 2 GB free disk space, Ethernet adapter (10/100 Base-T Ethernet; IEEE 802.3 standard), Windows 7 SP1, Windows 7 Embedded, Windows 8, and Windows 10
- PC for POSPac MMS Post-processing Software: Intel Pentium series 1Ghz or faster 64-bit processor (minimum), 2GB RAM, 2.6 GB free disk space, USB Port (For Security Key), Windows 7 SP1, Windows 8.1, Windows 10

- 1 One sigma unless otherwise stated
- 2 Depending on quality of differential corrections
- 3 Assumes 1 m IMU-GNSS antenna offset
- 4 No range limit
- 5 Whichever is greater, for periods of 20 seconds or less
- 6 Whichever is greater, for periods of 35 seconds or less
- 7 Height excludes connector
- 8 Real time Trimble Centerpoint® RTX Correction Service. Typical results, subject to regional coverage.

Specifications subject to change without notice.

APPLANIX

Canada:
85 Leek Crescent, Richmond
Hill,
ON Canada L4B 3B3
T+1-289-695-6000

United Kingdom:
Forester's House, Old
Racecourse, Oswestry UK SY10
7PW
T+44 1691 700500

USA:
15840 FM 529 Rd, Suite 316,
Houston, Texas, 77095
T+1.713.936.2990

