

# TRIMBLE AP+ 30 AIR

## Next Generation Embedded GNSS-Inertial Solution for Robust Airborne Positioning and Direct Georeferencing

Powerful enough for use on manned platforms yet small enough for use on unmanned aerial vehicles (uavs)

The Trimble® AP+ Air GNSS-inertial system is comprised of next-generation compact, low-power hardware, featuring dual embedded survey-grade GNSS chipsets, an onboard inertial measurement unit (IMU), an external IMU, and the all-new Applanix IN-Fusion+™ GNSS-aided inertial firmware.

### Integrate Once, Use Many

The “Integrate once, use many” concept means a single hardware platform can be used to build a complete range of mapping payloads, from UAV to manned aircraft, using the same design. This consistency saves costs associated with design and integration.


The Trimble AP+ Air is configurable to support the Direct Georeferencing accuracy demands of everything from low-flying UAVs to high-altitude manned platforms. Compatible with photogrammetric cameras, LiDAR, hyperspectral and multispectral cameras, Synthetic Aperture Radar and virtually any other type of airborne remote sensor, the Trimble AP+ Air is a powerful, compact, and versatile solution. Easily integrated with any type of platform, AP+ Air saves significant costs in all types of surveys.

### The Best Solution Just Got Better

The Trimble AP+ Air OEM solution is fully supported by the industry-leading Applanix POSPac™ MMS post-processing software, featuring Post-Processed Trimble CenterPoint® RTX™ for centimeter position accuracy without base stations, making it the ultimate solution for integrators wishing to produce a highly efficient airborne mapping system. For LiDAR integrators, the Trimble AP+ Air OEM is fully compatible with the POSPac MMS LiDAR QC Tools for UAV.

### Key Features

- “Integrate once, use many” concept means a single platform can be used to build a complete range of mapping payloads, from UAV to manned aircraft, using the same design, which saves costs
- Reduced SWaP
  - 54% smaller footprint,
  - 64% lighter, 75% less power
- Next generation, survey-grade GNSS receiver
- Dual inertial support (onboard and external) for simple gimbal mount support
- Two antenna heading support
- Next generation In-Fusion+ Aided-Inertial Firmware
- Completely configurable, from entry-level UAV applications, all the way up to high-accuracy solutions for high altitude LiDAR mapping



# TRIMBLE AP+ 30 AIR

## TECHNICAL SPECIFICATIONS

### System Summary

- Applanix IN-Fusion GNSS-inertial integration technology
- Onboard IMU with solid-state MEMS inertial sensors and Applanix SmartCal™ compensation technology
- High performance external IMU
- Advanced Trimble Maxwell™ Custom GNSS survey technology with 2 x 336 tracking channels
- Optional Dual Antenna, GAMS (GNSS Azimuth Measurement System) included
- Primary Antenna
  - GPS: L1 C/A, L2C, L2E, L5
  - GLONASS: L1 C/A, L2 C/A, L3 CDMA<sup>6</sup>
  - BeiDou: B1, B2, B3B<sup>7</sup>
  - Galileo: E1, E5A, E5B, E5AltBOC, E6<sup>6</sup>
  - IRNSS: L5
  - QZSS: L1 C/A, L1S, L1C, L2C, L5, LEX
  - SBAS: L1 C/A, L5
  - MSS L-Band: Trimble RTX
- Secondary Antenna:
  - GPS: L1 C/A, L2C, L2E, L5
  - GLONASS: L1 C/A, L2 C/A, L3 CDMA<sup>6</sup>
  - BeiDou: B1, B2, B3B<sup>7</sup>
  - Galileo: E1, E5A, E5B, E5AltBOC, E6<sup>6</sup>
  - IRNSS: L5
  - QZSS: L1 C/A, L1S, L1C, L2C, L5, LEX
  - SBAS: L1 C/A, L5
- High-precision multiple correlator for GNSS pseudorange measurements
- Unfiltered, unsmoothed pseudorange measurements data with low noise, low multipath error, low time domain and high dynamic response
- Very low noise GNSS carrier phase measurements with <1 mm precision in a 1 Hz bandwidth
- Proven Trimble low elevation tracking technology
- Real-time GNSS L1, SBAS positioning mode
- Real-time 100 Hz position, attitude output, dual IMU 200 Hz data rate logging
- Navigation output format: ASCII (NMEA-0183), binary (Trimble GSOF)
- RTK license support for Reference Inputs CMR, CMR+, sCMRx, RTCM 2.1, 2.2, 3.0, 3.1, 3.2, sold separately
- Supported by POSPac MMS
- No export permit required

### LAN INPUT/OUTPUT

All Ethernet functions are supported through dedicated IP address (static or DNS) simultaneously including web-based control GUI access and real-time data streaming

TCP/IP and UDP ..... ASCII and binary data streaming (time tag, PPS sync, status, position, attitude, velocity, track and speed, dynamics, performance metrics, GNSS data), configuration messages

HTTP ..... Web-based control software (GUI) for easy system configuration and low rate display. Support for all common browsers (IE, Safari, Mozilla, Google Chrome, Firefox)

### SERIAL INPUT/OUTPUT

RS232 ports (baud rates up to 460,800) ..... ASCII and binary data streaming (time tag, PPS sync, status, position, attitude, velocity, track and speed, dynamics, performance metrics, GNSS data), reference input (CMR, CMR+, sCMRx, RTCM), configuration messages

USB 2.0 Device Configuration ..... ASCII and binary data streaming (time tag, PPS sync, status, position, attitude, velocity, track and speed, dynamics, performance metrics, GNSS data), configuration messages

1 Typical performance. Actual results are dependent upon satellite configuration, atmospheric conditions and other environmental effects.  
 2 Typical mission profile, max RMS error (GAMS not required).  
 3 Real-time Trimble CenterPoint RTX correction service, typical airborne results, subject to regional coverage. Subscription sold separately, requires RTK license.  
 4 POSPac MMS, Single Base station or SmartBase.  
 5 POSPac MMS, Post-Processed CenterPoint RTX, typical mission performance subscription sold separately. The accuracy is subject to quality of GNSS, data set duration, and regional coverage.  
 6 There is no official GLONASS L3CDMA or Galileo E6 ICD. The current tracking capability is based on publicly available information. Full receiver compatibility cannot be guaranteed.  
 7 The hardware of this product is designed for BeiDou B3 compatibility (trial version) and its firmware will be enhanced to fully support such new signal as soon as officially published ICD becomes available.  
 8 Does not include external IMU.  
 9 Performance based upon external IMU.  
 10 Subject to regional coverage.

### OTHER INPUT/OUTPUT

PPS (pulse-per-second) Time synchronization  
 Event Input (2) ..... Two time marks for external events, TTL 3.3V, 50 Hz max rate  
 Digital I/O (3) ..... LED drivers with dedicated functionalities for system integrators  
 External IMU Interface ..... Dedicated signals for external IMU support

### LOGGING

Internal Logging ..... 6 GB flash memory  
 External Logging ..... USB 2.0 host configuration support for removable USB device  
 Parameters ..... Time tag, status, position, attitude, velocity, track and speed, dynamics, performance metrics, raw IMU data (200 Hz), raw GNSS data (5 Hz)

## PERFORMANCE SPECIFICATIONS

### Absolute Accuracy Specifications<sup>1-9</sup> (RMS)

AIRBORNE APPLICATION					
	SPS	SBAS <sup>10</sup>	RTX <sup>3</sup>	POST-PROCESSED-RTX <sup>5</sup>	POST-PROCESSED <sup>4</sup>
Position (m)	1.5 H 3 V	0.50 H 0.85 V	0.04 H 0.08 V	0.03 H 0.06 V	0.02 H 0.05 V
Velocity (m/s)	0.050	0.050	0.020	0.010	0.010
Roll & Pitch (deg)	0.020	0.015	0.010	0.010	0.010
True Heading <sup>2</sup> (deg)	0.100	0.080	0.050	0.025	0.025

### PHYSICAL CHARACTERISTICS

Size<sup>8</sup> ..... 100x60x21 mm  
 Weight<sup>8</sup> ..... 100 g  
 Power<sup>8</sup> ..... 7W max, 8-34V DC or 3.3V DC  
 Connectors ..... Samtec LSHM-140-03.0-L-DV-A-N  
 Antenna Port ..... 2 x MMCX receptacle  
 ..... Output Voltage: Primary 7.5 VDC  
 ..... Secondary 5 VDC  
 ..... Maximum Current: 400 mA  
 ..... Minimum Input Signal Strength: 32 dB (>35 dB recommended)

### ENVIRONMENTAL CHARACTERISTICS

Temperature ..... -40 °C to +75 °C (Operational)  
 ..... -55 °C to +85 °C (Storage)  
 GNSS Operating Limit ..... 515 m/sec, 18,000 m

### ADDITIONAL ACCESSORIES

Evaluation Kit ..... Includes development board, power supply, and short antenna cables (sold separately)

## INERTIAL MEASUREMENT UNITS (IMUS)

TYPE	RANGE	OPERATIONAL TEMPERATURE (°C)	POWER	SIZE [L x W x H] (mm)	WEIGHT (KG)
Internal Onboard IMU-79	+/-6 g +/-350 dps	-40 °C to +75 °C	n/a	n/a	n/a
External IMU-82	+/-10 g +/-490 dps	-40 °C to +85 °C	4.75 to 36 VDC 4W max	61 x 68 x 65	0.33
External IMU-93	+/-10 g +/-490 dps	-40 °C to +85 °C	4.75 to 28 VDC 3W max	50 x 50 x 50	0.18

Specifications subject to change without notice.

### TRIMBLE APPLANIX

**Canada:**  
 85 Leek Crescent, Richmond Hill,  
 ON Canada L4B 3B3  
 T+1-289-695-6000

