

## ABSOLUTE ROTARY ENCODER SSI



### Main Features

- Compact and heavy-duty industrial model
- Interface: Synchronous-serial (RS422/485)
- Housing: 58 mm Ø
- Shaft: 6 or 10 mm Ø
- Hollow Shaft: 12 mm Ø
- Resolution: Max. 25 Bit = 33,554,432 steps over 4,096 revolutions
- Code: Gray
- EMC: EN 50 081-2, EN 61000-6-2, CE

### Mechanical Structure

- Flange and housing of Aluminum
- Shaft of stainless steel
- Precision ball bearings with sealing or cover rings
- Code disc made of unbreakable and durable plastic

### Applications

- Sensing of
- Angles
- Distances
- Tracks
- Inclinations
- Differences between two or more axes

### Electrical Features

- Temperature insensitive IR-opto-receiver-array
- Only one IR-transmitter-diode per opto-Array
- Highly integrated circuit in SMD -technology
- Polarity inversion protection
- Over-voltage-peak protection

### ABSOLUTE ROTARY ENCODER SSI

#### Technical Data

##### Electrical Data

Clock input	Via opto-coupler
Data input	Line-driver according to RS 485 / RS 422
Clock frequency	100 kHz - 1 MHz
Step frequency LSB	Max. 100 kHz (valid code)
Accuracy of division	$\pm \frac{1}{2}$ LSB
EMC	Certified according to EN 50 081-2, EN 61000-6-2
Supply voltage	10-30 V DC (absolute limits)
Current consumption	~180 mA
Electrical lifetime	$> 10^5$ h
Connection	Connector or cable, 1 meter long

##### Mechanical Data

Housing	Aluminum, optional stainless steel		
Lifetime	$F_a \leq 250$ N, $F_r \leq 250$ N: $1 \cdot 10^8$ revolutions		
	$F_a \leq 40$ N, $F_r \leq 110$ N: $3 \cdot 10^9$ revolutions		
Inertia of rotor	$\approx 50$ gcm <sup>2</sup>		
RPM	Max. 6,000 (continuously)		
Shock (EN 60068-2-27)	$\leq 30$ g (halfsine, 11 ms)		
Permanent shock (EN 60028-2-29)	$\leq 10$ g (halfsine, 16 ms)		
Vibration (EN 60068-2-6)	$\leq 10$ g (10 Hz ... 1,000 Hz)		
Weight, Singleturn / Multiturn	$\approx 500$ g / $\approx 700$ g		
Friction torque	$\leq 5$ Ncm		
<b>Flange</b>	<b>Synchro (Y)</b>	<b>Clamp (F), Synchro (Z)</b>	<b>Hollow shaft (H)</b>
Shaft diameter	6 mm	10 mm	12 mm
Shaft length	10 mm	20 mm	
Hollow Shaft depth min. / max.			15 / 30 mm

##### Environmental Conditions

Operating temperature	- 30 ... + 70 °C
Storage temperature	- 40 ... + 85 °C
Humidity	98 % (without liquid state)
Protection Class (EN 60529)	
Casing side	IP 65
Shaft side	IP 65 up to 0.5 bar


### ABSOLUTE ROTARY ENCODER SSI

#### Interface

##### Synchron-Serielles Interface (SSI)

Driver	Driver meets EIA standard RS 485 / RS 422; transmission rates up to 10 MBit/s
Transfer	Transfer distance up to 1,200 m
Transmission	Balanced transmission provides high noise immunity
Pair lines	Shielded and twisted pair lines are essential to attain extremely high noise immunity
Interface	For a detailed description of the synchronous-serial interface (SSI) refer to introduction section.
Optional	Built-in RS 485 / RS 422 interface for bus mode (strobe-function) Up to 32 encoders (AWC) can be used on the same data line !

#### Single Shift



$$t_p < 20\mu s \quad t_m > 20\mu s \quad t < t_m$$


### ABSOLUTE ROTARY ENCODER SSI

#### Electrical Interface

	12 pin circular plug Pin	open cable
Clock -	1	green
Clock +	2	yellow
Data +	3	brown
Data -	4	white
Complement	8	pink
+ U <sub>b</sub> = 10-30 V	11	white *
GND	12	brown *
Shield	-	Shielding

\* 0.5 mm<sup>2</sup>

#### Pinning AWC (Male)



COMPLEMENT-Input		Encoder counting direction at clockwise rotation (as seen on shaft)
Function	Level	
Direction of rotation	0 (Input to GND)	Up
	1 (Input to + U <sub>b</sub> or ≥ 8 V)	Down

### ABSOLUTE ROTARY ENCODER SSI


#### Mechanical Drawings

##### Synchro Flange (Y,Z)


The only difference between the Y- and Z-Flange is the shaft size (refer to the table besides).

	d [mm]	l [mm]
Y-Flange	6 <sub>f6</sub>	10
Z-Flange	10 <sub>h8</sub>	20

Cable Exit (cable diameter = 8mm or 0.315")



12 pin circular connector (cable outlet: 6-9mm = 0.236-0.354")




### ABSOLUTE ROTARY ENCODER SSI


#### Mechanical Drawings

##### Clamp Flange (F)

Cable Exit (cable diameter = 8mm or 0.315")




12 pin circular connector (cable outlet: 6-9mm = 0.236-0.354")



## ABSOLUTE ROTARY ENCODER SSI

### Hollow Shaft (H)



### Mounting instructions

The clamp ring may only be tightened if the shaft of the driving element is in the hollow shaft.

The diameter of the hollow shaft can be reduced to 10 mm or 8 mm by using an adapter (this reducing adapter can be pushed into the hollow shaft).

Allowed shaft movements of the drive element are listed in the table.

	axial	radial
static	± 0.3 mm	± 0.5 mm
dynamic	± 0.1 mm	± 0.2 mm

### ABSOLUTE ROTARY ENCODER SSI

#### Models / Ordering Description

Description	Type Key								
Absolute rotary encoder	<b>AWC 58.</b>	.....	-	.....	-	.	G	0	. SL . . . .
Diameter in mm									
Steps per revolution	360*	36/1							
	3600*	36/10							
	1024	10							
	4096	<b>12</b>							
	8192	13							
No. of revolutions	1	<b>1</b>							
	16	16							
	256	256							
	4096	<b>4096</b>							
Flange	Clamp (shaft = 10 mm)					<b>F</b>			
	Synchro (shaft = 6 mm)					<b>Y</b>			
	Synchro (shaft = 10 mm)					<b>Z</b>			
	Hollow shaft = 12 mm					<b>H</b>			
Code	Gray					<b>G</b>			
Latch-function	Without (integrated in SSI)					<b>0</b>			
Strobe-function	Without						<b>0</b>		
	With						<b>S</b>		
Interface	Synchronous-serial acc. to RS422/RS485							<b>SL</b>	
Options	Without							<b>0</b>	
	Shaft sealing (not possible for Z-Flange)							<b>W</b>	
	Stainless steel configuration (flange, housing, cap)							<b>Q</b>	
Connection	Connector, axial								<b>1KG</b>
	Connector, radial								<b>1KW</b>
	Cable, axial (1m)								<b>00A</b>
	Cable, radial (1m) <sup>+</sup>								<b>00R</b>

Further models on request

\* only for Single-Turn configuration, <sup>+</sup> not available in stainless steel configuration

#### Accessories

Description	Type
Connector, counterpart	Circular connector, 12 pins 1KG
Shaft coupling **	Drilling: 10 mm GS 10
	Drilling: 6 mm GS 06
Clamp disc **	4 pcs. / AWC SP 15
Clamp ring **	2 pcs. / AWC SP H

\*\* not used for hollow shaft

We do not assume responsibility for technical inaccuracies or omissions. Specifications are subject to change without notice.