



ELECTRIC VEHICLE SAFETY PRODUCTS

FIRE BLANKET

Applications: Parking Lots, Auto Repair Shops, Firefighters, Parking Structures, Charging Stations, Service Stations, Dealerships, etc



BENEFITS

- Limits damage and spread of fire to nearby areas
- Use on any passenger vehicle including internal combustion vehicles and electric vehicles
- Contains toxic smoke derived from combustion
- Contains thick smoke for better visibility
- Deploy in under a minute with only two people

Available Sizes

- 12' x 21' - Utility
- 20' x 20' - Sedan
- 20' x 25' - SUV
- 25' x 30' - Pickup Truck

*custom sizes available upon request



Max Use Temperature 2,300°F

Tear Strength Method: FTMS191A/M5136.
 Warp: 35 lbs. min. avg.
 Fill: 25 lbs. min. avg.
 Flame Resistance: Method FTMS 191A/M5903.
 Flame Out: 1 second.
 Afterglow: 3.0 seconds.
 Char Length: 0.
 Burst Strength Method: FTMS 191A/M5122 (Mullen), 175 lbs. in. min. avg.
 Hydrostatic Resistance Method: FTMS191A/M5512 (Mullen), 200 lbs. in. min. avg.

Base cloth Content/Weave	100% E-Fiberglass Yarn/Satin
Fabric Finish	Grey Silicone coated/impregnated
Weight	17oz/yd ² +/-10%
Thickness	0.015 [±] /-10%

Packaged in PVC storage bag

MADE IN THE USA



OEL Worldwide Industries

Physical: 701 County Line Road Palmer Lake, CO 80133

Mailing PO Box 445 Palmer Lake, CO 80133

oelsales.com | 800.818.2244