

ImagePerfect™ 2129 Frontlit Banner is a premium coated banner with excellent thermal welding characteristics and printability. This product has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks, as well as UV-cured and latex inks (including 3rd generation).

IP 2129

ImagePerfect™ 2129 is a top-quality banner material which offers a flexible and soft handle while still containing an extremely strong fabric. It can be used for indoor and outdoor applications such as billboards at trade shows and events, construction sites, show rooms, promotional campaigns and many other applications. IP 2129 delivers high print quality with remarkable text definition and a large colour gamut to ensure colourful images and vibrant in-fills. Thermal welding allows for a strong seam, as does the use of ImagePerfect™ Seam Tack Tape. Laminate: ImagePerfect™ water-based liquid laminate with UV protection.

Specifications	
DESCRIPTION	Frontlit banner
COLOUR	White satin
THICKNESS	410μ
WEIGHT	450g/m ²
TENSILE STRENGTH	2400 / 1900 (N / 5cm)
TEAR RESISTENCE	240 / 200 (N/5cm)
TEMPERATURE RANGE	-20°C to +70°C
DURABILITY (UNPRINTED)	5 years
FLAME RETARDANCY	B1
SHELF LIFE	N/A
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© August 2019 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for its specific use. All technical data are subject to change.

The durability is based on mid European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the graphics. For instance, exterior performance will be decreased in the case of signs facing south, in areas of long high temperature exposure such as southern European countries, in industrially polluted areas or in areas of high altitude. Also, for horizontal applications, exterior performance will decrease.

The print media should be completely dry before further processing, such as cutting, laminating, varnishing or application, or the residual solvents can otherwise change the specific features of the product. To ensure the best possible outcome, the match-component ImagePerfect™ profile should be used with the relevant ImagePerfect™ media.