

Die folgenden Schnittstellenspezifikationen gelten für die Produkte der:

- Deutsche Glasfaser Business GmbH
- Deutsche Glasfaser Wholesale GmbH

Ansprechpartner: Schnittstellenspezifikation@deutsche-glasfaser.de

1 Passive optische Schnittstelle am Hausübergabepunkt (HÜP)

Optisches Interface:

- Connector: LC/APC
- Patchkabel: ITU-T G.657
- Interface: 1000BASEBX10-U
 - TX Wellenlänge: 1310 nm
 - TX Wellenlänge range: 1260 – 1360 nm
 - TX Pegel: -3 – -9 dBm
 - RX Wellenlänge: 1490 nm
 - RX Wellenlänge range: 1480 – 1500 nm
 - RX Pegel: -3 – -19.5 dBm
 - Laser Class: 1 (IEC 60825-1)

2 Passive optische Schnittstelle an der Teilnehmeranschlussdose (GF-TA)

Abhängig von der Anschlussadresse:

- Connector: LC/APC
- TX Wellenlänge: 1310
- TX Wellenlänge range: 1260 – 1360
- TX Pegel: -3 – -9 dBm
- RX Wellenlänge: 1490
- RX Wellenlänge range: 1480 – 1500 nm
- RX Pegel: -3 – -19.5 dBm

3 Optical/ Electrical converter

- Compliant with 1000BASE-BX10-U, 10 km range
- Single mode fiber (ITU-T G.657),
- SC/APC connector,
- Managed Quality of Service,
- Remote port enabling/disabling,
- Remote per-port rate shaping and limiting,
- min 64 VLANs,
- Flow control setting
- min 4 1000/100/10Base-T RJ45 Interfaces
- CE approved, Safety: – IEC EN 60950 – IEC EN 60825-1:2001-08,
- Laser safety – IEC EN 60825-1: Class 1 laser product,
- Emission: EN 55022, Class B, EN 55024,
- RoHS/WEEE marking: Compliant with 2002/95/EC
- Full TR-069 Management enabled and support,
- Genexis GAPS (7.0 and higher) compatible,
- CLI DHCP/TFTP,
- IEEE 802.3ah OAM in passive mode:
 - Discovery – Loopback –
 - Fault notification (dying gasp)

4 Router

WAN interface

- Option for:
 - 1000/100/10Base-T RJ-45 port
 - SFP (fixed fiber) interface (Compliant with 1000BASE-BX10-U)
 - Combo port (RJ-45 + SFP interface)
- VLAN per service triple play
- DHCP client
- PPPoE client
- IPv4/IPv6 dual stack
- IPv6 6rd
- MAP E/T

LAN interface

- 4 1000/100/10Base-T LAN ports (RJ-45)

Routing

- Line-speed (1000 Mbps) routing
- performance for packets > 256 byte.
- DHCP server
- NAT/PAT
- UPnP
- VPN pass-through
- SPI Firewall
- DMZ
- Mixed bridged/routed port(s) for IPTV
- IGMPv2, IGMPv3 snooping and proxy

Voice

- SIP based Voice-over-IP
- G.711 A-law/μ-law codec
- 5 REN support
- Line Echo Cancellation
- DTMF transmission: In-band, RFC2833,
- SIP-Info
- Class 5 features

IEEE 802.11n/ac wireless interface

- IEEE 802.11b/g/n (2.4 and 5.0 GHz) 2T2R
- IEEE 802.11ac (5.0 GHz)
- Automatic channel selection
- Internal antennae
- WEP, WPA, WPA2
- WPS button for simple WLAN network setup
- Multiple SSIDs supported

Management and control

- TR-069, TR-098, TR-104
- Genexis Automatic Provisioning System (GAPS) compatible
- SNMP
- DHCP/TFTP
- CLI
- Fail-safe firmware upgrade
- Factory default reset button