

MasterShield PEL 355 (formerly MasterProtect 355)

Version Revision Date: SDS Number: Date of last issue: -

000000264830 1.0 08.02.2023 Date of first issue: 08.02.2023

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name MasterShield PEL 355 (formerly MasterProtect 355)

000000000050267638 Product code

Manufacturer or supplier's details

Company MB Solutions Australia Pty Ltd

11 Stanton Road, Seven Hills Address

NSW 2147

+611300227300 Telephone

Emergency telephone : ChemTel: +1-813-248-0585; Australia: 1-300-954-583

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Aspiration hazard Category 1

Flammable liquids Category 3

Acute toxicity (Inhalation -

vapour)

Category 4

Acute toxicity (Oral) Category 4

Acute toxicity (Dermal) Category 4

Skin irritation Category 2

Eye irritation Category 2A

Skin sensitization Category 1

Hazardous to the aquatic

environment - acute hazard

Category 2

Hazardous to the aquatic

environment - chronic hazard

Category 2

GHS label elements

Hazard pictograms









MasterShield PEL 355 (formerly MasterProtect 355)

Version Revision Date: SDS Number: Date of last issue: -

1.0 08.02.2023 000000264830 Date of first issue: 08.02.2023

Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H312 Harmful in contact with skin.

H332 Harmful if inhaled. H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H304 May be fatal if swallowed and enters airways.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P271 Use only outdoors or in a well-ventilated area.

P260 Do not breathe dusts or mists.

P273 Avoid release to the environment.

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P243 Take action to prevent static discharges.

P241 Use explosion-proof electrical/ventilating/lighting/.?/

equipment.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P264 Wash face, hands and any exposed skin thoroughly after

handling.

P270 Do not eat, drink or smoke when using this product.

P233 Keep container tightly closed.

P242 Use only non-sparking tools.

P240 Ground and bond container and receiving equipment.

Response:

P312 Call a POISON CENTER/ doctor/ .?/ if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor/ .?.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P361 + P364 Take off immediately all contaminated clothing and wash it before reuse.

Rinse mouth.

P332 + P313 If skin irritation occurs: Get medical advice/ atten-

tion.

P391 Collect spillage.

P337 + P313 If eye irritation persists: Get medical advice/ at-



MasterShield PEL 355 (formerly MasterProtect 355)

Version Revision Date: SDS Number: Date of last issue: -

1.0 08.02.2023 000000264830 Date of first issue: 08.02.2023

tention.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use water spray, alcohol-resistant

foam, dry chemical or carbon dioxide to extinguish.

Storage:

P405 Store locked up.

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/container to appropriate hazardous

waste collection point.

Other hazards which do not result in classification

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : organic solvents

Components

Chemical name	CAS-No.	Concentration (% w/w)
turpentine oil	8006-64-2	>= 50 -<= 100

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

Remove contaminated clothing.

If inhaled : Remove the affected individual into fresh air and keep the

person calm.

If breathing difficulties develop, aid in breathing and seek im-

mediate medical attention.

In case of skin contact : Wash thoroughly with soap and water

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Wash affected eyes for at least 15 minutes under running

water with eyelids held open, consult an eye specialist.

If swallowed : Rinse mouth and then drink 200-300 ml of water.

Do not induce vomiting due to aspiration hazard.

Do not induce vomiting unless told to by a poison control cen-

ter or doctor.

Most important symptoms

and effects, both acute and

delayed

Harmful if swallowed, in contact with skin or if inhaled.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.



MasterShield PEL 355 (formerly MasterProtect 355)

Version Revision Date: SDS Number: Date of last issue: -

1.0 08.02.2023 000000264830 Date of first issue: 08.02.2023

Notes to physician Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Dry powder

Alcohol-resistant foam

Unsuitable extinguishing

media

water jet

Hazardous combustion prod-

ucts

harmful vapours nitrogen oxides

fumes/smoke carbon black carbon oxides

Specific extinguishing meth-

ods

The degree of risk is governed by the burning substance and

the fire conditions.

Containers may rocket or explode in heat of fire.

Keep containers cool by spraying with water if exposed to fire. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

for fire-fighters

Special protective equipment : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective clothing.

Avoid prolonged inhalation.

Avoid contact with the skin, eyes and clothing.

Avoid all sources of ignition: heat, sparks, open flame.

Environmental precautions Prevent spread over a wide area (e.g. by containment or oil

barriers).

Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for

containment and cleaning up

Pick up with suitable appliance and dispose of.

Dispose of absorbed material in accordance with regulations.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Sources of ignition should be kept well clear.

Take precautionary measures against static discharges. Substance/product can form explosive mixture with air. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of igni-



MasterShield PEL 355 (formerly MasterProtect 355)

Version Revision Date: SDS Number: Date of last issue: -

1.0 08.02.2023 000000264830 Date of first issue: 08.02.2023

tion.

Advice on safe handling : Take precautionary measures against static discharges.

Keep away from sources of ignition - No smoking.

Provide good room ventilation even at ground level (vapours

are heavier than air).

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at the

end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

Further information on stor-

age conditions

Keep container tightly closed and in a well-ventilated place.

Keep away from heat.

Avoid all sources of ignition: heat, sparks, open flame.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis		
turpentine oil	8006-64-2	TWA	100 ppm 557 mg/m3	AU OEL		
	Further inform	Further information: Sensitiser				
		TWA value	20 ppm	ACGIHTLV		
		TWA value	100 ppm 557 mg/m3	AU NOEL		
		TWA value	100 ppm 557 mg/m3	OEL (AU)		
		TWA	20 ppm	ACGIH		

Personal protective equipment

Respiratory protection : Respiratory protection in case of vapour/aerosol release.

Suitable respiratory protection for higher concentrations or

long-term effect:

Gas filter for gases/vapours of organic compounds (boiling

point <65 °C, f.e. EN 14387 Type AX)

Hand protection

Remarks : Suitable chemical resistant safety gloves (EN 374) also with

prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) etc. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Tightly fitting safety goggles (splash goggles) (e.g. EN 166)



MasterShield PEL 355 (formerly MasterProtect 355)

Version Revision Date: SDS Number: Date of last issue: -

1.0 08.02.2023 000000264830 Date of first issue: 08.02.2023

Skin and body protection : Body protection must be chosen based on level of activity

and exposure.
Antistatic apron

Protective measures : Avoid inhalation of dusts/mists/vapours.

Avoid contact with the skin, eyes and clothing.

Avoid prolonged and/or repeated contact with the skin. Handle in accordance with good building materials hygiene

and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : colourless to yellowish

Odor : characteristic

pH : Not applicable

boiling temperature : > 149 °C

Flash point : approx. 35 °C

Flammability (solid, gas) : Flammable.

Upper explosion limit / Upper

flammability limit

approx. 7,5 %(V)

Lower explosion limit / Lower

flammability limit

approx. 1 %(V)

Vapor pressure : No data available

Density : approx. 0,8 g/cm3 (20 °C)

Bulk density : Not applicable

Solubility(ies)

Water solubility : insoluble (20 °C)

Autoignition temperature : No data available

Decomposition temperature : Vapors may form explosive mixture with air.

No decomposition if stored and handled as pre-

scribed/indicated.



MasterShield PEL 355 (formerly MasterProtect 355)

Version Revision Date: SDS Number: Date of last issue: -

1.0 08.02.2023 000000264830 Date of first issue: 08.02.2023

Explosive properties : Not explosive

Not explosive

Oxidizing properties : not fire-propagating

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac- :

tions

No hazardous reactions if stored and handled as pre-

scribed/indicated.

Conditions to avoid : Avoid heat.

Avoid open flames.
Avoid sources of ignition.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed, in contact with skin or if inhaled.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.



MasterShield PEL 355 (formerly MasterProtect 355)

Version Revision Date: SDS Number: Date of last issue: -

1.0 08.02.2023 000000264830 Date of first issue: 08.02.2023

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May also damage the lung at swallowing (aspiration hazard).

Further information

Product:

Remarks : The product has not been tested. The statement has been

derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.



MasterShield PEL 355 (formerly MasterProtect 355)

Version Revision Date: SDS Number: Date of last issue: -

1.0 08.02.2023 000000264830 Date of first issue: 08.02.2023

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Observe national and local legal requirements.

The waste code in accordance with the European waste catalog (EWC) must be specified in cooperation with disposal

agency/manufacturer/authorities.

Residues should be disposed of in the same manner as the

substance/product.

Contaminated packaging : Contaminated packaging should be emptied as far as possi-

ble; then it can be passed on for recycling after being thor-

oughly cleaned.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1993

Proper shipping name : Flammable liquid, n.o.s.

(HYDROCARBONS)

Class : 3 Packing group : III

Labels : Flammable Liquids

Packing instruction (cargo : 366

aircraft)

Packing instruction (passen-

acking instruction (pe

355

ger aircraft)

IMDG-Code

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

(HYDROCARBONS)

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

ASIA_ROAD

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

(HYDROCARBONS)

Class : 3
Packing group : III
Labels : 3
Hazchem Code : •3Y



MasterShield PEL 355 (formerly MasterProtect 355)

Version Revision Date: SDS Number: Date of last issue: -

1.0 08.02.2023 000000264830 Date of first issue: 08.02.2023

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mix-

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP): Schedule 5

The ingredients of this product are reported in the following inventories:

AIIC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date : 08.02.2023

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

AU NOEL : National Workplace OELs, Workplace Exposure Standards for

Airborne Contaminants (Australia)

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

OEL (AU) : Adopted National Exposure Standards for Atmospheric Con-

taminants in the Occupational Environment (Australia)

ACGIH / TWA : 8-hour, time-weighted average ACGIHTLV / TWA value : Time Weighted Average (TWA): AU NOEL / TWA value : Time Weighted Average (TWA):

AU OEL / TWA : Exposure standard - time weighted average

OEL (AU) / TWA value : Time Weighted Average (TWA):

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Con-



MasterShield PEL 355 (formerly MasterProtect 355)

Version Revision Date: SDS Number: Date of last issue: -

1.0 08.02.2023 000000264830 Date of first issue: 08.02.2023

centration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN