

03 30 00	Cast-in-Place Concrete
03 40 00	Precast Concrete
03 70 00	Mass Concrete
31 00 00	Earthwork

MasterLife[®] 300L

MasterLife 300L Red Version

(MasterLife 300L admixture combined with MasterColor Medium Red admixture)
Liquid Crystalline Waterproofing Admixtures

Description

MasterLife 300L is a liquid crystalline capillary waterproofing admixture for concrete. It is designed for use in above- and below-grade applications. MasterLife 300L admixture will meet ASTM C494/C494M requirements for Type S, Specific Performance, admixtures.

Applications

Recommended for use in:

- Tinted concrete for precast elements
- Foundations
- Sewage and water treatment plants
- Water tanks and reservoirs
- Swimming pools
- Underground vaults
- Tunnels and subway systems
- Secondary containment structures
- Below-grade parking structures
- Precast components
- Water features
- Geotechnical grouting and ground improvement

Features

- Unique liquid crystalline formulation
- Automated dispenser / integral addition

Benefits

- Reduces concrete permeability
- Reduces penetration of water and other liquids
- Resists positive and negative side hydrostatic pressure
- Protects against sewage and industrial waste
- Seal hairline cracks
- Allows concrete to breathe
- Accurate dosing and addition verification with batch ticket printout
- Enhanced safety during batching
- No packaging waste or disposal cost

Performance Characteristics

Slump and Setting Time: The MasterLife 300L admixture has little to no effect on concrete slump or setting time at the recommended dosage.

Hardened Properties: Depending on the ingredients and proportions of a concrete mixture, a decrease in compressive strength may be experienced with MasterLife 300L admixture, typically in the range of 5 to 10 percent. Please consult your local sales representative for recommended concrete mixture adjustments prior to the use of MasterLife 300L admixture.

Typical Data for MasterLife 300L Admixture @ 1.25 gal/yd³ [6.2 L/m³]

Performance characteristic	Test method	Performance relative to untreated concrete mixture
Water Permeability	CRD-C 48	74% reduction
Water Penetration	DIN 1048	33% reduction
Capillary Absorption	ASTM C 1585	40% reduction

Guidelines for Use

Concrete Quality: Crystalline capillary waterproofing admixtures such as the MasterLife 300 series of admixtures are categorized as Permeability-Reducing Admixtures (PRAs) in ACI 212.3R-16, Report on Chemical Admixtures for Concrete. These admixtures "are intended to be used in, and complement, well-proportioned concrete mixtures, not to compensate for poorly proportioned concrete mixtures. Although recommendations differ from each manufacturer, a w/cm of 0.45 or less is typical for concrete designed to resist water movement." In accordance with the recommendations provided in ACI 318, ACI 350 and ACI 212.3R, Master Builders Solutions recommends the use of the MasterLife 300 series of admixtures in good quality concrete with a maximum water-cementitious materials ratio of 0.45 and a minimum compressive strength of 4000 psi (28 MPa). The MasterLife 300 series of admixtures meet the requirements for PRAs for concrete exposed to hydrostatic conditions (PRAH), as defined in ACI 212.3R-16. Master Builders Solutions recommends adherence to the following guidelines provided in ACI 212.3R-16 when the MasterLife 300 series of admixtures are used: "If the PRAH forms part of a primary waterproofing system, consider crack control measures (control joints), the admixture's crack sealing abilities, treatment of construction joints, and compatible repair systems. Also consider using concrete with the lowest drying shrinkage possible."

Dosage: MasterLife 300L admixture is recommended for use at a dosage of 1.25 gal/yd³ (6.2 L/m³).

Dispensing and Mixing: Mixture Proportions: The mix water content should be reduced by 1.25 gal/yd³ [6.2 L/m³] to account for the quantity of MasterLife 300L admixture used. MasterLife 300L admixture may be added to the concrete mixture during the initial batch sequence at the production plant or at the jobsite. If the delayed addition method is used, mixing at high speed for 3–5 minutes after the addition of MasterLife 300L admixture will result in mixture uniformity.

Product Notes

Corrosivity – Non-Chloride, Non-Corrosive: MasterLife 300L admixture will neither initiate nor promote corrosion of reinforcing steel, prestressing steel or of galvanized steel floor and roof systems. Neither calcium chloride nor other chloride-based ingredients are used in the manufacture of MasterLife 300L admixture.

Compatibility: MasterLife 300L admixture is compatible with most admixtures used in the production of quality concrete, including normal, mid-range and high-range water-reducers, retarders, accelerators and corrosion inhibitors. For air-entrained concrete applications, MasterLife 300L admixture can be used with MasterAir® AE 200, MasterAir AE VR10 and MasterAir AE 90 air-entraining admixtures. The dosage of air-entraining admixture should be established through truck trial evaluations.

Tinted Concrete: MasterLife 300L admixture can be used in combination with a coloring admixture, such as MasterColor Medium Red liquid admixture, to produce tinted concrete.

Packaging

MasterLife 300L admixture is available in 265 gal (1003 L) totes and by bulk delivery.

Storage and Handling

Storage Temperature: MasterLife 300L admixture should be stored at ambient temperatures above 40 °F (5 °C), and precautions should be taken to protect the admixture from freezing. If MasterLife 300L admixture freezes, thaw and reconstitute by mild mechanical agitation. Do not use pressurized air for agitation.

Shelf Life

MasterLife 300L admixture has a minimum shelf life of 12 months when stored under recommended conditions. Depending on storage conditions, the shelf life may be greater than stated. Please contact your local sales representative regarding suitability for use if the shelf life of MasterLife 300L admixture has been exceeded.

Related Documents

Safety Data Sheet: MasterLife 300L admixture

Additional Information

For additional information on MasterLife 300L admixture, or its use in developing a concrete mixture with special performance characteristics, contact your local sales representative.

Master Builders Solutions creates technologies for the construction industry inspiring people to build better. We are active in ~40 countries and operate 35 production sites with over 1,600 employees. We develop, produce, and market high-quality chemical admixtures, as well as adjacent core technologies, to master the challenges of today and support a decarbonized future. Our people are pivotal and pair leading technologies and a strong brand heritage to surpass our customers' expectations and drive continuous value creation.

Limited Warranty Notice

Master Builders Solutions warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS SOLUTIONS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders Solutions. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS SOLUTIONS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders Solutions' present knowledge and experience. However, Master Builders Solutions assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders Solutions reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

