

03 37 13	Shotcrete
31 32 33	Shotcrete Soil Slope Stabilization
31 33 33	Shotcrete Rock Slope Stabilization
31 74 19	Shotcrete Tunnel Lining

MasterRoc[®] SA 430

Liquid High-Performance Sprayed Concrete Accelerator for Wet-Mix Spraying

Description

MasterRoc SA 430 admixture is a high-performance shotcrete accelerator used mainly in the wet spraying process, but can also be used in the dry spraying process. MasterRoc SA 430 admixture is a liquid whose dosage can be varied to the desired setting and hardening times.

Applications

Recommended for use in:

- Tunnelling and mining
- Temporary support
- Permanent support
- Final lining
- Slope stabilization
- Repairs of concrete structures

Features

- Faster setting and higher early strengths
- Low consumption
- Easy to mix into the concrete, even at low temperatures
- Low viscosity

Benefits

- Produces quality shotcrete
- Improves adhesion and surface bond
- Higher ultimate strengths and more durable shotcrete compared with traditional accelerators
- Increased layer thickness possible

Performance Characteristics

Technical Data

Form	Liquid
Color	Transparent
Density (@ 68 °F/20 °C)	1.36 (nominal)
pH	< 11.5
Viscosity (@ 68 °F/20 °C)	30 to 70 cP (mPa.s)
Solubility in water	Total
Thermal Stability	40 °F (5 °C)
Chloride content	< 0.1 %

Guidelines for Use

Dosage: The dosage range of MasterRoc SA 430 admixture is 3 to 8 % by mass of cementitious material for most shotcrete. However, variations in the job conditions, concrete and mortar materials may require amounts outside of the normal dosage range. In such cases, contact your local sales representative for assistance. Precautions should be taken as overdosing can cause a reduction of ultimate strength.

MasterRoc SA 430 admixture is introduced with a proportioning pump into the compressed air which is added at the nozzle.

Storage and Handling

Storage Temperature: Minimum storage temperature for MasterRoc SA 430 admixture is 40 °F (4 °C). Maximum storage temperature is 140 °F (60 °C). If MasterRoc SA 430 admixture freezes, thaw at 68 °F (20 °C) or above and completely reconstitute with mild mechanical agitation. If freezing has occurred, performance tests should be carried out prior to its use. **Do not use pressurized air for agitation.**

Shelf Life: MasterRoc SA 430 admixture has a minimum shelf life of 12 months if stored in original tightly secured containers. Depending on storage conditions, the shelf life may be greater than stated. Please contact your local sales representative regarding suitability for use and dosage recommendations if the shelf life of MasterRoc SA 430 admixture has been exceeded.

Safety: MasterRoc SA 430 admixture is an irritant to skin and eyes. Safety glasses and rubber gloves must be worn when handling MasterRoc SA 430 admixture.

Packaging

MasterRoc SA 430 admixture is available by bulk delivery.

Related Documents

Safety Data Sheets: MasterRoc SA 430 admixture

Additional Information

For additional information on MasterRoc SA 430 admixture or its use in developing a high-performance shotcrete mixture, contact your local sales representative.

Master Builders Solutions creates technologies for the construction industry inspiring people to build better. We are active in ~40 countries and operate 35 production sites with over 1,600 employees. We develop, produce, and market high-quality chemical admixtures, as well as adjacent core technologies, to master the challenges of today and support a decarbonized future. Our people are pivotal and pair leading technologies and a strong brand heritage to surpass our customers' expectations and drive continuous value creation.

Limited Warranty Notice

Master Builders Solutions Admixtures US, LLC ("Master Builders Solutions") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS SOLUTIONS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders Solutions. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS SOLUTIONS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders Solutions' present knowledge and experience. However, Master Builders Solutions assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders Solutions reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.