

MasterFinish SRT 4II

Water-based protective agent for the production of exposed aggregate products and flooring for positive applications.

Material description

MasterFinish SRT 4II is a protective, water-based solution that forms a film that prevents splashes of fresh concrete and MasterFinish SRT 480 or 500 surface deactivator from adhering to previously prepared surfaces.

MasterFinish SRT 4II also facilitates the cleaning of decorative curbs and inserts made of terracotta, stone, marble, etc.

Once MasterFinish SRT 4II application is complete, it can be removed with a pressurized water jet while washing the floor treated with MasterFinish SRT 480 or 500.

MasterFinish SRT 4II can be used on all surfaces not sensitive to water, such as concrete, stone, wood, paint, plaster, aluminum, plastics, glass, etc.

It leaves no residue after cleaning. When applying to porous hydraulic plasters, it is recommended to perform a preliminary application and rinsing test to ensure the color does not change. If in doubt, it is advisable to use plastic sheeting to protect the surface.

Fields of application

MasterFinish SRT 4II can be used for all applications requiring a positive exposed aggregate concrete effect and is recommended for:

- urban or private traffic areas and pavements (pedestrian areas, squares, parking lots, sidewalks, external stairs, private or shared outdoor paving, garage ramps, etc.);
- production of gardening and street furniture elements with exposed aggregates;
- architectural concrete.

Directions for use

MasterFinish SRT 4II is a ready-to-use product that can be applied by brush or airless spray to the surfaces to be protected. It can be applied to both dry and damp surfaces, even a few hours before concrete is laid, if the substrate is not overly absorbent and if temperature and/or rainfall conditions allow.

Dosage

The approximate coverage is 0.2 - 0.3 liters per m² depending on the type of substrate and the adsorption capacity of the materials.

Wash the application equipment with water.

Packaging and Storage

MasterFinish SRT 4II is available in 18 kg canisters. Storage is recommended at temperatures between +5°C and +30°C.

MasterFinish SRT 4II can be stored in its original packaging at 20°C for one year.

Safety information

For information on the correct and safe use, transport, storage and disposal of the product, consult the most recent Safety Data Sheet.

Other services

For additional technical information, brochures, references, technical reports and technical support please visit www.master-builders-solutions.com/it-it or alternatively contact infomac@masterbuilders.com.

Scan QR code to visit the product page and download the latest version of this technical data sheet and any additional documentation.



MasterFinish SRT 4II

Water-based protective agent for the production of exposed aggregate products and flooring for positive applications.

Disclaimer

Since 16/12/1992, Master Builders Solutions Italia Spa has been operating under a Certified Quality System compliant with the UNI EN ISO 9001 Standard. Furthermore, the Environmental Management System is certified according to the UNI EN ISO 14001 Standard and the Safety Management System is certified according to the UNI ISO 45001 Standard.

For further information, please consult the local Technician of Master Builders Solutions. The technical advice on how to use our products, either written or verbally given, are based on the current state of our scientific and practical expertise, and does not imply the assumption of any guarantee and/or responsibility for the final results of works executed using our products.

Therefore, the customer is not exempted from the exclusive task and responsibility of verifying the suitability of our products for the intended use and purposes.

This version supersedes all the previous ones.

Master Builders Solutions Italia Spa
Via Vicinale delle Corti, 21 – 31100 Treviso – Italia
T +39 0422 429200 F +39 0422 421802
www.master-builders-solutions.com/it-it
e-mail: infomac@masterbuilders.com